

Buyer's Guide 10

Air - Vacuum - Fluid - Chemical - Steam



GROUP	PAGE
Solenoid Valves	2 - 10
Ball Valves	11 - 21
Butterfly Valves	21 - 26
Electric / Pneumatic Actuators / Gearboxes / Accessories	27 - 30
Knife Gate / Gate Valves / Pinch Valves	31 - 33
Globe / Needle / Angle Seat Valves	33
Globe Valve	34
Check Valves / Duck Bill Check Valves	35 - 37
Strainers	37 - 38
Yoshitake Steam Products	39 - 41
Pressure Relief Valves	42
Hawleys Engineering Products / SS Couplers	43
Timers / Auto Drains / Pressure Switch / Din Plugs	44 - 45
Liquid Filled Pressure Gauge	46
Pneumatic Air Service Equipment	47
Pneumatic Valves - Pilot / Mechanical	48 - 51
Pneumatic Silencer / Nylon Tube	52
Pneumatic Fittings - Push-fit	53 - 56
SS316 Push-Fit Fittings	57 - 58
SS316 Screwed Fittings	58 - 59

Approvals



Ph 1300 887 880
Ph 07 3202 6260
Ph 07 3356 1699

sales@processsystems.com.au
sales@npvvalves.com.au
sales@hawleys.com.au

www.valvesonline.com.au
www.npvvalves.com.au
www.hawleys.com.au

2 Way

AIR / FLUID / VACUUM



Model	Function/ Port Size		Orifice	CV	Pressure (Bar) Air & Fluid		Vacuum Hg”	Media Temperature	Material of Construction	Features
	BSP	Ømm	CV	AC	DC					
Normally Closed / Normally Open • Manual Override. SS304										S25 - S26
S25 - 2 - 1.6 - * V	N.C.	1/4	1.6	0.1	0-13	0-13	┆ 27	-10°C 100°C	Body: 304 Stainless Steel.	Air, Fluid & Vacuum.
S26 - 2 - 1.6 - * V	N.O.	1/4	1.6	0.1	0-13	0-13	┆		Seals: Viton Operator: Stainless Steel	Manual Override. Direct Acting. 11VA AC 15W DC IP65

AIR / WATER



Normally Closed · BRASS										
B35 - 2 - 10 - * N	N.C.	1/4	10	2.3	0.3-10	0.3-10	N/A	-5°C	Body: Brass	Air, Fluid
B35 - 3 - 10 - * N		3/8	10	2.3	0.3-10	0.3-10			Operator: Stainless Steel	11VA AC 15W DC IP65
B35 - 4 - 10 - * N		1/2	10	3	0.3-10	0.3-10			Seat: NBR	
B35 - 4 - 14 - * N		1/2	14	5	0.3-10	0.3-10				
B35 - 5 - 14 - * N		3/4	14	5	0.3-10	0.3-10				
B35 - 5 - 20 - * N		3/4	20	10	0.3-16	0.3-16				
B35 - 6 - 20 - * N		1	20	11	0.3-16	0.3-16				
B35 - 7 - 40 - * N		1-1/4	40	28	0.7-16	0.7-16				
B35 - 8 - 40 - * N		1-1/2	40	34	0.7-16	0.7-16		80°C		
B35 - 9 - 50 - * N	N.C.	2	50	50	0.7-16	0.7-16				

AIR / WATER




Normally Closed · Manual Override · BRASS										
B35M - 4 - 14 - * N	N.C.	1/2	14	5	0.3-10	0.3-10	N/A	-5°C	Body: Brass	Air, Fluid
B35M - 5 - 20 - * N		3/4	20	10	0.3-16	0.3-16			Operator: Stainless Steel	11VA AC 15W DC IP65
B35M - 6 - 20 - * N		1	20	11	0.3-16	0.3-16			Seals: NBR	
B35M - 7 - 40 - * N		1 1/4	40	28	0.7-16	0.7-16				
B35M - 8 - 40 - * N		1 1/2	40	34	0.7-16	0.7-16				
B35M - 9 - 50 - * N	N.C.	2	50	50	0.7-16	0.7-16		80°C		

AIR / WATER



Normally Open · BRASS										
B36 - 2 - 14 - * N	N.O.	1/4	14	3	0.3-10	0.3-10	N/A	-5°C	Body: Brass	Air, Fluid
B36 - 3 - 14 - * N		3/8	14	4	0.3-10	0.3-10			Operator: Stainless Steel	11VA AC 15W DC
B36 - 4 - 14 - * N		1/2	14	5	0.3-10	0.3-10			Seat: NBR	Part #s B36-7 to B36-9 20VA AC 17W DC 24V 21W DC 12V IP65
B36 - 5 - 20 - * N		3/4	20	10	0.3-16	0.3-16				
B36 - 6 - 20 - * N		1	20	11	0.3-16	0.3-16				
B36 - 7 - 40 - * N		1-1/4	40	28	0.7-16	0.7-16				
B36 - 8 - 40 - * N		1-1/2	40	34	0.7-16	0.7-16				
B36 - 9 - 50 - * N	N.O.	2	50	50	0.7-16	0.7-16		80°C		

AIR / WATER



Normally Closed / Normally Open · Cast Iron										
C85 - 8 - 40 - *	N.C.	1-1/2	40		1.5-12	1.5-12	N/A	5°C	Body: C = Cast Iron	Air & Fluid
C85 - 9 - 50 - *		2	50		1.5-12	1.5-12			Seals: Reinforced Natural Rubber.	Adjustable Closing Time
C85 - 11 - 80 - *		3	80		1.5-12	1.5-12			Operator: Brass & Stainless Steel	Anti Water Hammer.
C85 - 11F - 80 - *		Flange	80		1.5-12	1.5-12				11VA AC 15W DC IP65
C85 - 12F - 100 - *		Flange	100		1.5-12	1.5-12				
C85 - 14F - 150 - *	N.C.	Flange	150		1.5-12	1.5-12				
C86 - 8 - 40 - *	N.O.	1-1/2	40		1.5-12	1.5-12				
C86 - 9 - 50 - *		2	50		1.5-12	1.5-12				
C86 - 11 - 80 - *		3	80		1.5-12	1.5-12				
C86 - 11F - 80 - *		Flange	80		1.5-12	1.5-12				
C86 - 12F - 100 - *		Flange	100		1.5-12	1.5-12				
C86 - 14F - 150 - *	N.O.	Flange	150		1.5-12	1.5-12		50°C	Flanges – Table D	

2 Way / 2 Position Air · Water · Vacuum Normally Closed (N.C.) & Normally Open (N.O.)

2 Way

AIR / WATER / VACUUM



Normally Closed · SS304

Model	Function/ Port Size BSP	Orifice Ømm	CV	Pressure (Bar) Air & Fluid		Vacuum Hg"	Media Temperature	Material of Construction	Features
				AC	DC				
ES55 - 1 - 1 - * V	N.C.	1/8	1.0	0.04	0-25	0-25	27	Body: 304 Stainless Steel. Seals: Viton Operator: Stainless Steel	Air, Fluid & Vacuum. Direct Acting. 11VA AC 15W DC IP65
ES55 - 2 - 2 - * V		1/4	2.0	0.10	0-16	0-16			
ES55 - 2 - 3 - * V		1/4	3.0	0.20	0-10	0-10			
ES55 - 2 - 4 - * V	N.C.	1/4	4.0	0.40	0-6	0-6			

AIR / WATER / VACUUM



Normally Closed · SS304

Model	Function/ Port Size BSP	Orifice Ømm	CV	Pressure (Bar) Air & Fluid		Vacuum Hg"	Media Temperature	Material of Construction	Features
				AC	DC				
ES55 - 4 - 16 - * N	N.C.	1/2	16	4.8	0-5	0-5	27	Body: 304 Stainless Steel. Seals: NBR Operator: Stainless Steel	Air, Fluid & Vacuum. 304 Body (Optional 316SS) Zero Differential 33VA AC 20W DC ES55-7 to 9 28VA AC 30W DC IP65
ES55 - 5 - 20 - * N		3/4	20	7.6	0-5	0-5			
ES55 - 6 - 25 - * N		1	25	12	0-5	0-5			
ES55 - 7 - 35 - * N		1-1/4	35	24	0-5	0-5			
ES55 - 8 - 40 - * N		1-1/2	40	29	0-5	0-5			
ES55 - 9 - 50 - * N	N.C.	2	50	48	0-5	0-5			

AIR / WATER / VACUUM



Normally Open · SS304

Model	Function/ Port Size BSP	Orifice Ømm	CV	Pressure (Bar) Air & Fluid		Vacuum Hg"	Media Temperature	Material of Construction	Features
				AC	DC				
ES56 - 4 - 16 - * N	N.O.	1/2	16	4.8	0-5	0-5	27	Body: 304 Stainless Steel. Seals: NBR Operator: Stainless Steel	Air, Fluid & Vacuum. 304 Body (Optional 316SS) Zero Differential 45VA AC 30W DC IP65
ES56 - 5 - 20 - * N		3/4	20	7.6	0-5	0-5			
ES56 - 6 - 25 - * N		1	25	12	0-5	0-5			
ES56 - 6 - 25 - * N	N.O.	1	25	12	0-5	0-5			

POTABLE WATER



Normally Closed · SS316 (Watermark Approved)

Model	Function/ Port Size BSP	Orifice Ømm	CV	Pressure (Bar) Air & Fluid		Vacuum Hg"	Media Temperature	Material of Construction	Features
				AC	DC				
W35 - 4 - 14 - * E	N.C.	1/2	14	5	0.25 - 16	0.25 - 16	27	Body: 316 Stainless Steel. Seat: EPDM W WMKA 26321 SPEC 30	Air, Fluid, Potable Water 27VA AC 18W DC IP65
W35 - 5 - 20 - * E		3/4	20	10	0.25 - 16	0.25 - 16			
W35 - 6 - 25 - * E		1	25	11	0.25 - 16	0.25 - 16			
W35 - 7 - 40 - * E		1-1/4	40	28	0.7 - 16	0.7 - 16			
W35 - 8 - 40 - * E		1-1/2	40	34	0.7 - 16	0.7 - 16			
W35 - 9 - 50 - * E	N.C.	2	50	50	0.7 - 16	0.7 - 16			

POTABLE WATER



Normally Open · SS316 (Watermark Approved)

Model	Function/ Port Size BSP	Orifice Ømm	CV	Pressure (Bar) Air & Fluid		Vacuum Hg"	Media Temperature	Material of Construction	Features
				AC	DC				
W36 - 4 - 14 - * E	N.O.	1/2	14	5	0.25 - 16	0.25 - 16	27	Body: 316 Stainless Steel. Seat: EPDM W WMKA 26321 SPEC 30	Air, Fluid, Potable Water 27VA AC 18W DC IP65
W36 - 5 - 20 - * E		3/4	20	10	0.25 - 16	0.25 - 16			
W36 - 6 - 25 - * E		1	25	11	0.25 - 16	0.25 - 16			
W36 - 7 - 40 - * E		1-1/4	40	28	0.7 - 16	0.7 - 16			
W36 - 8 - 40 - * E		1-1/2	40	34	0.7 - 16	0.7 - 16			
W36 - 9 - 50 - * E	N.O.	2	50	50	0.7 - 16	0.7 - 16			

2 Way

STEAM / HIGH TEMP



Model	Function/ Port Size		Orifice	CV	Pressure (Bar) Air & Fluid		Media Temperature		Material of Construction	Features
	BSP	Ømm	CV	STEAM	OIL	STEAM	AIR/OIL			
Normally Closed • BRASS - Optional DIN IP65 Coil										B75
B75 - 2 - 3 - * TF	N.C.	1/4	3	0.26	0-10	0-10	-10°C	-10°C	Body: Brass Seals: PTFE Operator: Stainless Steel Type H Coil IP55	Steam (180°C) Air & Oil (200°C) High Temp. Piston Type.
B75 - 2 - 5 - * TF		1/4	5	0.64	0-5	0-5				
B75 - 3 - 4 - * TF		3/8	4	0.58	0-7	0-7				
B75 - 4 - 15 - * TF		1/2	15	4.5	0.5-10	0.5-20				
B75 - 5 - 20 - * TF		3/4	20	9.3	0.5-10	0.5-20				
B75 - 6 - 25 - * TF		1	25	13.2	0.5-10	0.5-20			Flying Lead HT Coil Standard	B75-2 9VA AC 8W DC B75-3 to B75-9 33VA AC 25W DC
B75 - 7 - 35 - * TF	1-1/4	35	26	0.5-10	0.5-20					
B75 - 8 - 35 - * TF	N.C. 1-1/2	35	26	0.5-10	0.5-20	180°C	200°C			
2" 20 Bar available in SS304 (S75 - 9 - 50 - * T)									Optional: DIN Plug	IP55

STEAM / HIGH TEMP



Normally Closed • SS304 - Optional DIN IP65 Coil									S75	
S75 - 4 - 15 - * TF	N.C.	1/2	15	4.5	0.5-10	0.5-20	-10°C	-10°C	Body: 304SS Option: 316SS Seals: PTFE Operator: Stainless Steel Type H Coil IP55 Flying Lead HT Coil Standard Optional: DIN Plug	Steam (180°C) Air & Oil (200°C) High Temp. Piston Type. 33VA AC 25W DC Optional: High Temp. to 250°C IP55
S75 - 5 - 20 - * TF		3/4	20	9.3	0.5-10	0.5-20				
S75 - 6 - 25 - * TF		1	25	13.2	0.5-10	0.5-20				
S75 - 7 - 35 - * TF		1-1/4	35	26	0.5-10	0.5-20				
S75 - 8 - 35 - * TF		1-1/2	35	26	0.5-10	0.5-20				
S75 - 9 - 50 - * TF	N.C.	2	50	48	0.5-10	0.5-20	180°C	200°C		
Flange option available on request										

316 STAINLESS STEEL



Normally Closed • SS316										SS75	
SS75 - 4 - 15 - * TF	N.C.	1/2	15	4.5	0.5-10	0.5-20	-10°C	-10°C	Body: 316SS Seals: PTFE Operator: Stainless Steel Type H Coil IP55 Flying Lead HT Coil Standard Optional: DIN Plug	Steam (180°C) Air & Oil (200°C) High Temp. Piston Type. 33VA AC 25W DC IP55	
SS75 - 5 - 20 - * TF		3/4	20	9.3	0.5-10	0.5-20					
SS75 - 6 - 25 - * TF		1	25	13.2	0.5-10	0.5-20					
SS75 - 7 - 35 - * TF		1-1/4	35	26	0.5-10	0.5-20					
SS75 - 8 - 35 - * TF	1-1/2	35	26	0.5-10	0.5-20						
SS75 - 9 - 50 - * TF	N.C.	2	50	48	0.5-10	0.5-20	180°C	200°C			
Flange option available on request											

VERY HIGH TEMP



Normally Closed · SS304									S75T
S75T - 4 - 15 - * TF	N.C.	1/2	15	4.5	0.5-25	-10°C	-10°C	Body: 304SS Seals: RTFE (PTFE + Metal) Operator: Stainless Steel Type H Coil IP55 Flying Lead HT Coil Standard Optional: DIN Plug	Steam (200°C) Air & Oil (250°C) High Temp. Piston Type. 33VA AC 25W DC IP55
S75T - 5 - 20 - * TF		3/4	20	9.3	0.5-25				
S75T - 6 - 25 - * TF		1	25	13.2	0.5-25				
S75T - 8 - 35 - * TF		1-1/2	35	26	0.5-25				
S75T - 9 - 50 - * TF	N.C.	2	50	48	0.5-25	225°C	225°C		

High Pressure

AIR / FLUID



Model	Function/ Port Size		Orifice	CV	Pressure (Bar) Air & Fluid		Vacuum Hg”	Media Temperature	Material of Construction	Features
	BSP	Ømm	CV	AC	DC					
	Normally Closed. BRASS									
B55H - 2 - 1.2 * T B55H - 2 - 1.6 * T B55H - 2 - 2 - * T B55H - 2 - 3 - * T B55H - 2 - 4 - * V B55H - 2 - 5 - * V	N.C. N.C.	1/4 1/4	1.2 1.6 2 3 4 5	0.07 0.09 0.11 0.26 0.58 0.64	0-150 0-80 0-60 0-40 0-20 0-15	0-105 0-56 0-42 0-28 0-14 0-10	27 27	-10°C 120°C	Body: Brass Seals: Teflon Viton 2-4/2-5	Air, Fluid & Vacuum Direct Acting Standard (E16H coil) -T 45VA AC 30W DC DIN Plug IP65 Optional (C3 coil) -TF 55VA AC 33W DC Flying Lead IP54

AIR / FLUID



Normally Closed. SS316									
S55H - 2 - 1.2 * T	N.C.	1/4	1.2	0.07	0-150	0-105	27	-10°C 120°C	Body: 316 Stainless Steel. Seals: Teflon Viton 2-4/2-5 Air, Fluid & Vacuum Direct Acting Standard (E16H coil) -T 45VA AC 30W DC DIN Plug IP65 Optional (C3 coil) -TF 55VA AC 33W DC Flying Lead IP54
S55H - 2 - 1.6 * T			1.6	0.09	0-80	0-56			
S55H - 2 - 2 * T			2	0.11	0-60	0-42			
S55H - 2 - 3 * T			3	0.26	0-40	0-28			
S55H - 2 - 4 * V			4	0.58	0-20	0-14			
S55H - 2 - 5 * V	N.C.	1/4	5	0.64	0-15	0-10			

AIR / FLUID



Normally Closed • BRASS										B75-B75H-B75HH	
B75 - 4 - 15 - * T	N.C.	1/2	15	4.5	0.5-20	0.5-20	N/A	-10°C	Body: Brass	Air, Fluid	
B75 - 5 - 20 - * T		3/4	20	9.3	0.5-20	0.5-20					
B75 - 6 - 25 - * T		1	25	13.2	0.5-20	0.5-20					
B75 - 7 - 35 - * T		1 1/4	35	26	0.5-20	0.5-20					
B75 - 8 - 35 - * T	N.C.	1 1/2	35	26	0.5-20	0.5-20		120°C	Seals: Teflon	High Press. Piston Type.	
2" 20 Bar available in SS304 (S75 - 9 - 50 - * T)									Operator: Stainless Steel	DIN plug IP65	
B75H - 4 - 15 - * T	N.C.	1/2	15	4.5	0.5-40	0.5-40	N/A	-10°C			
B75H - 5 - 20 - * T		3/4	20	9.3	0.5-40	0.5-40					
B75H - 6 - 25 - * T		1	25	13.2	0.5-40	0.5-40					
B75H - 7 - 35 - * T		1 1/4	35	26	0.5-40	0.5-40					
B75H - 8 - 35 - * T	1 1/2	35	26	0.5-40	0.5-40						
B75H - 9 - 50 - * T		2	50	48	0.5-40	0.5-40					
B75HH - 4 - 15 - * T		1/2	15	4.5	0.5-80	0.5-80	N/A	120°C			
B75HH - 5 - 20 - * T		3/4	20	9.3	0.5-80	0.5-80					
B75HH - 6 - 25 - * T		1	25	13.2	0.5-80	0.5-80					
B75HH - 7 - 35 - * T	1 1/4	35	26	0.5-80	0.5-80						
B75HH - 8 - 35 - * T	1 1/2	35	26	0.5-80	0.5-80						
B75HH - 9 - 50 - * T	N.C.	2	50	48	0.5-80	0.5-80			24.4VA AC	25W DC	

AIR / FLUID



Normally Closed • SS304								S75		
S75 - 4 - 15 - * T	N.C.	1/2	15	4.5	0.5-20	0.5-20	N/A	-10°C	Body: 304 SS	Air, Fluid
S75 - 5 - 20 - * T		3/4	20	9.3	0.5-20	0.5-20				High Press. Piston Type.
S75 - 6 - 25 - * T		1	25	13.2	0.5-20	0.5-20				
S75 - 7 - 35 - * T		1 1/4	35	26	0.5-20	0.5-20				
S75 - 8 - 40 - * T	1 1/2	40	26	0.5-20	0.5-20	Operator: Stainless Steel	24.4VA AC 25W DC IP65			
S75 - 9 - 50 - * T	N.C.	2	50	48	0.5-20			0.5-20	180°C	
Flange option available on request										

OTHER VALVES TO 150BAR AVAILABLE


2 Way

PETROCHEMICAL



Model	Function/ Port Size		Orifice	CV	Pressure (Bar) Air & Fluid		Vacuum Hg"	Media Temperature	Material of Construction	Features
	BSP	Ømm		CV	AC	DC				
Normally Closed • BRASS • Direct Acting • Manual Override										
B55M										
B55M - 4 - 15 - * V	N.C.	1/2	15	4.5	0-10	0-10	27	-10°C	Body: Brass Seals: Viton (std) Operator: Stainless Steel Maunual Override (T Bar Type)	Air, Fluid & Vacuum Optional: Explosion proof (See pages 7) 24.4VA AC 25W DC IP65
B55M - 5 - 20 - * V		3/4	20	9.3	0-10	0-10				
B55M - 6 - 25 - * V		1	25	13.2	0-10	0-10				
B55M - 7 - 35 - * V		1-1/4	35	26	0-10	0-10				
B55M - 8 - 35 - * V		1-1/2	35	26	0-10	0-10				
B55M - 9 - 50 - * V	N.C.	2	50	48	0-7	0-7	100°C			

PETROCHEMICAL / AGGRESSIVE FLUIDS · Normally Closed · SS316 - Coupled Diaphragm · Manual Override S55M



S55M - 4 - 15 - * V	N.C.	1/2	15	4.5	0-10	0-10	27	-10°C 100°C	Body: 316 Stainless Steel Seals: Viton (std.) Silicone. EPDM Operator: Stainless Steel Maanual Override (T Bar Type)	Air, Fluid & Vacuum. Zero Differential Optional: Explosion proof coils. (Page 7) 24.4VA AC 25W DC IP65
S55M - 5 - 20 - * V		3/4	20	9.3	0-10	0-10				
S55M - 6 - 25 - * V		1	25	13.2	0-10	0-10				
S55M - 7 - 35 - * V		1-1/4	35	26	0-10	0-10				
S55M - 8 - 35 - * V		1-1/2	35	26	0-10	0-10				
S55M - 9 - 50 - * V	N.C.	2	50	48	0-7	0-7				
Flanged available										

Solenoid Valves - 2/2 Way

Explosive Atmospheres Explosive Dust Environments Ex e Mb IIC T4 Gb and Ex tb mb IIIC T130°C Db



Ex

AIR / FLUID / PETROCHEMICAL Normally Closed · BRASS



Model	Function/ Port Size		Orifice	CV	Pressure (Bar) Air & Fluid		Vacuum Hg”	Media Temperature	Material of Construction	Features
	BSP	Ømm		CV	AC	DC				
EMICAL Normally Closed • BRASS										B55 Ex
B55EX - 3 - 4 - * V	N.C.	3/8	4	0.58	0-10	0-10	27	-10°C	Body: Brass	Air, Fluid
B55EX - 3 - 6 - * V		3/8	6	0.79	0-5	0-5			Vacuum	
B55EX - 3 - 8 - * V		3/8	8	0.97	0-2	0-2			Seals	
B55EX - 4 - 6 - * V		1/2	6	0.79	0-5	0-5			Viton (std)	
B55EX - 4 - 8 - * V		1/2	8	0.97	0-2	0-2			EPDM	
B55EX - 4 - 15 - * V		1/2	15	4.5	0-10	0-10			Silicone	Zero Differential.
B55EX - 5 - 20 - * V		3/4	20	9.3	0-10	0-10			PTFE	Vacuum.
B55EX - 6 - 25 - * V		1	25	13.2	0-10	0-10			(Models 3-4 to 4-8)	Low pressure
B55EX - 7 - 35 - * V		1 1/4	35	26	0-10	0-10			220-240v 50/60Hz,	& Tank Drain
B55EX - 8 - 35 - * V		1 1/2	35	26	0-10	0-10			220v DC	IP65
B55EX - 9 - 50 - * V	N.C.	2	50	48	0-7	0-7		40°C	110-120v 50/60Hz,	ICEX PTB 15.0015 X
									110v DC	ATEX 2027X PTB 11
									24v 50Hz, 24v DC	100% ED
									Manual Override	-40°C to +60°C
									Optional	

AIR / FLUID / PETROCHEMICAL Normally Closed · SS316



EMICAL Normally Closed • SS316										S55 Ex	
S55EX - 3 - 4 - * V	N.C.	3/8	4	0.58	0-10	27	-10°C	316SS Body	Air, Fluid		
S55EX - 3 - 6 - * V		3/8	6	0.79	0-5			Seals	Vacuum		
S55EX - 3 - 8 - * V		3/8	8	0.97	0-2			Viton (std)	Zero Differential.		
S55EX - 4 - 6 - * V		1/2	6	0.79	0-5			Silicone	Vacuum.		
S55EX - 4 - 8 - * V		1/2	8	0.97	0-2			EPDM	Low pressure		
S55EX - 4 - 15 - * V		1/2	15	4.5	0-10			PTFE	& Tank Drain		
S55EX - 5 - 20 - * V		3/4	20	9.3	0-10			(Models 3-4 to 4-8)	IP65		
S55EX - 6 - 25 - * V		1	25	13.2	0-10			220-240v 50/60Hz, 220v DC	ICEX PTB 15.0015 X		
S55EX - 7 - 35 - * V		1 1/4	35	26	0-10			110-120v 50/60Hz, 110v DC	ATEX 2027X PTB 11		
S55EX - 8 - 35 - * V		1 1/2	35	26	0-10				100% ED		
S55EX - 9 - 50 - * V	N.C.	2	50	48	0-7		40°C		-40°C to +60°C		
Flange option available on request								24v 50Hz, 24v DC Manual Override Optional			

Copy of certification can be downloaded from website... www.valvesonline.com.au

Air / Fluid 2-3 Way

Model	Function/ Port Size BSP	Orifice Ømm	CV CV	Pressure (Bar) Air & Fluid		Vacuum Hg"	Media Temperature	Material of Construction	Features
				AC	DC				

AIR / FLUID

Normally Closed · GR NYLON

P55

P55 - 4 - 16 - *V P55 - 5 - 20 - *V P55 - 6 - 25 - *V	N.C. I N.C.	1/2 3/4 1	16 20 25	0-6 0-6 0-6	0-6 0-6 0-6	27	5°C I 65°C	Body: Glass Reinforced Nylon Seals: Viton Operator: Stainless Steel	Air & Fluid. 33VA AC 20W DC IP65
---	-------------------	-----------------	----------------	-------------------	-------------------	----	------------------	---	---



AIR

3/2 Way Normally Closed · Manual Override · ZINC

Z17

Z17 - 1 - 1 - * NM	N.C.	1/8	1.0	0.04	0-10	0-10	27	5°C - 80°C	Body: Zinc Diecast Seals: NBR Operator: Stainless Steel	Air Manifold up to 10 Valves Manual Override 6VA AC 5W DC IP65
--------------------	------	-----	-----	------	------	------	----	------------	--	--



AIR / FLUID

3/2 Way Normally Closed / Normally Open · SS304

ES57-58

ES57 - 2 - 1.5 - * V ES58 - 2 - 1.5 - * V	N.C. N.O.	1/4 1/4	1.6 1.6	0.20 0.20	0-13 0-13	0-13 0-13	27 27	-10°C I 100°C	Body: 304 Stainless Steel. Seals: Viton Operator: Stainless Steel	Air, Fluid Vacuum. Direct Acting. 11VA AC 15W DC IP65
--	--------------	------------	------------	--------------	--------------	--------------	----------	---------------------	---	---



AIR / FLUID

3/2 Way Normally Closed / Normally Open · SS304 · Manual Override

S27-28

MANUAL OVERRIDE S27 - 2 - 1.6 - * VM S28 - 2 - 1.6 - * VM	N.C. N.O.	1/4 1/4	1.6 1.6	0.20 0.20	0-13 0-13	0-13 0-13	27 27	-10°C I 100°C	Body: 304 Stainless Steel. Seals: Viton Operator: Stainless Steel	Air, Fluid Vacuum. Direct Acting. Manual Override 11VA AC 15W DC IP65
---	--------------	------------	------------	--------------	--------------	--------------	----------	---------------------	---	--



AIR / HIGH PRESSURE

3/2 Way Normally Closed - Manual Override · ALUMINIUM · High Flow

A67

A67 - 2 - 8 - * N A67 - 4 - 15 - * N	N.C. N.C.	1/4 1/2	8 12	1.5-24 1.5-24	0.5-24 0.5-24	— —	-5°C 80°C	Body: Aluminium Seals: NBR Operator: Stainless Steel	Air High Flow Manual Override High Pressure. 20VA AC 21W DC IP65
---	--------------	------------	---------	------------------	------------------	--------	------------------	---	--



**Air
5 Way**

AIR



Model	Function/ Port Size		Orifice/CV		Pressure (Bar) Air & Fluid		Description	Media Temperature	Material of Construction	Features	
	BSP		Ømm	CV	AC	DC					
5/2 Solenoid / Spring • ALUMINIUM											A69
A69 - 1 - 5 - *N	5/2	1/8	5	0.67	1.5-8	1.5-8	5/2 Way Solenoid Operated - Spring Return	5°C	Aluminium Body & Spool. POM Ends. Seals: NBR. Operator: Brass & Stainless Steel	Air	
A69 - 2 - 7 - *N	5/2	1/4	7	2	1.5-8	1.5-8		80°C		Manual Override. Lockable High Flow	
A69 - 3 - 7 - *N	5/2	3/8	7	2	1.5-8	1.5-8					
A69 - 4 - 8 - *N	5/2	1/2	8	2.8	1.5-8	1.5-8					6VA AC 5W DC IP65

AIR



5/2 Solenoid / Solenoid • ALUMINIUM A610										
A610 - 1 - 5 - *N	5/2	1/8	5	0.67	1.5-8	1.5-8	5/2 Way Double Solenoid	5°C 80°C	Aluminium Body & Spool. POM Ends. Seals: NBR. Operator: Brass & Stainless Steel	Air Manual Override. Lockable High Flow 6VA AC 5W DC IP65
A610 - 2 - 7 - *N	5/2	1/4	7	2	1.5-8	1.5-8				
A610 - 3 - 7 - *N	5/2	3/8	7	2	1.5-8	1.5-8				
A610 - 4 - 8 - *N	5/2	1/2	8	2.8	1.5-8	1.5-8				

AIR




5/3 Solenoid / Solenoid • Closed Centre • ALUMINIUM A611										
A611 - 2 - 7 - *N	5/3	1/4	7	2	1.5-8	1.5-8	5/3 Way Closed centre	5°C 80°C	Aluminium Body & Spool. POM Ends. Seals: NBR. Operator: Brass & Stainless Steel	Air Manual Override. Lockable High Flow 6VA AC 5W DC IP65
A611 - 3 - 7 - *N	5/3	3/8	7	2	1.5-8	1.5-8				
A611 - 4 - 8 - *N	5/3	1/2	8	2.8	1.5-8	1.5-8				
Optional Open Centre A612-2-7-*N A612-4-8-*N	5/3 5/3	1/4 1/2	7 8	2 2.8	1.5-8 1.5-8	1.5-8 1.5-8				

AIR




Manifold. ALUMINIUM SM										
EXAMPLE SM02 - 01 SM03 - 02 SM03 - 03 SM03 - 04	2 station 1/8" BSP 3 station 1/4" BSP 3 station 3/8" BSP 4 station 1/2" BSP		STATIONS 2-12 Any type or valve style 5/2 way or 5/3 way can be manifolded.				Extruded Aluminium			
BP Valve port size 1/8" = 01 1/4" = 02 3/8" = 03 1/2" = 04	Blanking Plate		Also mixed solenoid/spring & double solenoid can be mounted on the one manifold. Specials: - Up to 15 stations							

AIR



5/2 NAMUR Solenoid / Spring • Manual Override. ALUMINIUM								ENS	
ENS12*5 Solenoid/Spring	1/4	5	1.4	1.5-8	1.5-8	Solenoid/ Spring Return	5°C 80°C	Body & Spool: Aluminium POM Ends. Seals: NBR	Air
END12*5 Solenoid/Solenoid	1/4	5	1.4	1.5-8	1.5-8	Solenoid/ Solenoid			Manual Override. Lockable High Flow
Optional 3/2 Converter Plate									6VA AC 5W DC
									IP65

AIR



5/2 Air Pilot. NAMUR • ALUMINIUM								ANP	
ANPS - 2 - 5 - N ANPP - 2 - 5 - N	1/4 1/4	5 5	1.4 1.4	1.5-8 1.5-8	1.5-8 1.5-8	Pilot/Spr. Pilot/Pilot	5°C 80°C	Body & Spool: Aluminium POM Ends. Seals: NBR	Air IP65
Optional 3/2 Converter Plate ENSAP 3-2									



AIR



AIR



AIR



AIR



AIR



AIR



AIR



AIR



Model	Function/ Port Size		Orifice CV		Pressure (Bar) Air & Fluid		Vacuum Hg"	Media Temperature	Material of Construction	Features
	BSP		Ømm	CV	AC	DC				
3/2, 5/2 NAMUR Solenoid / Spring • Manual Override • Aluminium Body										ALV
ALV510F3 - C5 - * Ex	3/2 5/2	1/4	6	1.1	2-8	2-8	–	-10°C +60°C	Body & Housing: Aluminium Seats: NBR 220-240v 50/60Hz 110-120v 50/60Hz 24v DC 4VA 2.5W	NAMUR Ex d IIc T6 IEC Ex CQM 12.022X IP66 M20 x 1.5 Gland
Converter Plate Included 3/2 + 5/2 Optional: Ex NEPSI Intrinsically Safe										
3/2, 5/2 NAMUR Solenoid / Solenoid • Manual Override • Aluminium Body										ALV
ALV520F3 - C5 - * Ex	3/2 5/2	1/4	6	1.1	2-8	2-8	–	-10°C +60°C	Body & Housing: Aluminium Seats: NBR 220-240v 50/60Hz 110-120v 50/60Hz 24v DC 4VA 2.5W	NAMUR Ex d IIc T6 IEC Ex CQM 12.022X IP66 M20 x 1.5 Gland
Converter Plate Included 3/2 + 5/2 Optional: Ex NEPSI Intrinsically Safe										
3/2, 5/2 NAMUR Solenoid / Spring • Manual Override • SS316 Body										ALV
ALV610F3 - C4 - * Ex	3/2 5/2	1/4	6	1.1	2-8	2-8	–	-10°C +60°C	Body & Housing: SS316 Seats: NBR 220-240v 50/60Hz 110-120v 50/60Hz 24v DC 4VA 2.5W	NAMUR Ex d IIc T6 IEC Ex CQM 12.022X IP66 M20 x 1.5 Gland
Converter Plate Included 3/2 + 5/2 Optional: Ex NEPSI Intrinsically Safe										
3/2, 5/2 NAMUR Solenoid / Solenoid • Manual Override • SS316 Body										ALV
ALV620F3 - C4 - * Ex	3/2 5/2	1/4	6	1.1	2-8	2-8	–	-10°C +60°C	Body & Housing: SS316 Seats: NBR 220-240v 50/60Hz 110-120v 50/60Hz 24v DC 4VA 2.5W	NAMUR Ex d IIc T6 IEC Ex CQM 12.022X IP66 M20 x 1.5 Gland
Converter Plate Included 3/2 + 5/2 Optional: Ex NEPSI Intrinsically Safe										
5/2 IN-LINE Solenoid / Spring • Manual Override • Aluminium Body										ALV
ALV510P2 - C5 - * Ex	5/2	1/4	6	1.1	2-8	2-8	–	-10°C +60°C	Body & Housing: Aluminium Seats: NBR 220-240v 50/60Hz 110-120v 50/60Hz 24v DC 4VA 2.5W	Body Ported Ex d IIc T6 IEC Ex CQM 12.022X IP66 M20 x 1.5 Gland
Optional: Ex NEPSI Intrinsically Safe										
5/2 IN-LINE Solenoid / Solenoid • Manual Override • Aluminium Body										ALV
ALV520P2 - C5 - * Ex	5/2	1/4	6	1.1	2-8	2-8	–	-10°C +60°C	Body & Housing: Aluminium Seats: NBR 220-240v 50/60Hz 110-120v 50/60Hz 24v DC 4VA 2.5W	Body Ported Ex d IIc T6 IEC Ex CQM 12.022X IP66 M20 x 1.5 Gland
Optional: Ex NEPSI Intrinsically Safe										
5/2 IN-LINE Solenoid / Spring • Manual Override • SS316 Body										ALV
ALV610P2 - C4 - * Ex	5/2	1/4	6	1.1	2-8	2-8	–	-10°C +60°C	Body & Housing: SS316 Seats: NBR 220-240v 50/60Hz 110-120v 50/60Hz 24v DC 4VA 2.5W	Body Ported Ex d IIc T6 IEC Ex CQM 12.022X IP66 M20 x 1.5 Gland
Optional: Ex NEPSI Intrinsically Safe										
5/2 IN-LINE Solenoid / Solenoid • Manual Override • SS316 Body										ALV
ALV620P2 - C4 - * Ex	5/2	1/4	6	1.1	2-8	2-8	–	-10°C +60°C	Body & Housing: SS316 Seats: NBR 220-240v 50/60Hz 110-120v 50/60Hz 24v DC 4VA 2.5W	Body Ported Ex d IIc T6 IEC Ex CQM 12.022X IP66 M20 x 1.5 Gland
Optional: Ex NEPSI Intrinsically Safe										

PVC

AIR / FLUID / AQUACULTURE Manual Handle · PVC

BLP

Model	Orifice Ømm	Port Size BSP	Actuator	Media Pressure	Media Temperature	Actuator Air Pressure /Voltage	Material of Construction	Features
 Series BLP PVC Body	BLP4B - L - E BLP5B - L - E BLP6B - L - E BLP7B - L - E BLP8B - L - E BLP9B - L - E BLP10B - L - E BLP11B - L - E BLP12B - L - E	15 20 25 32 40 50 65 80 100	1/2 3/4 1 1-1/4 1-1/2 2 2-1/2 3 4	Manual Handle	Vacuum 10 BAR	0°C 60°C	MANUAL HANDLE UPVC Body (std.) (Also PP & PVDF) PTFE Seats O-rings EPDM (Std) Viton	True Union with Safety Block. Threaded OR Solvent Weld ANSI Flange
• B = BSP • S = Solvent Weld • F = Flanged								

AIR / FLUID / AQUACULTURE Double Acting Pneumatic · PVC

BLPDA

	Series BLP	BLP4B - DA - E	15	1/2	DA50	Vacuum	0°C	6-8 BAR	UPVC Body (std.) (Also PP & PVDF)	True Union with Safety Block. Stainless Steel Adaptor and Yoke. BSP or Solvent Weld Actuator std. aluminium Optional Stainless Steel
		BLP5B - DA - E	20	3/4	DA50					
		BLP6B - DA - E	25	1	DA50					
		BLP7B - DA - E	32	1-1/4	DA63					
		BLP8B - DA - E	40	1-1/2	DA63					
		BLP9B - DA - E	50	2	DA63					
		BLP10B - DA - E	65	2-1/2	DA75					
		BLP11B - DA - E	80	3	DA75					
		BLP12B - DA - E	100	4	DA75	10 BAR	60°C	6-8 BAR	Threaded, Solvent Weld	
		Double Acting PVC Body	Viton available, change 'E' to 'V' • B = BSP • S = Solvent Weld • F = Flanged							

AIR / FLUID / AQUACULTURE Spring Return Pneumatic · PVC

BLPSR

	Series BLP Single Acting PVC Body	BLP54B - SR - E	15	1/2	SR50	Vacuum	0°C	6-8 BAR	UPVC Body (std.) (Also PP & PVDF)	True Union with Safety Block. Stainless Steel Adaptor and Yoke. BSP or Solvent Weld Actuator std. aluminium Optional Stainless Steel				
		BLP55B - SR - E	20	3/4	SR50				PTFE Seats O-rings EPDM (Std) Viton					
		BLP56B - SR - E	25	1	SR50									
		BLP57B - SR - E	32	1-1/4	SR63									
		BLP58B - SR - E	40	1-1/2	SR63									
		BLP59B - SR - E	50	2	SR75									
		BLP10B - SR - E	65	2-1/2	SR75									
		BLP11B - SR - E	80	3	SR88									
		BLP12B - SR - E	100	4	SR88						10 BAR	60°C	6-8 BAR	Threaded, Solvent Weld
		For normally open function change 4th digit to 6 • B = BSP • S = Solvent Weld • F = Flanged												

AIR / FLUID / AQUACULTURE Electric On/Off · PVC

BLPE

	Series BLP	BLP4B - E* - E	15	1/2	OM-1	VACUUM	0°C	E1=240VAC	UPVC Body (std.) (Also PP & PVDF)	True Union with Safety Block. Stainless Steel Adaptor and Yoke.
		BLP5B - E* - E	20	3/4	OM-1			E2=110VAC		
		BLP6B - E* - E	25	1	OM-1			E5=24VAC		
		BLP7B - E* - E	32	1-1/4	OM-1			E7=12VDC		
		BLP8B - E* - E	40	1-1/2	OM-1			E8=24VDC		
		BLP9B - E* - E	50	2	OM-1			E11=415V		
		BLP10B - E* - E	65	2-1/2	OM-A			IP67		
		BLP11B - E* - E	80	3	OM-A					
		BLP12B - E* - E	100	4	OM-A					
		• B = BSP • S = Solvent Weld • F = Flanged								

AIR / FLUID / AQUACULTURE Manual / Pneumatic / Electric · Flange · PVC

BLPF

Model	Orifice Ømm	Port Size BSP	Actuator	Media Pressure	Media Temperature	Actuator Air Pressure /Voltage	Material of Construction	Features
 Series BLPF Flange PVC Body	BLP6F - L - E BLP7F - L - E BLP8F - L - E BLP9F - L - E BLP10F - L - E BLP11F - L - E BLP12F - L - E	25 32 40 50 65 80 100	ANSI 150 FLANGE MANUAL LEVER PNEUMATIC DA / SR ELECTRIC	Vacuum 10 BAR	0°C 60°C		UPVC Body (std.) (Also PP & PVDF) PTFE Seats O-rings EPDM (Std) Viton	True Union with Safety Block. Flange - ANSI Actuation Optional Pneumatic, Electric, Lever & Gear Box

VITON FKM Optional for all Ball Valve O-Rings (Replace 'E' for 'V' in code)
BFP PVC Butterfly Valve See Page 21
BCP PVC Check Valve See Page 35
YSP PVC Y Strainer See Page 37

PVC

Model	Orifice Ømm	Port Size BSP	Actuator	Media Pressure	Media Temperature	Actuator Air Pressure /Voltage	Material of Construction	Features
AIR / FLUID / AQUACULTURE 3 Way • Manual • PVC								
BLP3L4B - L - E BLP3L5B - L - E BLP3L6B - L - E BLP3L7B - L - E BLP3L8B - L - E BLP3L9B - L - E	15 20 25 32 40 50	1/2 3/4 1 1-1/4 1-1/2 2	MANUAL LEVER	Vacuum 10 BAR	0°C 60°C	6-8 BAR 6-8 BAR Air Pressure	UPVC Body PTFE Seats O-rings EPDM (Std) FKM Optional Threaded, Solvent Weld	True Union St.St. Adaptor and Yoke. BSP or Solvent Weld. Manual Lever FKM Optional
3L = 'L' Port • 3T = 'T' Port • B = BSP • S = Solvent Weld • V = FKM								


AIR / FLUID / AQUACULTURE 3 Way • Manual • PVC

BLP3



AIR / FLUID / AQUACULTURE 3 Way • Double Acting • PVC


BLPDA



BLP3L4B - DA - E BLP3L5B - DA - E BLP3L6B - DA - E BLP3L7B - DA - E BLP3L8B - DA - E BLP3L9B - DA - E	15 20 25 32 40 50	1/2 3/4 1 1-1/4 1-1/2 2	DA50 DA50 DA50 DA50 DA63 DA63	Vacuum 10 BAR	0°C 60°C	6-8 BAR 6-8 BAR Air Pressure	UPVC Body PTFE Seats O-rings EPDM FKM Optional Threaded, Solvent Weld	True Union St.St. Adaptor and Yoke. BSP or Solvent Weld. Double Acting Pneumatic Actuated FKM Optional
3L = 'L' Port • 3T = 'T' Port • B = BSP • S = Solvent Weld								

AIR / FLUID / AQUACULTURE 3 Way • Spring Return • PVC

BLPSR



BLP3L4B - SR - E BLP3L5B - SR - E BLP3L6B - SR - E BLP3L7B - SR - E BLP3L8B - SR - E BLP3L9B - SR - E	15 20 25 32 40 50	1/2 3/4 1 1-1/4 1-1/2 2	SR50 SR50 SR50 SR50 SR75 SR75	Vacuum 10 BAR	0°C 60°C	6-8 BAR 6-8 BAR Air Pressure	UPVC Body PTFE Seats O-rings EPDM FKM Optional Threaded, Solvent Weld	True Union St.St. Adaptor and Yoke. BSP or Solvent Weld. Spring Return Pneumatic Actuated FKM Optional
3L = 'L' Port • 3T = 'T' Port • B = BSP • S = Solvent Weld								

AIR / FLUID / AQUACULTURE 3 Way • Electric On/Off • PVC

BLPE



BLP3L4B - E* - E BLP3L5B - E* - E BLP3L6B - E* - E BLP3L7B - E* - E BLP3L8B - E* - E BLP3L9B - E* - E	15 20 25 32 40 50	1/2 3/4 1 1-1/4 1-1/2 2	OM-1 OM-1 OM-1 OM-1 OM-A OM-A	VACUUM 10 BAR	0°C 60°C	E1=240VAC E2=110VAC E5=24VAC E7=12VDC E8=24VDC E11=415V	UPVC Body (std.) (Also PP & PVDF) PTFE Seats O-rings EPDM FKM Optional Threaded, Solvent Weld	True Union with Safety Block. Stainless Steel Adaptor and Yoke. Actuator - see Series 'OM' for details. BSP or Solvent Weld IP67 FKM Optional
• B = BSP • S = Solvent Weld • F = Flanged				Available in Viton				

VITON FKM Optional for all Ball Valve O-Rings (Replace 'E' for 'V' in code)

BFP PVC Butterfly Valve See Page 21
BCP PVC Check Valve See Page 35
YSP PVC Y Strainer See Page 37

BRASS 2pc
Nickle Plated

AIR / FLUID



Model	Orifice Ømm	Port Size BSP	Actuator	Media Pressure	Media Temperature	Material of Construction	Features
Lever • NP Brass						BVB	
BVB2B - L - T BVB3B - L - T BVB4B - L - T BVB5B - L - T BVB6B - L - T BVB7B - L - T BVB8B - L - T BVB9B - L - T BVB10B - L - T BVB11B - L - T BVB12B - L - T	8 10 15 20 25 32 40 50	1/4 3/8 1/2 3/4 1 1-1/4 1-1/2 2	Lever Lever	16 BAR 16 BAR	-20°C 120°C	Body: 2 piece Brass. BSP Threaded. Seats: PTFE	Lever * Not lockable

AIR / FLUID



Handle • NP Brass							MBV
MBVM - 02	8	1/4		Vacuum	0°C	Body: 2 Piece Chrome Plated Brass	Handle
MBVM - 03	8	3/8	HANDLE				
MBVM - 04	10	1/2		16 BAR	80°C		

AIR / FLUID



Handle • NP Brass							MBV
MBVF - 02	8	1/4		Vacuum	0°C	Body: 2 Piece Chrome Plated Brass	Handle
MBVF - 03	8	3/8	HANDLE				
MBVF - 04	10	1/2		16 BAR	80°C		

BLACK 2pc
Forged Steel

AIR / STEAM




Lever • Forged Steel • Class 800 • NPT							BVF
BVF8 - 04	15	1/2	Lever	13.62Mpa @ -29 to 35 deg C	180 deg C @ (1.0Mpa)	Body: Forged Steel Seat: PTFE Gland: RPTE Coating: Black Steel	A105 Forged Steel ASTM B16.34 design ASME B1.20.1 ends API 598 test Class 800 NPT Thread
BVF8 - 05	20	3/4	Lever				
BVF8 - 06	25	1					
BVF8 - 07	32	1-1/4					
BVF8 - 08	40	1-1/2					
BVF8 - 09	50	2					


SS316

AIR / FLUID



Model	Orifice Ømm	Port Size BSP	Actuator	Media Pressure	Media Temperature	Material of Construction	Features			
Lever. Lockable. 2 Piece • SS316							BVS			
BVS2B - L - T	8	1/4	Lever	63 BAR	-20°C	Body: 2 piece 316 Stainless Steel. BSP Threaded. Seats: R PTFE	Lockable Lever			
BVS3B - L - T	10	3/8				API 598 Test				
BVS4B - L - T	15	1/2								
BVS5B - L - T	20	3/4								
BVS6B - L - T	25	1								
BVS7B - L - T	32	1-1/4								
BVS8B - L - T	40	1-1/2								
BVS9B - L - T	50	2								
BVS10B - L - T	65	2-1/2								
BVS11B - L - T	80	3								
BVS12B - L - T	100	4								
							Lever	63 BAR	180°C	

AIR / FLUID / STEAM / PETROCHEMICAL · Dead Man Handles



Kit Model	Valve Sizes	BLS	BLSF	Material of Construction	Features
DMH - 04	1/2"	✓	✓	SS316	Direct Mount Kit. Adjustable Spring Tension By Handle Nut.
DMH - 06	3/4" & 1"	✓	✓		
DMH - 08	1-1/4", 1-1/2" & 2"	✓	✓		
DMH - 11	2-1/2"-3"	✓	✓		
Handles c/w Mounting Kit and Internal Spring		See next page (Page 14)			

**SS316 3 way
Threaded**

Model	Orifice Ømm	Port Size BSP	Actuator	Media Pressure	Media Temperature	Actuator Air Pressure /Voltage	Material of Construction	Features
-------	----------------	------------------	----------	-------------------	----------------------	--------------------------------------	--------------------------------	----------

AIR / FLUID / STEAM / PETROCHEMICAL L Port or T Port. Lever. Lockable. • SS316

BLS3



BLS3L2B - L - RT	9.5	1/4	Lever	63 BAR W.O.G.	-20°C	9mm	Body: 316 Stainless Steel	Compact Design
BLS3L3B - L - RT	9.5	3/8						API 598 Test
BLS3L4B - L - RT	12	1/2						Lockable Lever
BLS3L5B - L - RT	15	3/4						Spring Close Lever Optional for Smaller Sizes
BLS3L6B - L - RT	20	1						W TM Watermark WMK26529
BLS3L7B - L - RT	25	1-1/4						
BLS3L8B - L - RT	32	1-1/2						
BLS3L9B - L - RT	40	2						
BLS3L10B - L - RT	50	2-1/2						
BLS3L11B - L - RT	65	3						
BLS3L12B - L - RT	75	4						

3L = 'L' Port 3T = 'T' Port — For Flanged 3 Way Full Bore to 4" refer to page 16

☐ Shaft

AIR / FLUID / STEAM / PETROCHEMICAL L Port or T Port Gear Box • SS316

BLS3



BLS3L4B - G - RT	15	1/2	GB1	63 BAR W.O.G.	-20°C	Gearbox	Body: 316 Stainless Steel	Compact Design
BLS3L5B - G - RT	20	3/4	GB1					API 598 Test
BLS3L6B - G - RT	25	1	GB1					Gear Box
BLS3L7B - G - RT	32	1-1/4	GB1					SS Trim
BLS3L8B - G - RT	32	1-1/2	GB1	Vacuum	180°C			Visual Indicator
BLS3L9B - G - RT	40	2	GB2					W TM Watermark WMK26529
BLS3L10B - G - RT	50	2-1/2	GB2					
BLS3L11B - G - RT	65	3	GB2	10 BAR Steam				
BLS3L12B - G - RT	75	4	GB2					

3L = 'L' Port 3T = 'T' Port — For Flanged 3 Way Full Bore to 4" refer to page 16 • See Page 29 for Gear Box Specifications

AIR / FLUID / STEAM / PETROCHEMICAL Double Acting Pneumatic • SS316

BLS3DA



BLS3L2B - DA - RT	8	1/4	DA50	63 BAR W.O.G.	-20°C	6-8 BAR	Body: 316 Stainless Steel	Compact Design
BLS3L3B - DA - RT	10	3/8	DA50					API 598 Test
BLS3L4B - DA - RT	12	1/2	DA50					Standard with aluminium actuator.
BLS3L5B - DA - RT	15	3/4	DA50					Optional Stainless Steel Actuator
BLS3L6B - DA - RT	20	1	DA50					W TM Watermark WMK26529
BLS3L7B - DA - RT	25	1-1/4	DA63					
BLS3L8B - DA - RT	32	1-1/2	DA75	Vacuum				
BLS3L9B - DA - RT	43	2	DA75					
BLS3L10B - DA - RT	55	2-1/2	DA88					
BLS3L11B - DA - RT	66	3	DA100	10 BAR Steam	180°C	6-8 BAR Air Pressure		
BLS3L12B - DA - RT	75	4	DA115					

3L = 'L' Port 3T = 'T' Port — For Flanged 3 Way Full Bore to 4" refer to page 16

AIR / FLUID / STEAM / PETROCHEMICAL Spring Return Pneumatic • SS316

BLS3SR



BLS3L2B - SR - RT	8	1/4	SR50	63 BAR W.O.G.	-20°C	6-8 BAR	Body: 316 Stainless Steel	Compact Design
BLS3L3B - SR - RT	10	3/8	SR50					API 598 Test
BLS3L4B - SR - RT	12	1/2	SR50					Standard with aluminium actuator.
BLS3L5B - SR - RT	15	3/4	SR63					Optional Stainless Steel Actuator
BLS3L6B - SR - RT	20	1	SR63					W TM Watermark WMK26529
BLS3L7B - SR - RT	25	1-1/4	SR75					
BLS3L8B - SR - RT	32	1-1/2	SR88	Vacuum				
BLS3L9B - SR - RT	43	2	SR100					
BLS3L10B - SR - RT	55	2-1/2	SR115					
BLS3L11B - SR - RT	66	3	SR125	10 BAR Steam	180°C	6-8 BAR Air Pressure		
BLS3L12B - SR - RT	75	4	SR145					

3L = 'L' Port 3T = 'T' Port — For Flanged 3 Way Full Bore to 4" refer to page 16

AIR / FLUID / STEAM / PETROCHEMICAL Electric On/Off • SS316





BLS3E



BLS3L2B - E* - RT	8	1/4	OM-1	63 BAR W.O.G.	-20°C	E1=240VAC E2=110VAC E5=24VAC E7=12VDC E8=24VDC E11=415VAC	Body: 316 Stainless Steel	API 598 Test
BLS3L3B - E* - RT	10	3/8	OM-1					Electric Actuator
BLS3L4B - E* - RT	12	1/2	OM-1					See Series 'OM' for actuator details
BLS3L5B - E* - RT	15	3/4	OM-1					Also available as Spring Close P27
BLS3L6B - E* - RT	20	1	OM-1					W TM Watermark WMK26529
BLS3L7B - E* - RT	25	1-1/4	OM-1					
BLS3L8B - E* - RT	32	1-1/2	OM-A	Vacuum				
BLS3L9B - E* - RT	43	2	OM-2					
BLS3L10B - E* - RT	55	2-1/2	OM-2					
BLS3L11B - E* - RT	66	3	OM-3	10 BAR Steam	180°C			
BLS3L12B - E* - RT	75	4	OM-4					

3L = 'L' Port 3T = 'T' Port — For Flanged 3 Way Full Bore to 4" refer to page 16

'L' PORT CONFIGURATION 'T' PORT CONFIGURATION



Refer to page 9 & 10 for suitable solenoid control valve

• * For grease and high viscosity applications upsize actuator is recommended.
Consult factory for sizing.

SS316 Fire Safe

ANSI-150 Optional ANSI-300	Orifice Ømm	Flanged ANSI 150	Actuator	Media Pressure	Media Temperature	Actuator Air Pressure /Voltage	Material of Construction	Features
PETROCHEMICAL Lever. Lockable • SS316 ANSI 150 • ANSI 300 BLSF								
 Series BLSF ANSI-150 Flange Lever Handle	BLSF4FA - L - RT	15		20 BAR W.O.G.		9mm	Body: 2 piece 316 Stainless Steel ANSI 150 RF Seats: Filled PTFE	Direct Mount. High Pad Self Adjusting Stem Packing Lockable Lever API 607 6th Edition API 598 Test DMH (Spring Close Lever) optional to 80mm
	BLSF5FA - L - RT	20						
	BLSF6FA - L - RT	25						
	BLSF7FA - L - RT	32						
	BLSF8FA - L - RT	40						
	BLSF9FA - L - RT	50						
	BLSF10FA - L - RT	65						
	BLSF11FA - L - RT	80						
	BLSF12FA - L - RT	100						
	BLSF13FA - L - RT	125						
	BLSF14FA - L - RT	150						
	BLSF15FA - L - RT	200						
	BLSF16FA - L - RT	250						
	BLSF17FA - L - RT	300						
Optional ANSI 300BLSF3 Code contact factory • Spring Close Lever Optional on Smaller Sizes • Spring Close Handle 1/2" ~ 1 1/2"						☐ Shaft		

AIR / FLUID / STEAM / PETROCHEMICAL										Gear Box • SS316		ANSI 150 • ANSI 300		BLSF	
 Series BLSF ANSI-150 Flange Gear Box	BLSF4FA - G - RT	15	ANSI 150 RF	GB1	20 BAR W.O.G.	-20°C	Gearbox	Body: 2 piece 316 Stainless Steel ANSI 150 RF Seats: Filled PTFE	Direct Mount. High Pad Self Adjusting Stem Packing API 607 6th Edition API 598 Test						
	BLSF5FA - G - RT	20		GB1											
	BLSF6FA - G - RT	25		GB1											
	BLSF7FA - G - RT	32		GB1											
	BLSF8FA - G - RT	40		GB1											
	BLSF9FA - G - RT	50		GB1											
	BLSF10FA - G - RT	65		GB2											
	BLSF11FA - G - RT	80		GB2	Vacuum										
	BLSF12FA - G - RT	100		GB2											
	BLSF13FA - G - RT	125		GB3											
	BLSF14FA - G - RT	150		GB3											
	BLSF15FA - G - RT	200		GB4											
	BLSF16FA - G - RT	250		GB5	10 BAR Steam										
	BLSF17FA - G - RT	300		GB6		180°C									
Optional ANSI 300BLSF3 Code contact factory • See Page 29 for Gear Box Specifications															

AIR / FLUID / STEAM / PETROCHEMICAL			Double Acting Pneumatic • SS316			ANSI 150 • ANSI 300		BLSFDA				
 Series BLSF Double Acting 316 Stainless Steel Body	BLSF4FA - DA - RT	15	ANSI 150 RF	DA50	*	20 BAR W.O.G.	-20°C	6-8 BAR	Body: 2 piece 316 Stainless Steel ANSI 150 RF Seats: Filled PTFE Optional: Limit Switch. De-Clutch Gear Box	Direct Mount. High Pad Self Adjusting Stem Packing API 607 6th Edition API 598 Test Actuator- std. aluminium Optional Stainless Steel		
	BLSF5FA - DA - RT	20		DA50								
	BLSF6FA - DA - RT	25		DA50								
	BLSF7FA - DA - RT	32		DA63								
	BLSF8FA - DA - RT	40		DA63								
	BLSF9FA - DA - RT	50		DA75								
	BLSF10FA - DA - RT	63		DA88								
	BLSF11FA - DA - RT	80		DA100								
	BLSF12FA - DA - RT	100		DA115								
	BLSF13FA - DA - RT	125		DA125								
	BLSF14FA - DA - RT	150		DA145								
	BLSF15FA - DA - RT	200		DA160								
	BLSF16FA - DA - RT	250		DA200		10 BAR Steam					180°C	6-8 BAR Air Pressure
	BLSF17FA - DA - RT	300		DA240								
Optional ANSI 300BLSF3 Code contact factory												

AIR / FLUID / STEAM / PETROCHEMICAL Spring Return Pneumatic • SS316 ANSI 150 • ANSI 300 BLSFSR									
 Series BLSF Spring Return 316 Stainless Steel Body	BLSF54FA - SR - RT	15	ANSI 150 RF	SR50 SR63 SR63 SR75 SR75 SR88 SR100 SR115 SR145 SR160 SR180 SR200 SR240 SR270	*	20 BAR W.O.G.	-20°C	6-8 BAR	Body: 2 piece 316 Stainless Steel ANSI 150 RF Seats: Filled PTFE Optional: Limit Switch. De-Clutch Gear Box Actuator- std. aluminium Optional Stainless Steel
	BLSF55FA - SR - RT	20							
	BLSF56FA - SR - RT	25							
	BLSF57FA - SR - RT	32							
	BLSF58FA - SR - RT	40							
	BLSF59FA - SR - RT	50							
	BLSF510FA - SR - RT	63							
	BLSF511FA - SR - RT	80							
	BLSF512FA - SR - RT	100							
	BLSF513FA - SR - RT	125							
	BLSF514FA - SR - RT	150							
	BLSF515FA - SR - RT	200							
	BLSF516FA - SR - RT	250							
	BLSF517FA - SR - RT	300							
For normally open function change 5th digit to 6 – Optional ANSI 300BLSF3 Code contact factory									

AIR / FLUID / STEAM / PETROCHEMICAL			Electric On/Off • SS316		ANSI 150 • ANSI 300		BLSFE		
 Series BLSF Electric Actuated 316 Stainless Steel Body	BLSF4FA - E* - RT	15	ANSI 150 RF	OM-1	20 BAR W.O.G.	-20°C	E1=240VAC E2=110VAC E5=24VAC E7=12VDC E8=24VDC E11=415VAC	Body: 2 piece 316 Stainless Steel ANSI 150 RF Seats: Filled PTFE	Direct Mount. High Pad Self Adjusting Stem Packing API 607 6th Edition API 598 Test see Series 'OM' for Actuator details P27 Also available as Spring Close with Exd IECE P27
	BLSF5FA - E* - RT	20		OM-1					
	BLSF6FA - E* - RT	25		OM-1					
	BLSF7FA - E* - RT	32		OM-1					
	BLSF8FA - E* - RT	40		OM-1					
	BLSF9FA - E* - RT	50		OM-A					
	BLSF10FA - E* - RT	63		OM-2					
	BLSF11FA - E* - RT	80		OM-3					
	BLSF12FA - E* - RT	100		OM-4					
	BLSF13FA - E* - RT	125		OM-4					
	BLSF14FA - E* - RT	150		OM-5					
	BLSF15FA - E* - RT	200		OM-6					
	BLSF16FA - E* - RT	250		OM-8					
	BLSF17FA - E* - RT	300		OM-10					
Optional ANSI 300BLSF3 Code contact factory									

Fire Safe ANSI 300BLSF3 Available. Also 600, 900.

• * For grease and high viscosity applications upsize actuator is recommended. Consult factory for sizing.

– For further technical information contact Process Systems or your distributor.

– (std. = Standard Product).

* VOLTAGE CODE: 1 = 240VAC, 2 = 110VAC, 5 = 24VAC, 7 = 12VDC, 8 = 24VDC, 11 = 415VAC

• ELASTOMER CODE: V = Viton (FKM), S = Silicone, T = PTFE, E = EPDM, N = NBR Nitrile, NC = Normally closed, NO = Normally open

WCB Fire Safe

ANSI-150 Optional ANSI-300	Orifice Ømm	ANSI 150 RF	Actuator	Media Pressure	Media Temperature	Actuator Air Pressure /Voltage	Material of Construction	Features	
PETROCHEMICAL Lever. Lockable • Carbon Steel ANSI 150 BLCF									
BLCF4FA - L - RT BLCF5FA - L - RT BLCF6FA - L - RT BLCF7FA - L - RT BLCF8FA - L - RT BLCF9FA - L - RT BLCF10FA - L - RT BLCF11FA - L - RT BLCF12FA - L - RT BLCF13FA - L - RT BLCF14FA - L - RT BLCF15FA - L - RT BLCF16FA - L - RT BLCF17FA - L - RT	15 20 25 32 40 50 65 80 100 125 150 200 250 300	ANSI 150 RF	LEVER	20 BAR W.O.G.	-20°C	9mm	Body: 2 piece Carbon Steel ANSI 150 RF Seats: Filled PTFE	Direct Mount. High Pad Self Adjusting Stem Packing API 607 6th Edition API 598 Test Lockable Lever	
						11mm			
						14mm			
						17mm			
						22mm			
						27mm			
Optional ANSI 300 Code contact factory • Spring Close Lever Optional on Smaller Sizes • Spring Handle 1" ~ 2"						□ Shaft			

AIR / FLUID / STEAM / PETROCHEMICAL			Gear Box • Carbon Steel		ANSI 150		BLCF		
 Series BLCF ANSI-150 Flange Gear Box Carbon Steel Body	BLCF4FA - G - RT	15	ANSI 150 RF	GB1	20 BAR W.O.G.	-20°C	Gearbox	Body: 2 piece Carbon Steel ANSI 150 RF Seats: Filled PTFE API 607 6th Edition API 598 Test	
	BLCF5FA - G - RT	20		GB1					
	BLCF6FA - G - RT	25		GB1					
	BLCF7FA - G - RT	32		GB1					
	BLCF8FA - G - RT	40		GB1					
	BLCF9FA - G - RT	50		GB1					
	BLCF10FA - G - RT	65		GB2					
	BLCF11FA - G - RT	80		GB2	Vacuum				
	BLCF12FA - G - RT	100		GB2					
	BLCF13FA - G - RT	125		GB3					
	BLCF14FA - G - RT	150		GB3					
	BLCF15FA - G - RT	200		GB4					
	BLCF16FA - G - RT	250		GB5	10 BAR Steam	180°C			
	BLCF17FA - G - RT	300		GB6					
Optional ANSI 300 Code contact factory • See Page 29 for Gear Box Specifications									

AIR / FLUID / STEAM / PETROCHEMICAL Double Acting Pneumatic • Carbon Steel ANSI 150 BLCFDA									
 Series BLCF Double Acting Carbon Steel Body	BLCF4FA - DA - RT	15	ANSI 150 RF	DA50	*	20 BAR W.O.G.	-20°C	6-8 BAR	Body: 2 piece Carbon Steel ANSI 150 RF Seats: Filled PTFE Optional: Limit Switch. De-Clutch Gear Box API 607 6th Edition API 598 Test Actuator- std. aluminium Optional Stainless Steel
	BLCF5FA - DA - RT	20		DA50					
	BLCF6FA - DA - RT	25		DA50					
	BLCF7FA - DA - RT	32		DA63					
	BLCF8FA - DA - RT	40		DA63					
	BLCF9FA - DA - RT	50		DA75					
	BLCF10FA - DA - RT	63		DA88					
	BLCF11FA - DA - RT	80		DA100					
	BLCF12FA - DA - RT	100		DA115					
	BLCF13FA - DA - RT	125		DA125					
	BLCF14FA - DA - RT	150		DA145					
	BLCF15FA - DA - RT	200		DA160					
	BLCF16FA - DA - RT	250		DA200		10 BAR Steam	180°C	6-8 BAR Air Pressure	
	BLCF17FA - DA - RT	300		DA240					
Optional ANSI 300 Code contact factory									

AIR / FLUID / STEAM / PETROCHEMICAL										Spring Return Pneumatic • Carbon Steel				ANSI 150		BLCFSR	
	Series BLCF	BLCF54FA - SR - RT	15	ANSI 150 RF	SR50	*	20 BAR W.O.G.	-20°C	6-8 BAR	Body: 2 piece Carbon Steel ANSI 150 RF Seats: Filled PTFE Optional: Limit Switch. De-Clutch Gear Box	Direct Mount. High Pad Self Adjusting Stem Packing API 607 6th Edition API 598 Test Actuator- std. aluminium Optional Stainless Steel						
		BLCF55FA - SR - RT	20		SR63												
		BLCF56FA - SR - RT	25		SR63												
		BLCF57FA - SR - RT	32		SR75												
		BLCF58FA - SR - RT	40		SR75												
		BLCF59FA - SR - RT	50		SR88												
		BLCF510FA - SR - RT	63		SR100												
		BLCF511FA - SR - RT	80		SR115												
		BLCF512FA - SR - RT	100		SR145												
		BLCF513FA - SR - RT	125		SR160												
Spring Return Carbon Steel Body		BLCF514FA - SR - RT	150	SR180													
		BLCF515FA - SR - RT	200	SR200													
		BLCF516FA - SR - RT	250	SR240	10 BAR Steam	180°C	6-8 BAR Air Pressure										
		BLCF517FA - SR - RT	300	SR270													
For normally open function change 5th digit to 6 – Optional ANSI 300 Code contact factory																	

AIR / FLUID / STEAM / PETROCHEMICAL										Electric On/Off • Carbon Steel			ANSI 150		BLCFE		
	Series BLCF	BLCF4FA - E* - RT	15	ANSI 150 RF	OM-1	*	20 BAR W.O.G.	-20°C	E1=240VAC	Body: 2 piece Carbon Steel ANSI 150 RF Seats: Filled PTFE	Direct Mount. High Pad Self Adjusting Stem Packing API 607 6th Edition API 598 Test see Series 'OM' for Actuator details P27 Also available as Spring Close P27						
		BLCF5FA - E* - RT	20		OM-1												
		BLCF6FA - E* - RT	25		OM-1												
		BLCF7FA - E* - RT	32		OM-1												
		BLCF8FA - E* - RT	40		OM-1												
		BLCF9FA - E* - RT	50		OM-A												
		BLCF10FA - E* - RT	63		OM-2												
		BLCF11FA - E* - RT	80		OM-3												
		BLCF12FA - E* - RT	100		OM-4												
		BLCF13FA - E* - RT	125		OM-4												
Electric Actuated Carbon Steel Body	BLCF14FA - E* - RT	150	OM-5	10 BAR STEAM	180°C	IP67	E2=110VAC E5=24VAC E7=12VDC E8=24VDC E11=415VAC										
	BLCF15FA - E* - RT	200	OM-6														
	BLCF16FA - E* - RT	250	OM-8														
	BLCF17FA - E* - RT	300	OM-10														
	Optional ANSI 300 Code contact factory																

Fire Safe ANSI 300BLSF3 Available. Also 600, 900.

• * For grease and high viscosity applications upsize actuator is recommended. Consult factory for sizing.

– For further technical information contact Process Systems or your distributor.

– (std. = Standard Product).

* VOLTAGE CODE: 1 = 240VAC, 2 = 110VAC, 5 = 24VAC, 7 = 12VDC, 8 = 24VDC, 11 = 415AC

• ELASTOMER CODE: V = Viton (FKM), S = Silicone, T = PTFE, E = EPDM, N = NBR Nitrile, NC = Normally closed, NO = Normally open

Metal Seat

HIGH TEMPERATURE / HIGH PRESSURE

Lever • Lockable • SS316 • 2000 PSI • Uni-Directional

BLM



Series BLM


Model	Orifice Ømm	Connection	Actuator	Media Pressure	Media Temperature	Material of Construction	Features
BLM4B - L - M BLM5B - L - M BLM6B - L - M BLM7B - L - M BLM8B - L - M BLM9B - L - M	15 20 25 32 40 50	1/2 3/4 1 1-1/4 1-1/2 2	Lever Actuation Optional Lever	125 BAR	13.62Mpa @ -29 to 35 °C Max. Temp. 454°C (See Data Sheet)	Body: 3 pce 316 Stainless Steel BSP Threaded. Seats: Metal Uni-Directional Flow	Direct Mount. Metal Seat. Design: ANSI B16.34 Test: ANSI / FCI 70-2 Class V

For Actuators consider Extension Brackets for heat transfer (See Factory)

HIGH TEMPERATURE / HIGH PRESSURE

Lever • Lockable • SS316 • ANSI 300 • Uni-Directional

BLMFA



Series BLMFA

Model	Orifice Ømm	Connection	Actuator	Media Pressure	Media Temperature	Material of Construction	Features
BLM4FA - L - M BLM5FA - L - M BLM6FA - L - M BLM7FA - L - M BLM8FA - L - M BLM9FA - L - M BLM10FA - L - M BLM11FA - L - M BLM12FA - L - M	15 20 25 32 40 50 65 80 100	ANSI 300 RF	Lever Actuation Optional Lever	40 BAR	4Mpa @ -29 to 35 °C Max. Temp. 454°C (See Data Sheet)	Body: 2 piece Stainless Steel ANSI 300 RF Seats: Metal Uni-Directional Flow	Direct Mount. Metal Seat. Design: ANSI B16.10 Flange: ANSI 300 Test: API 598 ANSI / FCI 70-2 Class V

For Actuators consider Extension Brackets for heat transfer (See Factory)

Fire Safe

HIGH PRESSURE / HIGH TEMPERATURE / FIRE SAFE • LEVER • LOCKABLE • 2000 PSI

BLF (BSP)



Series BLF

Model	Orifice Ømm	Connection	Actuator	Media Pressure	Media Temperature	Material of Construction	Features
BLF4B - L - T BLF5B - L - T BLF6B - L - T BLF7B - L - T BLF8B - L - T BLF9B - L - T BLF10B - L - T BLF11B - L - T BLF12B - L - T	15 20 25 32 40 50 65 80 100	BSP	Lever Actuation Optional Lever	Vacuum 125 BAR	-20°C 180°C	Body: 3 piece 316 Stainless Steel. Investment Cast. Seat: PTFE	Direct Mount. Optional Actuator ISO 5211 Length DIN 3202-M3 Fire Safe API607 Approval # 249036

HIGH PRESSURE / HIGH TEMPERATURE / FIRE SAFE • LEVER • LOCKABLE • 2000 PSI

BLF (NPT)



Series BLFN

Model	Orifice Ømm	Connection	Actuator	Media Pressure	Media Temperature	Material of Construction	Features
BLF4N - L - T BLF5N - L - T BLF6N - L - T BLF7N - L - T BLF8N - L - T BLF9N - L - T BLF10N - L - T BLF11N - L - T BLF12N - L - T	15 20 25 32 40 50 65 80 100	NPT	Lever Actuation Optional Lever	Vacuum 125 BAR	-20°C 180°C	Body: 3 piece 316 Stainless Steel. Investment Cast. Seat: PTFE	Direct Mount. Optional Actuator ISO 5211 Length DIN 3202-M3 Fire Safe API607 Approval # 249036

HIGH PRESSURE / HIGH TEMPERATURE / FIRE SAFE • LEVER • LOCKABLE • 2000 PSI

BLFS (Socket)



Series BLFS

Model	Orifice Ømm	Connection	Actuator	Media Pressure	Media Temperature	Material of Construction	Features
BLF4S - L - T BLF5S - L - T BLF6S - L - T BLF7S - L - T BLF8S - L - T BLF9S - L - T BLF10S - L - T BLF11S - L - T BLF12S - L - T	15 20 25 32 40 50 65 80 100	SOCKET	Lever Actuation Optional Lever	Vacuum 125 BAR	-20°C 180°C	Body: 3 piece 316 Stainless Steel. Investment Cast. Seat: PTFE	Direct Mount. Optional Actuator ISO 5211 Length DIN 3202-M3 Fire Safe API607 Approval # 249036

High Pressure

AIR / WATER



Model	Orifice Ømm	Port Size BSP	Actuator	Media Pressure @30°C	Media Temperature	Actuator Air Pressure /Voltage	Material of Construction	Features			
Lever. Lockable								BLSHP			
BLSHP2B - L - D	8	1/4	LEVER	3,000 PSI 200 BAR	40°C @ 200 BAR	Lever Lockable	Body: 316 Stainless Steel Ball: Stainless Steel Seat: Delrin Optional: PEEK for grease and solvents	Highflow			
BLSHP3B - L - D	10	3/8						High pressure			
BLSHP4B - L - D	15	1/2						Lockable Lever			
BLSHP5B - L - D	20	3/4									
BLSHP6B - L - D	25	1									
BLSHP8B - L - D	40	1-1/2	LEVER								
BLSHP9B - L - D	50	2									
ALSO AVAILABLE - 3 WAY FULL BORE L/T • MANUAL OR ACTUATED • Optional Fire Safe Approval											

AIR / WATER



Double Acting Pneumatic								BLSDA
BLSHP2B - DA - D	8	1/4	DA50	3,000 PSI 200 BAR	40°C @ 200 BAR	6-8 BAR	Body: 316 Stainless Steel Ball: Stainless Steel Seat: Delrin Optional: PEEK for grease and solvents	Highflow High pressure Actuator std. aluminium
BLSHP3B - DA - D	10	3/8	DA50					
BLSHP4B - DA - D	12	1/2	DA50					
BLSHP5B - DA - D	17	3/4	DA63					
BLSHP6B - DA - D	22	1	DA63					
BLSHP8B - DA - D	35	1-1/2	DA88	6-8 BAR				
BLSHP9B - DA - D	35	2	DA88					
ALSO AVAILABLE - 1/2" UP TO 1" NPT 10,000 PSI 2-WAY 3-WAY • Optional Fire Safe Approval								

AIR / WATER



Spring Return Pneumatic							BLSHSR	
BLSHP52B - SR - D	8	1/4	SR63	3,000 PSI 200 BAR	40°C @ 200 BAR	6-8 BAR	Body: 316 Stainless Steel Ball: Stainless Steel Seat: Delrin Optional: PEEK for grease and solvents	Highflow High pressure Actuator std. aluminium
BLSHP53B - SR - D	10	3/8	SR63					
BLSHP54B - SR - D	12	1/2	SR75					
BLSHP55B - SR - D	17	3/4	SR75					
BLSHP56B - SR - D	22	1	SR88					
BLSHP58B - SR - D	35	1-1/2	SR100	200 BAR		6-8 BAR		
BLSHP59B - SR - D	35	2	SR100					
ALSO AVAILABLE - 1/2" UP TO 1" NPT 10,000 PSI 2-WAY 3-WAY • Optional Fire Safe Approval								

AIR / WATER



Electric On/Off								BLSHE
BLSHP2B - E* - D	8	1/4	OM-1	3,000 PSI 200 BAR	40°C @ 200 BAR	E1=240VAC E2=110VAC E5=24VAC E7=12VDC E8=24VDC	Body: 316 Stainless Steel Ball: Stainless Steel Seat: Delrin Optional: PEEK for grease and solvents	Highflow High pressure see Series 'OM' for Actuator details Page 27
BLSHP3B - E* - D	10	3/8	OM-1					
BLSHP4B - E* - D	12	1/2	OM-1					
BLSHP5B - E* - D	17	3/4	OM-1					
BLSHP6B - E* - D	22	1	OM-1					
BLSHP8B - E* - D	35	1-1/2	OM-A					
BLSHP9B - E* - D	35	2	OM-A					
ALSO AVAILABLE - 1/2" UP TO 1" NPT 10,000 PSI 2-WAY 3-WAY • Optional Fire Safe Approval								

SS316 3pc V Port

AIR / FLUID / STEAM / PETROCHEMICAL




Model	Port Size BSP	Actuator		Modulating Controller 4-20mA 1-10VDC	Media Pressure	Media Temperature	Actuator Air Pressure /Voltage	Material of Construction	Features	
		Lever	Gear Box							
ETROCHEMICAL • Lever. Lockable. 3 Piece • V Port 60°										BLV
BLV5B - L - T60 BLV6B - L - T60 BLV8B - L - T60 BLV9B - L - T60 BLV11B - L - T60 BLV12B - L - T60	3/4 1 1-1/2 2 3 4	L L L L L L	 GB1 GB1 GB2 GB2		63 BAR W.O.G. Vacuum 10 BAR Steam using R.T Seat	-20°C 180°C	See below for options	Body: 3 piece 316 Stainless Steel. BSP Threaded. Filled Seats: filled PTFE Optional: Socket weld NPT	Direct Mount. High Pad Self Adjusting Stem Packing Lockable Lever Optional: Gearbox/Actuator	
Change 'L' to 'G' for Gear box • Optional 50/50 SS Seats HT 3/4" ~ 4"						200°C				

FLUID / STEAM / PETROCHEMICAL



CHEMICAL • Lever. Lockable. 3 Piece • V Port 60° (30° Optional)										BLVF
BLV4FA - L - T60	15	ANSI 150 RF	L		63 BAR	-20°C	See below for options	Body: 2 piece 316 Stainless Steel. Seats: filled PTFE Flanged ANSI 150 RF	Direct Mount. High Pad Self Adjusting Stem Packing Lockable Lever /Gearbox/Actuator	
BLV5FA - L - T60	20		L		W.O.G.					
BLV6FA - L - T60	25		L		Vacuum					
BLV7FA - L - T60	32		L							
BLV8FA - L - T60	40		L			180°C				
BLV9FA - L - T60	50		L	GB1	10 BAR					
BLV10FA - L - T60	65		L	GB1	Steam using					
BLV11FA - L - T60	80			GB2	R.T. Seat					
BLV12FA - L - T60	100			GB2						
Change 'L' to 'G' for Gear box • Optional 50/50 SS Seats HT 3/4" ~ 4"										200°C

• Optional modulating V Port Control (Elements to fit above valves) • See website or contact sales for actuated codes.



**BAS
Auto Return IP67**

Series BAS



SS316 2 Way
Electric - Auto Return

Model	Orifice Ømm	Port Size BSP	Actuator	Media Pressure @30°C	Media Temperature	Open/Close Time	Material of Construction	Features
2 Way Auto Return Ball Valve • 12~24v AC/DC								
BASM54B - EL - T BASM55B - EL - T BASM56B - EL - T	15 20 20	1/2 3/4 1	N.C. N.C.	10 BAR	2°C	5 Sec	Ball: SS316 Body: SS304 Seals: FKM Seats: PTFE Actuator: PPO	Works like a Solenoid Valve - take the power off and it returns Very low power consumption 5 Sec operation
BASM64B - EL - T BASM65B - EL - T BASM66B - EL - T	15 20 20	1/2 3/4 1	N.O. N.O.	10 BAR	90°C	5 Sec	Ball: CPVC Body: CPVC Seals: FKM Seats: PTFE	Min 30 Sec power on to charge capacitor. 30% Duty Cycle
BAPM54B - EL - T	15	1/2	N.C.	10 BAR	90°C	5 Sec	Ball: CPVC Body: CPVC Seals: FKM Seats: PTFE	
C/W Manual Override								

BASM

BASM3

Series BAS



SS316 3 Way
Electric - Auto Return

BASM3L4B - EL - T BASM3L5B - EL - T	12 15	1/2 3/4	3 Way L Port	10 BAR 10 BAR	90°C 90°C	5 Sec 5 Sec	Ball: SS316 Body: SS304 Seals: FKM Seats: PTFE Actuator: PPO	Works like a Solenoid Valve - take the power off and it returns Very low power consumption
C/W Manual Override								

PVC

AIR / FLUID / AQUACULTURE Manual Handle • PVC

BFP

Series BFP



Lever
PVC Body

BFP50 - L - E BFP65 - L - E BFP80 - L - E BFP100 - L - E BFP125 - L - E BFP150 - L - E BFP200 - L - E	50 65 80 100 125 150 200	Slotted Flange	Manual Lever	0 10 BAR	0°C 60°C		UPVC Body EPDM Seat Optional Viton (FKM)	UPVC Body Universal Flange Semi Lugged Manual Lever. Optional Gearbox.
Optional to 600mm Diameter								

AIR / FLUID / AQUACULTURE Double Acting Pneumatic • PVC

BLPDA

Series BFP



Double Acting
PVC Body

BFP50 - DA - E BFP65 - DA - E BFP80 - DA - E BFP100 - DA - E BFP125 - DA - E BFP150 - DA - E BFP200 - DA - E	50 65 80 100 125 150 200	Slotted Flange	DA50 DA50 DA63 DA63 DA75 DA88 DA100	0 10 BAR	0°C 60°C	6-8 BAR 6-8 BAR Air Pressure	UPVC Body EPDM Seat Optional Viton (FKM)	UPVC Body Universal Flange Semi Lugged Double Acting Pneumatic Actuator
--	--	----------------	---	-------------	-------------	------------------------------------	--	---

AIR / FLUID / AQUACULTURE Spring Return Pneumatic • PVC

BFPSR

Series BFP



Single Acting
PVC Body

BFP550 - SR - E BFP565 - SR - E BFP580 - SR - E BFP5100 - SR - E BFP5125 - SR - E BFP5150 - SR - E BFP5200 - SR - E	50 65 80 100 125 150 200	Slotted Flange	SR63 SR63 SR75 SR75 SR88 SR100 SR115	0 10 BAR	0°C 60°C	6-8 BAR 6-8 BAR Air Pressure	UPVC Body EPDM Seat Optional Viton (FKM)	UPVC Body Universal Flange Semi Lugged Spring Return Pneumatic Actuator
For normally open function change 4th digit to 6								

AIR / FLUID / AQUACULTURE Electric On/Off • PVC

BFPE

Series BFP



Electric
Actuated
PVC Body

BFP50 - E* - E BFP65 - E* - E BFP80 - E* - E BFP100 - E* - E BFP125 - E* - E BFP150 - E* - E BFP200 - E* - E	50 65 80 100 125 150 200	Slotted Flange	OM-1 OM-1 OM-1 OM-A OM-A OM-2 OM-2	0 10 BAR	0°C 60°C	E1=240VAC E2=110VAC E5=24VAC E7=12VDC E8=24VDC E11=415V IP67	UPVC Body EPDM Seat Optional Viton (FKM)	UPVC Body Universal Flange Semi Lugged Electric On/Off Actuator
--	--	----------------	--	-------------	-------------	--	--	---

BLP 2 Way PVC Ball Valves
BLP3 3 Way PVC Ball Valves
BCP PVC Ball Check Valves
YSP PVC Y Strainer

See Page 11
See Page 12
See Page 35
See Page 37

Series BFD Wafer

AIR / WATER / VACUUM



Model	Nominal Bore Ømm	Actuator	Media Pressure	Media Temperature	Actuator Voltage/Air Pressure	Material of Construction	Features	
Lever and Gear Operated • Ductile Iron • Wafer Connection							BFD	
BFD50 - L - E	50	LEVER	16 BAR	-20°C	UNIVERSAL WAFER SUITABLE MOST FLANGE TABLES	- Ductile Iron - 316 S/S disc - EPDM liner (E) Optional: Viton (V) NBR (N)	Direct Pad Mount. Operator: • Lever • Gear Box IP67 WTM SMK26314 WMK26314 WSSA	
BFD65 - L - E	65							GB1
BFD80 - L - E	80							GB1
BFD100 - L - E	100							GB1
BFD125 - L - E	125							GB1
BFD150 - L - E	150							GB2
BFD200 - L - E	200							GB2
BFD250 - L - E	250							GB2
BFD300 - L - E	300							GB2
BFD350 - G - E	350							GB3
BFD400 - G - E	400	GEARBOX	10 BAR	40°C				
BFD450 - G - E	450						GB4	
BFD500 - G - E	500						GB4	
BFD600 - G - E	600						GB5	
Substitute 'G' for Gear Box option				For Non Potable - EPDM 100°C				

AIR / WATER / VACUUM



Double Acting Pneumatic • Ductile Iron • Wafer Connection							BFDDA
BFD50 - DA - E	50	DA50		-20°C	6-8 BAR	- Ductile Iron - 316 S/S disc - EPDM liner (E) - Optional Viton (V) NBR (N) Replacable liner	Double acting Pneumatic actuator. Direct pad mount. Optional: S/S Actuator
BFD65 - DA - E	65	DA50					 SMK26314 WMK26314 WSSA
BFD80 - DA - E	80	DA63					
BFD100 - DA - E	100	DA75					
BFD125 - DA - E	125	DA88					
BFD150 - DA - E	150	DA100					
BFD200 - DA - E	200	DA115					
BFD250 - DA - E	250	DA125					
BFD300 - DA - E	300	DA145					
BFD350 - DA - E	350	DA180					
BFD400 - DA - E	400	DA200		40°C	6-8 BAR		
BFD450 - DA - E	450	DA200					
BFD500 - DA - E	500	DA240					
BFD600 - DA - E	600	DA270					
				For Non Potable - EPDM 100°C			


AIR / WATER / VACUUM



Spring Return Pneumatic • Ductile Iron • Wafer Connection							BFDSR
BFD550 - SR - E	50	SR63	 16 BAR	-20°C	6-8 BAR	- Ductile Iron - 316 S/S disc - EPDM liner (E) - Optional Viton (V) NBR (N) Replacable liner	Spring Return Pneumatic actuator. Direct pad mount.  SMK26314 WMK26314 WSSA
BFD565 - SR - E	65	SR63					
BFD580 - SR - E	80	SR75					
BFD5100 - SR - E	100	SR88					
BFD5125 - SR - E	125	SR100					
BFD5150 - SR - E	150	SR115					
BFD5200 - SR - E	200	SR125					
BFD5250 - SR - E	250	SR145					
BFD5300 - SR - E	300	SR180					
BFD5350 - SR - E	350	SR200					
BFD5400 - SR - E	400	SR240	 10 BAR	40°C	6-8 BAR		
BFD5450 - SR - E	450	SR270					
BFD5500 - SR - E	500	SR270					
BFD5600 - SR - E	600	SR380					
* For normally open function change 4th digit to 6				For Non Potable - EPDM 100°C			

AIR / WATER / VACUUM



Electric On/Off • Ductile Iron • Wafer Connection							BFDE
BFD50 - E* - E	50	OM-1			E1=240VAC E2=110VAC E5=24VAC E7=12VDC E8=24VDC E11=415VAC IP67	- Ductile Iron - 316 S/S disc - EPDM liner (E) - Optional Viton (V) NBR (N) Replacable liner	on/off electric actuator.
BFD65 - E* - E	65	OM-1					
BFD80 - E* - E	80	OM-1					
BFD100 - E* - E	100	OM-A					
BFD125 - E* - E	125	OM-A					
BFD150 - E* - E	150	OM-2					
BFD200 - E* - E	200	OM-3					
BFD250 - E* - E	250	OM-4					
BFD300 - E* - E	300	OM-5					
BFD350 - E* - E	350	OM-6					
BFD400 - E* - E	400	OM-7					 SMK26314 WMK26314 WSSA
BFD450 - E* - E	450	OM-8					
BFD500 - E* - E	500	OM-9					
BFD600 - E* - E	600	OM-11					
				*			
Power Open / Power Closed. Available in Spring Return Electric Actuation.					For Non Potable - EPDM 100°C		

* Please Note: For dry powder applications, upsized actuator is recommended. Contact factory for sizing.

Series BFDD Double Flange

AIR / WATER / VACUUM



Model	Nominal Bore Ømm	Actuator	Media Pressure	Media Temperature	Flange Options	Material of Construction	Features
Double Flange							
BFDD50 - L - E	50	LEVER	16 BAR	-20°C For Non Potable - EPDM 100°C	Standard: AS 4087 PN16	• Ductile Iron • 316 S/S disc • EPDM liner (E)	Direct Pad Mount. Operator: • Lever • Gear Box IP67 Double Flange. Flange to AS4087 PN16 Std. AS2129 Table E Optional W TM SMK40876 WMK40876 WSSA
BFDD65 - L - E	65						
BFDD80 - L - E	80						
BFDD100 - L - E	100						
BFDD125 - L - E	125						
BFDD150 - L - E	150						
BFDD200 - L - E	200						
BFDD250 - L - E	250						
BFDD300 - L - E	300						
BFDD350 - G - E	350						
BFDD400 - G - E	400	GEARBOX	10 BAR	40°C			Not Watermark Approved
BFDD450 - G - E	450						
BFDD500 - G - E	500						
BFDD600 - G - E	600						
BFDD700 - G - E							
BFDD800 - G - E							
BFDD900 - G - E							
BFDD1000 - G - E							
BFDD1200 - G - E							
BFDD700 - G - E		GEARBOX		-20°C			Not Watermark Approved
BFDD800 - G - E							
BFDD900 - G - E							
BFDD1000 - G - E							
BFDD1200 - G - E				90°C			

BFDD

AIR / WATER / VACUUM



Double Flange · Double Acting							
BFDD50 - DA - E	50	DA50	16 BAR	-20°C For Non Potable - EPDM 100°C	Standard: AS 4087 PN16	• Ductile Iron • 316 S/S disc • EPDM liner (E)	Direct Pad Mount. Double Flange. Flange to AS4087 PN16 Std. AS2129 Table E Optional W TM SMK40876 WMK40876 WSSA
BFDD65 - DA - E	65	DA50					
BFDD80 - DA - E	80	DA63					
BFDD100 - DA - E	100	DA75					
BFDD125 - DA - E	125	DA88					
BFDD150 - DA - E	150	DA100					
BFDD200 - DA - E	200	DA115					
BFDD250 - DA - E	250	DA125					
BFDD300 - DA - E	300	DA145					
BFDD350 - DA - E	350	DA180					
BFDD400 - DA - E	400	DA200	10 BAR	40°C			
BFDD450 - DA - E	450	DA200					
BFDD500 - DA - E	500	DA240					
BFDD600 - DA - E	600	DA270					
		*					

BFDDDA

AIR / WATER / VACUUM



Double Flange · Spring Return							
BFDD550 - SR - E	50	SR63	16 BAR	-20°C For Non Potable - EPDM 100°C	Standard: AS 4087 PN16	• Ductile Iron • 316 S/S disc • EPDM liner (E)	Spring Return Pneumatic actuator. Direct pad mount. Double Flange. Flange to AS4087 PN16 Std. AS2129 Table E Optional W TM SMK40876 WMK40876 WSSA
BFDD565 - SR - E	65	SR63					
BFDD580 - SR - E	80	SR75					
BFDD5100 - SR - E	100	SR88					
BFDD5125 - SR - E	125	SR100					
BFDD5150 - SR - E	150	SR115					
BFDD5200 - SR - E	200	SR125					
BFDD5250 - SR - E	250	SR145					
BFDD5300 - SR - E	300	SR180					
BFDD5350 - SR - E	350	SR200					
BFDD5400 - SR - E	400	SR240	10 BAR	40°C			
BFDD5450 - SR - E	450	SR270					
BFDD5500 - SR - E	500	SR270					
BFDD5600 - SR - E	600	SR570					
		*					

BFDDSR

AIR / WATER / VACUUM



Double Flange · Electric							
BFDD50 - E* - E	50	OM-1	16 BAR	-20°C For Non Potable - EPDM 100°C	Standard: AS 4087 PN16	• Ductile Iron • 316 S/S disc • EPDM liner (E)	on/off electric actuator. Double Flange. Flange to AS4087 PN16 Std. AS2129 Table E Optional W TM SMK40876 WMK40876 WSSA
BFDD65 - E* - E	65	OM-1					
BFDD80 - E* - E	80	OM-1					
BFDD100 - E* - E	100	OM-A					
BFDD125 - E* - E	125	OM-A					
BFDD150 - E* - E	150	OM-2					
BFDD200 - E* - E	200	OM-3					
BFDD250 - E* - E	250	OM-4					
BFDD300 - E* - E	300	OM-5					
BFDD350 - E* - E	350	OM-6					
BFDD400 - E* - E	400	OM-7	10 BAR	40°C			
BFDD450 - E* - E	450	OM-8					
BFDD500 - E* - E	500	OM-9					
BFDD600 - E* - E	600	OM-11					
		*					

BFDE

* Please Note: For dry powder applications, upsized actuator is recommended. Contact factory for sizing.

Series BFL Lugged

AIR / WATER / VACUUM



Model	Nominal Bore Ømm	Actuator	Media Pressure	Media Temperature	Actuator Voltage/Air Pressure	Material of Construction	Features	
Lever and Gear Operated • Ductile Iron							BFL	
BFL50 - L - E	50	LEVER	16 BAR	-20°C	6-8 BAR	- Ductile Iron - 316 S/S disc - EPDM liner (E) - Optional Viton (V) NBR (N)	Direct Pad Mount. Operator: • Lever • Gear Box IP67 AS2129 Table E or Table D  SMK26314 WMK26314 WSSA	
BFL65 - L - E	65							GB1
BFL80 - L - E	80							GB1
BFL100 - L - E	100							GB1
BFL125 - L - E	125							GB1
BFL150 - L - E	150							GB2
BFL200 - L - E	200							GB2
BFL250 - L - E	250							GB2
BFL300 - L - E	300							GB2
BFL350 - G - E	350							GB3
BFL400 - G - E	400	GEARBOX	10 BAR	40°C	6-8 BAR			
BFL450 - G - E	450						GB4	
BFL500 - G - E	500						GB4	
BFL600 - G - E	600						GB5	
Substitute 'G' for Gear Box option				For Non Potable - EPDM 100°C		ANSI 150 BFLA		

AIR / WATER / VACUUM



Double Acting Pneumatic • Ductile Iron							BFLDA
BFL50 - DA - E	50	DA50	* 16 BAR 10 BAR	-20°C	6-8 BAR	- Ductile Iron - 316 S/S disc - EPDM liner (E) - Optional Viton (V) NBR (N) Replacable liner	Double acting Pneumatic actuator. Direct pad mount. AS2129 Table E or Table D  SMK26314 WMK26314 WSSA
BFL65 - DA - E	65	DA50					
BFL80 - DA - E	80	DA63					
BFL100 - DA - E	100	DA75					
BFL125 - DA - E	125	DA88					
BFL150 - DA - E	150	DA100					
BFL200 - DA - E	200	DA115					
BFL250 - DA - E	250	DA125					
BFL300 - DA - E	300	DA145					
BFL350 - DA - E	350	DA180					
BFL400 - DA - E	400	DA200					
BFL450 - DA - E	450	DA200					
BFL500 - DA - E	500	DA240					
BFL600 - DA - E	600	DA270					
					For Non Potable - EPDM 100°C		ANSI 150 BFLA

AIR / WATER / VACUUM



Spring Return Pneumatic • Ductile Iron							BFLSR
BFL550 - SR - E	50	SR63	* 16 BAR <				

AIR / WATER / VACUUM



Electric On/Off • Ductile Iron							BFLE
BFL50 - E* - E	50	OM-1	* 16 BAR 10 BAR	-20°C <			

* Please Note: For dry powder applications, upsized actuator is recommended. Contact factory for sizing.

Series BFS Wafer

AIR / WATER



Model	Nominal Bore Ømm	Actuator	Media Pressure	Media Temperature	Actuator Voltage/Air Pressure	Material of Construction	Features
Lever and Gear Operated • 316SS Body - PTFE Seat							BFS
BFS50 - L - T	50	LEVER GEARBOX	10 BAR	-20°C		LEVER	
BFS65 - L - T	65					304 SS	
BFS80 - L - T	80					BODY MATERIAL	
BFS100 - L - T	100					316 SS	
BFS125 - L - T	125					DISC MATERIAL	
BFS150 - L - T	150					316 SS	
BFS200 - L - T	200					SEAT MATERIAL	
BFS250 - L - T	250					PTFE Coated NBR	
BFS300 - L - T	300					WAFER STYLE	
BFS350 - ISO - T	350					Suit Flanges	
BFS400 - ISO - T	400					Table E, D ANSI 150 & BS4504 PN10	
BFS450 - ISO - T	450					AS4087 PN16, AS2129 Table E	
BFS500 - ISO - T	500						
BFS600 - ISO - T	600						
Substitute 'G' for Gear Box option • Optional Lugged Valves Available							

BFS

AIR / WATER



Double Acting Pneumatic • 316SS Body - PTFE Seat							BFSDA	
BFS50 - DA - T	50	DA63	*	10 BAR	-20°C	6-8 BAR	Body: 316 SS	Double acting Pneumatic actuator. Direct pad mount. Optional: S/S Actuators
BFS65 - DA - T	65	DA75					Seat: PTFE Coated NBR	
BFS80 - DA - T	80	DA75					Disc: 316 SS	
BFS100 - DA - T	100	DA88						
BFS125 - DA - T	125	DA100						
BFS150 - DA - T	150	DA115						
BFS200 - DA - T	200	DA125						
BFS250 - DA - T	250	DA160						
BFS300 - DA - T	300	DA180			10 BAR	120°C	6-8 BAR	

BFSDA

AIR / WATER



Spring Return Pneumatic · 316SS Body - PTFE Seat							BFSSR	
BFS550 - SR - T	50	SR75	*	10 BAR	-20°C	6-8 BAR	Body: 316 SS	Spring Return Pneumatic actuator. Direct pad mount. Optional: S/S Actuators
BFS565 - SR - T	65	SR88						
BFS580 - SR - T	80	SR88						
BFS5100 - SR - T	100	SR100						
BFS5125 - SR - T	125	SR115						
BFS5150 - SR - T	150	SR125						
BFS5200 - SR - T	200	SR145						
BFS5250 - SR - T	250	SR180						
BFS5300 - SR - T	300	SR200			10 BAR	120°C	6-8 BAR	
For normally open function change 4th digit to 6								

BFSSR

AIR / WATER



Electric On/Off • 316SS Body - PTFE Seat							BFSE	
BFS50 - E* - T	50	OM-1	*	10 BAR	-20°C	E1=240VAC E2=110VAC E5=24VAC E7=12VDC E8=24VDC 11=415VAC	Body: 316 SS	on/off electric actuator.
BFS65 - E* - T	65	OM-1						
BFS80 - E* - T	80	OM-A						
BFS100 - E* - T	100	OM-2						
BFS125 - E* - T	125	OM-3						
BFS150 - E* - T	150	OM-4						
BFS200 - E* - T	200	OM-4						
BFS250 - E* - T	250	OM-6						
BFS300 - E* - T	300	OM-7			10 BAR	120°C		Seat: PTFE Coated NBR
							Disc: 316 SS	
Available in Spring Return Electric Actuation and all St/St Electric Actuator								

BFSE

* Please Note: For dry powder applications, upsized actuator is recommended. Contact factory for sizing.

Series JMC

Model	Nominal Bore Ømm	Actuator	Media Pressure	Media Temperature	Flange Options	Material of Construction	Features
-------	------------------	----------	----------------	-------------------	----------------	--------------------------	----------

MULTI PURPOSE

Ductile Iron • 20 Bar

JMC



JMC31300 - 050 JMC31300 - 065 JMC31300 - 080 JMC31300 - 100 JMC31300 - 125 JMC31300 - 150 JMC31300 - 200 JMC31300 - 250 JMC31300 - 300 JMC31300 - 350 JMC31300 - 400 JMC31300 - 450 JMC31300 - 500 JMC31300 - 600	50 65 80 100 125 150 200 250 300 350 400 450 500 600	Bare Shaft (ISO) Lever, Gearbox, Pneumatic, Electric	20 BAR	-20°C 130°C Continuous	Standard: Wafer Optional: Lug/Double Flange	• Ductile Iron Body • 316 S/S disc • EPDM liner (E) • NBR liner (N) (Optional)	• Lever: Standard or Heavy Duty • Gearbox • Pneumatic: DA or SR • Electric • Simple Liner Replacement gives short down time. • Up to 2400mm Ø available
--	---	---	---------------	--	---	---	--

General Applications:

Water treatment, Food and drinks industries, Sugar and paper mills, Chemical, Oil, Offshore, Sea water, General industries.

Technical Data:

Diameter (DM): 50 to 2400
Pressure (bar): 20 max
Temperature (°C): -30 to 130

Flange Types:

Diameter (DM): 50 to 2400
PN 6-25 / ANSI 150-300 / AWWA / JIS
(Other: on request)

Certifications and Approvals:

Marine (ABS, Bureau Veritas, DNV), Oil (Total), Fire protection (VDS, APSAD, UL, FM), Potable water (ACS, WRAS, PSB), Food (FDA), Electrical continuity

Series ZGX Triple Eccentric

Model	Nominal Bore Ømm	Actuator	Media Pressure	Media Temperature	Flange Options	Material of Construction	Features
-------	------------------	----------	----------------	-------------------	----------------	--------------------------	----------

SEVERE DUTY

Cast Steel • Triple Eccentric • 20 Bar

ZGX



ZGXH - 050 ZGXH - 065 ZGXH - 080 ZGXH - 100 ZGXH - 125 ZGXH - 150 ZGXH - 200 ZGXH - 250 ZGXH - 300	50 65 80 100 125 150 200 250 300	Bare Shaft (ISO) Lever, Gearbox, Pneumatic, Electric	20 BAR	-20°C 270°C	Standard: Wafer Optional: Lug + Flange	• Cast Steel Body • Cast Steel disc • Stellite/Graphite Seat 2205SS	• 270°C max temperature • Triple Eccentric • Long Life • Low Torque • The Seat wears in. The tighter it is closed the better the seal • Larger sizes available • Optional Lever, Pneumatic, Electric Actuators available
---	---	---	---------------	---	--	--	---

Sizes up to 2000mm Diameter available upon request.

General Applications:

High temperature steam and liquids. Critical applications.

Technical Data:

Diameter (DM): 50 to 2000
Pressure (bar): 20
Wafer: Connection

Flange Types:

Wafer available for all flange types
ANSI: - 150 - 200 - 600 - 900

Certification & Approvals:

ISO, CE, TS, API
Optional to 20 Bar working pressure

Valve Handle

Heavy Duty with Locking Beville

NPVLEV

Series NPVLEV

Model	Mounting Interfaces	Drive Sizes Square	Body Material	Feature
NPVLEV - F0711 NPVLEV - F1014 NPVLEV - F1019	F07 F10 F10	11mm 14mm 19mm	CF8M	Heavy Duty for harsh environments. Locking handle for partial closure. Locking pin for security.

Valve Lockout

Safety Lockout for Valve / Actuator

VSL

Series VSL

Model	Mounting Interfaces	Drive Sizes Square	Body Material	Feature
VSL - * (13 models - See website for details)	F05 - F25	7mm - 55mm	2205 Duplex Stainless Steel	Locks directly onto valve spindle. Retrofit easily between valve and actuator. Wafer style externally compatible. Takes safety lockout tags.

Electric

Double Acting.



Power On, Power Off • Die Cast Housing • FBE Coating

OM

OM-1 - *	35	13	15	F03/F05	14	STAR DRIVE	✓	✓	✓	✓	OPTIONAL	OPTIONAL Exdb11BT 4Gb, Exdb111CT130Cdb1P68
OM-A - *	50	24	20	F05/F07	17		✓	✓	✓	✓		
OM-2 - *	90	17	15	F07/F10	22		✓	✓	✓	✓		
OM-3 - *	150	26	22	F07/F10	22		✓	✓	✓	✓		
OM-4 - *	400	18	16	F10/F12	36		✓	✓	✓	✓		
OM-5 - *	500	25	22	F10/F12	36		✓	✓	✓	✓		
OM-6 - *	650	31	28	F10/F12	36		✓	✓	✓	✓		
OM-7 - *	1000	55	46	F14#	36		✓	✓	✓	✓		
OM-8 - *	1500	55	46	F14#	36		✓	✓	✓	✓		
OM-9 - *	2000	70	58	F16#	75 Ø		✓	✓	✓	✓		
OM-10 - *	2500	70	58	F16#	75 Ø		✓	✓	✓	✓		
OM-11 - *	3000	70	58	F16#	75 Ø		✓	✓	✓	✓		
OM-12 - *	3500	70	58	F16#	75 Ø		✓	✓	✓	✓		
OM-13 - *	4500	95	—	F25#	75 Ø	✓	✓	✓	✓			

Modulating

Input 4-20ma, 1-5V DC, 2-10V DC • Die Cast Housing • FBE Coating

Omm



OM-1M - *	35	13	15	F03/F05	14	STAR DRIVE	✓	✓	✓	OPTIONAL	✓	OPTIONAL Exdb11BT 4Gb, Exdb11CT130CdbIP68
OM-AM - *	50	24	20	F05/F07	17		✓	✓	✓		✓	
OM-2M - *	90	17	15	F07/F10	22		✓	✓	✓		✓	
OM-3M - *	150	26	22	F07/F10	22		✓	✓	✓		✓	
OM-4M - *	400	18	16	F10/F12	36		✓	✓	✓		✓	
OM-5M - *	500	25	22	F10/F12	36		✓	✓	✓		✓	
OM-6M - *	650	31	28	F10/F12	36		✓	✓	✓		✓	
OM-7M - *	1000	55	46	F14#	36		✓	✓	✓		✓	
OM-8M - *	1500	55	46	F14#	36		✓	✓	✓		✓	
OM-9M - *	2000	70	58	F16#	75 Ø		✓	✓	✓		✓	
OM-10M - *	2500	70	58	F16#	75 Ø		✓	✓	✓		✓	
OM-11M - *	3000	70	58	F16#	75 Ø		✓	✓	✓		✓	
OM-12M - *	3500	70	58	F16#	75 Ø		✓	✓	✓		✓	
OM-13M - *	4500	95	—	F25#	75 Ø	✓	✓	✓	✓			
12 VDC Modulating Not Available			# Optional Mounting Available									

Stainless Steel

Power on, Power Off. SS316 Housing

OMS



OMS-1 - *	35	13	15	F03/F05	14	↑ STAR DRIVE ↓	✓	✓	✓	✓	OPTIONAL	-
OMS-2 - *	90	17	15	F07/F10	22		✓	✓	✓	✓		-
OMS-3 - *	150	26	22	F07/F10	22		✓	✓	✓	✓		-
OMS-4 - *	400	18	16	F10/F12	36		✓	✓	✓	✓		-
OMS-5 - *	500	25	22	F10/F12	36		✓	✓	✓	✓		-
OMS-6 - *	650	31	28	F10/F12	36		✓	✓	✓	✓		-
Available with 4-20mA Modulating Control												

Spring Return

Fail Safe • Die Cast Housing • FBE Coating • With and without manual override

S



S500 - *	50	9	3	7	3	F07	17	STAR DRIVE	-	✓	✓	✓	OPTIONAL	OPTIONAL Exdb11BT 4Gb, Exdb11CT130CdbJP68
S1300 - *	130	9	8	8	8	F10	22		-	✓	✓	✓		
S2000 - *	200	13	12	11	12	F12	27		-	✓	✓	✓		
S2600 - *	250	17	12	12	12	F12	27		-	✓	✓	✓		
S3600 - *	360	19	19	24	24	F12	36		-	✓	✓	✓		
S500 H - *	50	9	3	7	3	F07	17		✓	✓	✓			
S1300 H - *	130	9	8	8	8	F10	22		✓	✓	✓			
S2000 H - *	200	13	12	11	12	F12	27		✓	✓	✓			
S2600 H - *	250	17	12	12	12	F12	27		✓	✓	✓			
S3600 H - *	360	19	19	24	24	F12	36		✓	✓	✓			

Optional Items

Multi-Turn Actuator • M41 • M55 • M80 • M100

 On/Off	 Modulating	 Spring Return		- Limit Switches 2xZero Voltage L/S Standard with all actuators other than modulating. (0.250v. 5 amp) - Modulating Control. 4–20MA, 1–5VDC, 2–10VDC - Explosion Proof IECEx  , ATEX,  - Special Voltages — Including 415V 3 Phase - Local Control Unit - Potentiometer (1K or 5K OHM) - Torque Limiter	- Current Position Transmitter output 4–20MA - Heater - High Speed Open & Close, 3 Seconds, 8 Seconds - Floating Controller - Standard Voltages: 240vAC, 110vAC, 24vAC, 12vDC, 24vDC, 415vAC - Other Voltages Available - Slow Speed Open/Close Options to 150 Seconds
OME	OMEM	SE	Local Control Unit		

All above optional items are special order and subject to lead times.

- Pneumatic • Aluminium
- Stainless Steel

Pneumatic Double Acting

Double Acting



Model	Double Acting Torque (Nm) @ 6 Bar Air Supply	MTG Flange ISO5211	Drive MM (F to F)	Features & Options
Aluminium Body • Double Acting (Nett Torque) DA				
DA32	8	F03	9	Standard: Visual indicator Adjustable stroke Anodised aluminium body (Std) NBR seals (80°C) 8 BAR (max) Options: Viton seals See page 29 for Drive Adapters
DA50	19.9	F03/F05	11	
DA63	35.2	F05/F07	14	
DA75	70	F05/F07	17	
DA88	110	F05/F07	17	
DA100	160	F07/F10	17	
DA115	258	F07/F10	22	
DA125	332	F07/F10	22	
DA145	522	F10/F12	27	
DA160	681	F10/F12	27	
DA180	919	F10/F14	36	
DA200	1276	F10/F14	36	
DA240	2785	F16	46	
DA270	3720	F16	46	
DA380	4636	F16	46	
DA570	6941	F16/F25	46	
DA800	9890	F16/F25	55	
Indent Only				

Double Acting



Stainless Steel Body • Double Acting (Nett Torque)				SDA	
SDA52	24	F04/F05	11	STAR DRIVE	Standard: Visual indicator Adjustable stroke 304 Stainless Steel body (std) NBR seals (80°C) 8 BAR (max) Options: Viton seals (120°C) SS316 Body
SDA63	43	F05/F07	14		
SDA83	85	F05/F07	17		
SDA105	195	F07/F10	22		
SDA125	346	F07/F10	22		
SDA140	521	F10/F12	27		
SDA160	794	F10/F12	27		
SDA210	1596	F14	36		
Larger sizes available in Stainless Steel					

Scotch Yoke Actuator available in DA & SR for larger torques

Pneumatic Spring Return

Spring Return



Model	Spring Return (Full Spring Set)				MTG Flange ISO5211	Drive MM (F to F)	Features & Options
	Spring Torque (Close) (Nm)		Air Torque (Open)(Nm) @ 6 Bar Air Supply				
	0°	90°	0°	90°			
Aluminium Body • Spring Return (Nett Torque)							SR
SR50	8.1	11.7	11.9	8.2	F03/F05	11	Standard: Visual indicator Adjustable stroke Anodised aluminium body (Std) NBR seals (80°C) 8 BAR (max) Options: Viton seals See page 29 for Drive Adapters
SR63	13.3	20.2	21.9	14.9	F05/F07	14	
SR75	26.5	41.5	43.3	28.3	F05/F07	17	
SR88	44	69.3	65.8	40.5	F05/F07	17	
SR100	60.8	96.5	98.7	65	F07/F10	17	
SR115	98.4	157	159	100	F07/F10	22	
SR125	126	198	206	135	F07/F10	22	
SR145	198	309	324	213	F10/F12	27	
SR160	269	399	411	282	F10/F12	27	
SR180	379	568	540	351	F10/F14	36	
SR200	510	756	766	520	F10/F14	36	
SR240	1124	1685	1661	1100	F16	46	
SR270	1580	2369	2336	1548	F16	46	
SR380	1888	2744	2748	1892	F16	46	
SR570	2972	4313	3969	2629	F16/F25	46	
SR800	3311	4924	6580	4966	F16/F25	55	

Spring Return



Stainless Steel Body • Spring Return (Full Spring Set) (Nett Torque)							SSR	
SSR52	10	14	13.5	8.5	F04/F05	11	STAR DRIVE	Standard: Visual indicator Adjustable stroke 304 Stainless Steel body (std) NBR seals (80°C) 8 BAR (max) Options: Viton seals SS316 Body
SSR63	16	25	25	16	F05/F07	14		
SSR83	38	55	52	34	F05/F07	17		
SSR105	76	118	117	73	F07/F10	22		
SSR125	125	188	175	110	F07/F10	22		
SSR140	205	309	309	200	F10/F12	27		
SSR160	335	500	450	275	F10/F12	27		
SSR210	625	863	864	620	F14	36		
Larger sizes available in Stainless Steel								

Big range of Scotch Yoke Actuators available.

Gear Box Cast Steel

DE-CLUTCH



Model	Speed Ratio	Torque (Nm)	Connection ISO 5211		Hand Wheel Dia (mm)	Drive □ mm		Suggested Actuator Size	
		Output Max.	Valve	Actuator		Actuator	Valve	DA	SR
DC1 - 11	40:1	300	F05/F07	F05/F07	200	11	11	52	52
DC1 - 14						14	14	63	63
DC1 - 17						17	17	75	75
DC2 - 14	28:1	350	F07	F07/F10	300	14	11	63	63
DC2 - 17						17	17	75	100
DC2 - 22						22	22	-	-
DC3 - 22	32:1	640	F07/F10	F10/F12	300	22	22	115	125
DC4 - 27	50:1	1200	F10/F12	F10/F12	350	27	27	140	160
DC5 - 36	62:1	2100	F14	F14/F16	400	36	36	180	200
DC6 - 46	70:1	2800	F16	F14/F16	500	46	46	240	270


Features: • Ductile Iron Body, FBE Coating.
• IP67 Environment Protection.
• SS316 Drive Shaft and Fastenings
• Air Safety Interlock (Exhausts Actuator when Engaged)

Function: Can manually override a pneumatic actuated valve

* Add Value Torque when sizing for Spring Return Actuator

Also available with SS316 Body

DIRECT




Suitable for Ball Valve & Butterfly Valve					Drive □ mm	□	○
GB1	40:1	255	F05/F07	200	14	Ø 14 x 10 Ø 16 x 11	
GB2	36:1	570	F07/F10	300	22	Ø 19 x 13 Ø 22 x 16	
GB3	36:1	930	F10/F12	350	27 (or 36)	Ø 28 x 19	
GB4	50:1	1400	F14	400	36		Ø25 ~ Ø45
GB5	70:1	2600	F16	500	36 (or 46)		Ø45 ~ Ø75
GB6	140:1	5200	F16	500	46 (or 55)		Ø45 ~ Ø75
GB7	207:1	8000	F25	500	46 (or 55)		Ø60 ~ Ø80

Features: • Ductile Iron Body, FBE Coating
• IP67 Environment Protection, IP68 Optional
• SS316 Drive Shaft and Fastenings
• Suitable for Ball and Butterfly Valves
• Visual Position Indicator
• Optional Chain Drive GBC

Full SS316 Available on request

□ = Square Drive (standard)
○ = Double D (optional)
○ = Custom Hole & Keyway (optional)

DRIVE ADAPTORS



- Adapters - Customised as requested.
- Shaft Extensions - Customised for Butterfly and Gate Valves
- Special - Valve Assemblies Made to Order

Mounting Brackets



BKT 1	F03 - F04 - F05
BKT 2	F04 - F05 - F07
BKT 3	F07 - F10 - F12
BKT 4	F10 - F12 - F14
BKT 5	F10 - F12 - F14 - F16

Square to Square mm			Star to Square mm			Double D mm to Star				Key Drive mm to Star				
Model	A	B	Model	C	D	Model	C	E	ØF	Model	C	K	ØG	Length
ZT 11 - 9	11	9	ST 11 - 9	11	9	DT 17 - 9.6	17	9.6	14.5	KD 17 - 12.8	17	3	12.8	19
ZT 14 - 9	14	9	ST 14 - 9	14	9					KD 19 - 12.8	19	3	12.8	19
ZT 14 - 11	14	11	ST 14 - 11	14	11	DT 17 - 11.2	17	11.2	16.1	KD 22 - 15.9	22	5	15.9	24
ZT 17 - 9	17	9	ST 17 - 9	17	9					KD 22 - 19.05	22	5	19.05	24
ZT 17 - 11	17	11	ST 17 - 11	17	11	DT 22 - 16.1	22	11.2	16.1	KD 27 - 19.05	27	5	19.05	29
ZT 17 - 14	17	14	ST 17 - 14	17	14					KD 27 - 22.2	27	5	22.2	29
ZT 22 - 14	22	14	ST 19 - 11	19	11	DT 22 - 19.25	22	12.8	19.25	KD 36 - 28.7	36	8	28.7	38
ZT 22 - 17	22	17	ST 19 - 14	19	14					KD 36 - 31.8	36	8	31.8	38
ZT 22 - 19	22	19	ST 19 - 17	19	17	DT 27 - 19.25	27	12.8	19.25	KD 46 - 31.8	46	8	31.8	48
ZT 27 - 17	27	17	ST 22 - 14	22	14					KD 46 - 33.3	46	10	33.3	48
ZT 27 - 22	27	22	ST 22 - 17	22	17	DT 27 - 22.4	27	16	22.4	KD 46 - 38.1	46	10	38.1	48
ZT 35 - 27	35	27	ST 22 - 19	22	19					KD 46 - 41.4	46	12	41.4	48
ZT 36 - 22	36	22	ST 27 - 17	27	17	DT 36 - 22	36	16	22					
ZT 36 - 27	36	27	ST 27 - 22	27	22									
			ST 35 - 19	35	19									
			ST 36 - 22	36	22									
			ST 36 - 27	36	27									
			ST 46 - 36	46	36									

Custom Drive Extensions (S/S316) Consult Factory • GBC Chain Drive and Gear Box assembly available.

- Limit Switch Box • Positioner
- Heavy Duty Valve Handle
- Safety Lockout

Feed Back

Limit Switch Box



Aluminium Enclosure • Prewired • Hi Visual Indicator • IP67

SK

SK - 100	IP67	2 x SPDT Mechanical Switch 10 Amp AC 250V Max 2 Amp DC	-20°C – 80°C	2 Cable Entry M20 x 1.5	Die Cast Aluminium. Powder Coated. SK-1 Bracket Standard (Equivalent to APL210N)
----------	------	--	--------------	----------------------------	---

Limit Switch Box



Aluminium Enclosure • Explosive Atmosphere • IP66

ALSEX

ALS 500 M2 Ex	IP66	15A SPDT x 2 (Std) 15A SPDT x 3 } Optional 15A SPDT x 4 }	-25°C – 85°C	2 Cable Entry M20 x 1.5	Die Cast Aluminium. Powder Coated. Coated Bracket Supplied to suit DA/SR 50-270 Exd II BT6 IEC Ex CQM 12.0047 IP66
 Explosive Atmosphere		Various Inductive Sensors (Optional)			

Limit Switch Box



316 Stainless Steel Enclosure • Explosive Atmosphere • IP66

ALSEX

ALS 600 M2 Ex	IP66	15A SPDT x 2 (Std) 15A SPDT x 3 } Optional 15A SPDT x 4 }	-25°C – 85°C	2 Cable Entry M20 x 1.5	316SS Body SS Bracket Supplied to suit DA/SR 50-270 Exd II BT6 IEC Ex CQM 12.0047 IP66
 Explosive Atmosphere		Various Inductive Sensors (Optional)			

Rotary Electro-Pneumatic Positioner • IP66 • DA (Std) SR optional

POS-LIN



Model	Function	Rating		Features and Options
POS - A	Analogue DA & SR	Weatherproof IP66 Sensitivity 0.4%	1.5% Hysteresis 3LPM@1.5 BAR AIR	Powder Coated Aluminium Body Conduit Entry M20 X 1.5 Input 4-20mA Output 4-20mA Supply Pressure 1.4 ~ 7 BAR 90° Rotation Powder Coated Steel (Black) Bracket supplied to suit DA/ SR 50-270 Standard. Other Brackets - Please specify when ordering.
POS - D	Digital DA	Weatherproof IP66 Sensitivity 0.4%	1.5% Hysteresis 3LPM@1.5 BAR AIR	
POS - DS	Digital SR	Smart Positioner		
DA = Double Acting (Standard) SR = Single Acting (Optional) PLEASE SPECIFY WHEN ORDERING				

Linear Electro-Pneumatic Positioner • IP66 • DA (Std) SR optional

POS-LIN



Model	Function	Rating		Features and Options
POS - LIN - D	Linear DA	Weatherproof IP66 Sensitivity 0.4%	1.5% Hysteresis 3LPM@1.5 BAR AIR	Powder Coated Aluminium Body Conduit Entry M20 X 1.5 Input 4-20mA Output 4-20mA Supply Pressure 1.4 ~ 7 BAR Powder Coated Steel (Black) Bracket supplied to suit DA/ SR 50-270 For Actuators greater than 180cm3 Volume. Standard with 10-40mm Feedback Lever. Larger Lever on request
POS - LIN - SR	Linear SR			
DA = Double Acting (Standard) SR = Single Acting (Optional) PLEASE SPECIFY WHEN ORDERING				

Mounting Brackets Optional Material & Function

SK



Mounting Brackets		To suit Actuators	Base Holes	Height mm	Material:
SK-1 BKT SK-2 BKT	Std. BKT Optional	DA/SR 50 - 100 Old Style High Mounting	80 x 30 80 x 30	30 40	SS304 50mm PCD Mounting (F05)
SK-3 BKT SK-4 BKT	Optional Optional	DA/SR 115 - 240 Old Style High Mounting	130 x 30 130 x 30	40 60	
SK-M1	Multi Function	Suits most size Actuators DA/SR 50-270	80 x 30 130 x 30	30/40 30/40	Powder Coated Steel – Black. 50mm (F05) Limit Switch Mounting
SK-M	Multi Function	Suits most size Actuators DA/SR 50-270	80 x 30 130 x 30	40/52.5 40/52.5	Powder Coated Steel – Black. 50mm (F05) Limit Switch Mounting

Knife Gate



Series KGDHW

Cast Iron
Manual
Hand Wheel

Model	Orifice Ømm	Diameter Nominal (D/N)	Actuator	Media Pressure	Media Temperature	Actuator Air Pressure	Material of Construction	Features
Manual Hand Wheel • Cast Iron • Unidirectional								
KGDHWN - 50	50	50	HAND WHEEL RISING STEM	10 BAR	0°C		Blade: SS316 Body: Cast Iron	Low Torque Hand Wheel
KGDHWN - 65	65	65					Stem: SS304	Fusion Bonded Epoxy Coating
KGDHWN - 80	80	80					Shroud: FBE Coated Steel	Rising Stem
KGDHWN - 100	100	100					Seats: NBR	
KGDHWN - 125	125	125					Packing: PTFE	
KGDHWN - 150	150	150						
KGDHWN - 200	200	200						
KGDHWN - 250	250	250		10 BAR	80°C NBR			
KGDHWN - 300	300	300						
Sizes up to 1000mm available • AS2129 Table E • AS4087 • Sizes above 300mm EN1092 Flange								

KGDHW



Series KGSHR

SS316
Manual Hand Wheel

Manual Hand Wheel ST/ST • Unidirectional								
KGSHRN/M - 50	45	50	HAND WHEEL RISING STEM	10 BAR	0°C		Blade: SS316 Body: SS316	Metal or Elastomer Seat
KGSHRN/M - 65	60	65					Stem: SS304	Fully Lugged
KGSHRN/M - 80	74	80					Shroud: SS304	Uni-Directional
KGSHRN/M - 100	93	100					Seats: NBR or Metal	Rising Stem
KGSHRN/M - 125	116	125					Optional: VITON, EPDM	Optional: ANSI 150
KGSHRN/M - 150	138	150						
KGSHRN/M - 200	188	200						
KGSHRN/M - 250	233	250						
KGSHRN/M - 300	281	300						
KGSHRN/M - 350	330	350						
KGSHRN/M - 400	368	400			80°C NBR 100°C METAL			
KGSHRN/M - 450	415	450			Optional VITON / EPDM			
KGSHRN/M - 500	460	500		10 BAR				
KGSHRN/M - 600	560	600						
Sizes up to 1000mm available • N = NBR Seat • M = Metal Seat • AS2129 Table E (STD) • AS4087 • Optional ANSI 150								

KGSHR



Series KGSDA

SS316
Double Acting
Pneumatic

Double Acting Pneumatic ST/ST • Unidirectional								
KGSDAN/M - 50	45	50	DOUBLE ACTING PNEUMATIC	10 BAR	0°C	6-8 BAR	Blade: SS316 Body: SS316	Double Acting Pneumatic
KGSDAN/M - 65	60	65					Stem: SS304	Fully Lugged
KGSDAN/M - 80	74	80					Shroud: SS304	Uni-Directional
KGSDAN/M - 100	93	100					Seats: NBR or Metal	Magnetic Piston for Reed Switch Feedback
KGSDAN/M - 125	116	125					Optional: VITON, EPDM	Optional: ANSI 150
KGSDAN/M - 150	138	150						
KGSDAN/M - 200	188	200						
KGSDAN/M - 250	233	250						
KGSDAN/M - 300	281	300						
KGSDAN/M - 350	330	350						
KGSDAN/M - 400	368	400			80°C NBR 100°C METAL			
KGSDAN/M - 450	415	450			Optional VITON / EPDM			
KGSDAN/M - 500	460	500		10 BAR		6-8 BAR		
KGSDAN/M - 600	560	600						
Sizes up to 1000mm available • N = NBR Seat • M = Metal Seat • AS2129 Table E (STD) • AS4087 • Optional ANSI 150								

KGSDA

- Options: Micro Sensors (Electric & Pneumatic), Deflector Cones, Solenoid & Remote Control, Extensions, Electric Control, Chain Drive, ANSI 150 Flange, Higher Pressure.
- Optional Limit Switches. KGM = Mechanical Lever SPDT IP65 (10amp 250v AC/DC) KGR = Magnetic Reed Switch SPST IP65 (10mA max 5-120v AC/DC)

Gate Valves

AIR / WATER



Model	Nominal Bore Ømm	Actuator	Connection	Media Pressure	Media Temperature	Material of Construction	Features
Manual Hand Wheel · Brass Body · BSP							GVB
GVB - 04	15	HAND WHEEL RISING STEM	1/2	16 BAR	-20°C	Body: Brass Seat: Brass Gland: PTFE	Economical Isolation Valve Media: Air/Water
GVB - 05	20		3/4				
GVB - 06	25		1				
GVB - 07	32		1-1/4				
GVB - 08	40		1-1/2				
GVB - 09	50		2				
GVB - 11	80		3				
GVB - 12	100		4	16 BAR	120°C		

AIR / STEAM



Manual Hand Wheel · Forged Steel · Class 800 · NPT							GVF8
GVF8 - 04	15	HAND WHEEL RISING STEM	1/2	13.62 Mpa @ -29 to 35 deg C	454 deg C @ 5.5 Mpa	Body: Forged Steel Seat: Cr13 Gland: Flexible Graphite Coating: Black Steel	ASTM A105 API 602 design ASME B1.20.1 ends API 598 test Class 800 Media: Fluid/Steam
GVF8 - 05	20		3/4				
GVF8 - 06	25		1				
GVF8 - 07	32		1-1/4				
GVF8 - 08	40		1-1/2				
GVF8 - 09	50		2				

WATER / FLUIDS



Manual Hand Wheel • Carbon Steel • ANSI 150 • Rising Stem • ANSI 300							GVWR + GVWR3
GVWR - 50	50	MANUAL HAND WHEEL RISING STEM	RF FLANGED ANSI 150	1964 Kpa @ -29 to 35 deg C	260 deg C @ 1171 Kpa	Body: Cast Steel	ASTM A216-WCB
GVWR - 65	65					Wedge: Cast Steel	API 600 Design
GVWR - 80	80					Packing:	ASME B16.10
GVWR - 100	100					Graphite/304	ASME B16.5 ends
GVWR - 125	125						API 598 test
GVWR - 150	150						
GVWR - 200	200						
GVWR - 250	250						
GVWR - 300	300						
Optional: Class 300, 600, 900, 1500, 2500 - ANSI 300 GVWR3							

WATER / FLUIDS



Manual Hand Wheel · SS316 · BSP							GVS
GVS - 04	15	HAND WHEEL RISING STEM	1/2	13 BAR AIR / WATER 16 BAR FLUID 10 BAR STEAM	-20°C 180°C	Body: SS316 Seat: SS316 Gland: PTFE	ANSI 816.34 Design BS21/2779 ends API 598 test Media: Fluid
GVS - 05	20		3/4				
GVS - 06	25		1				
GVS - 07	32		1-1/4				
GVS - 08	40		1-1/2				
GVS - 09	50		2				

WATER / FLUIDS



Manual Hand Wheel • Rising Stem • SS316 • ANSI 150							GVSF
GVSF - 50 GVSF - 65 GVSF - 80 GVSF - 100 GVSF - 125 GVSF - 150 GVSF - 200 GVSF - 250 GVSF - 300	50 65 80 100 125 150 200 250 300	MANUAL HAND WHEEL RISING STEM	RF FLANGED ANSI 150	1964 Kpa @ -29 to 35 deg C	260 deg C @ 1171 Kpa	Body: CF8M Wedge: CF8M Stem: F316 Packing: Graphite/316	CF8M API 600 Design ASME B16.10 ASME B16.5 ends API 598 test Media: Fluid/Steam
Optional: Class 300, 600							

2 Way Gate Valves Pinch Valves

Resilient Seated Ductile Iron
Gate Valve
Angle Seat Valve

Gate Valves

WATER / FLUIDS



Model	Nominal Bore Ømm	Actuator	Connection	Media Pressure	Media Temperature	Material of Construction	Features	
Manual Hand Wheel • Ductile Iron • AS4087 PN16							GVC	
GVC - 050	050	MANUAL HAND WHEEL NON RISING STEM	RF FLANGED AS 4087 PN16	16 BAR	0°C	Body: Ductile Iron Powder Coated Wedge: EPDM Coated Ductile Iron Stem: Stainless Steel Bonnet: Ductile Iron Bush: Bronze Coating: R4-ES FBE Counter Clockwise to Open	Design AS 2638.2-2006 End Flange	
GVC - 065	065			16 BAR	0°C			Standard: AS4087 PN16
GVC - 080	080							
GVC - 100	100							
GVC - 125	125							
GVC - 150	150							
GVC - 200	200							
GVC - 250	250							
GVC - 300	300							
GVC - 350	350							
GVC - 400	400							
GVC - 450	450							
GVC - 500	500	16 BAR	40°C		Optional: AS2129 Table E			
GVC - 600	600							
Optional • Metal Seat • Key Cap							 SMK26312 WMK26312 WSSA	

FLOW CONTROL



Needle Valve - SS316 • BSP							NVS
NVS - 01	5	MANUAL TEE LEVER	1/8	BSP	408 BAR	180°C	Body: SS316 Packing: PTFE Fine Adjustment of Flow
NVS - 02	5		1/4				
NVS - 03	5		3/8				
NVS - 04	5		1/2				
NVS - 05	7		3/4				
NVS - 06	9		1				


AIR / FLUID / STEAM



Angle Seat Valve - SS316 • BSP							AS
AS5 - 04 - SR	13	PNEUMATIC ACTUATING SPRING CLOSED ↓	1/2	Over Seat 16 BAR 16 BAR	-10°C 180°C	Body & Actuator: SS316 Packing: PTFE FKM	Compact Design Single Acting (Spring return) Normally Closed
AS5 - 05 - SR	18		3/4				
AS5 - 06 - SR	24		1				
AS5 - 07 - SR	31		1-1/4				
AS5 - 08 - SR	35		1-1/2				
AS5 - 09 - SR	45		2				
Optional Proximity Switch • DA Actuator • Tri-Clover Clamps							

Pinch Valve Rubber

FLUID / SLURRY



Pinch Valve - Plastic • Air Pilot Control • Normally Open							
Model	Nominal Bore mm	N.O. - BSP	Media Pressure	Pilot Pressure	Specification	Material of Construction	Features
STANDARD	Bore MM	BSP	Media	Pilot	Contact Process Systems for individual sleeve specs.	Housing: G.R Nylon Sleeve: NBR	Air, Fluid & Dry Flowables. Viscous Fluid Slurry Sludge Service No Blockage. Full Flow. Air pilot operated
AP - 6331	6	N.O. 1/4	3.4	5.5			
AP - 6291	8	3/8	4	6			
AP - 6222	16	3/4	4	6			
AP - 6206	32	1 1/4	4	6			
AP - 6603	50	N.O. 2	3.4	4.7			

Globe Valve

AIR / FLUID



Model	Nominal Bore Ømm	Actuator	Connection	Media Pressure	Media Temperature	Material of Construction	Features
Manual Hand Wheel • SS316 • BSP							GLS
GLS - 04 GLS - 05 GLS - 06 GLS - 07 GLS - 08 GLS - 09	15 20 25 32 40 50	MANUAL HAND WHEEL RISING STEM	1/2 3/4 1 1-1/4 1-1/2 2 BSP	13 BAR AIR/WATER/ OIL	-20°C 180°C	Body: SS316 Seat: SS316 Packing: PTFE	ANSI B16.34 Design BS21/2779 ends API598 Test Media: Air/Water/Oil

AIR / FLUID / STEAM



Manual Hand Wheel • Forged Steel • Class 800 • NPT							GLF8
GLF8 - 04 GLF8 - 05 GLF8 - 06 GLF8 - 07 GLF8 - 08 GLF8 - 09	15 20 25 32 40 50	MANUAL HAND WHEEL RISING STEM	1/2 3/4 1 1-1/4 1-1/2 2 NPT	13.62 Mpa @ -29 to 35 deg.C	454 deg.C @ 5.5 Mpa	Body: Forged Steel Seat: 13Cr Packing: Flexible Graphite Coating: Black Steel	ASTM A105 API 602 design ASME B1.20.1 ends API598 Test Class 800 Media: Fluid/Steam

AIR / FLUID / STEAM



Manual Hand Wheel • Carbon Steel • ANSI 150							GLOW
GLOW - 50 GLOW - 65 GLOW - 80 GLOW - 100 GLOW - 125 GLOW - 150 GLOW - 200 GLOW - 250 GLOW - 300	50 65 80 100 125 150 200 250 300	MANUAL HAND WHEEL RISING STEM	ANSI 150 FLANGE	1964 Kpa @ -29 to 35 deg.C	260 deg.C @ 1171 Kpa	Body: Cast Steel Seat: Stellite Packing: Flexible Graphite Coating: Silver primer Optional: Bellows Seal	ASTM A216-WCB ASME B16.34 design ASME B16.10 ASME B16.5 ends API 598 test Media: Fluid/Steam
Optional: Class 600							

AIR / FLUID / STEAM



Manual Hand Wheel • Carbon Steel • ANSI 300							GLOW3
GLOW3 - 50 GLOW3 - 65 GLOW3 - 80 GLOW3 - 100 GLOW3 - 125 GLOW3 - 150 GLOW3 - 200	50 65 80 100 125 150 200	MANUAL HAND WHEEL RISING STEM	ANSI 300 FLANGE	5170 Kpa @ -29 to 35 deg.C	260 deg.C @ 1171 Kpa	Body: Cast Steel Seat: Stellite Packing: Flexible Graphite Coating: Silver primer Optional: Bellows Seal	ASTM A216-WCB ASME B16.34 design ASME B16.10 ASME B16.5 ends API 598 test Media: Fluid/Steam
Optional: Class 600							

Bellow Sealed Globe Valve • Hot & Cold Water • Steam



BSV-2EN							BSV-2EN
BSV-2EN-015 BSV-2EN-020 BSV-2EN-025 BSV-2EN-032 BSV-2EN-040 BSV-2EN-050 BSV-2EN-065 BSV-2EN-080 BSV-2EN-100 BSV-2EN-125 BSV-2EN-150	15mm 20mm 25mm 32mm 40mm 50mm 65mm 80mm 100mm 125mm 150mm	MANUAL HAND WHEEL NON RISING	PN16 FLANGE	16 BAR	300°C	Body: Ductile Iron Internals: Stainless Steel PN25 Undrilled 25-150mm	Zero Leakage by Two-Stage Sealing Extremely Low Torque and Maintenance Free

Bronze Globe Valves • Threaded & Flanged • Hot & Cold Water • Steam



GLB							GLB
GLB Threaded	1/2" - 2" BSP	MANUAL HAND WHEEL	BSP	16 BAR	225°C	Body & Bonnet: Bronze Body Seat Ring, Disc & Stem: Stainless Steel	

Check Valve

AIR / FLUID / AQUACULTURE Ball Check • PVC



Model	Nominal Bore Ømm	Connection	Nominal Cracking Pressure	Media Pressure	Media Temperature	Material of Construction	Features
BCPE - 04	15	1/2	0.1 BAR Depending on Valve Size	10 BAR	0°C	UPVC Body	Optional: BSP Threaded
BCPE - 05	20	3/4		10 BAR	60°C	Seat: EPDM Optional Diaphragm: Viton FKM	Standard: Solvent Welded
BCPE - 06	25	1					
BCPE - 08	40	1-1/2					
BCPE - 09	50	2					
FKM Optional							

AIR / WATER



Piston Check • Brass • BSP

Model	Nominal Bore Ømm	Connection	Nominal Cracking Pressure	Media Pressure	Media Temperature	Material of Construction	Features
PCBN - 04	15	1/2	0.1 BAR	16 BAR	-0°C	Body: Brass	Economical
PCBN - 05	20	3/4		16 BAR	80°C	Seat: NBR	Can be mounted in any attitude Media: Air/Water
PCBN - 06	25	1					
PCBN - 07	32	1-1/4					
PCBN - 08	40	1-1/2					
PCBN - 09	50	2					
PCBN - 11	80	3					

AIR / WATER



Swing Check • SS316 • BSP

Model	Nominal Bore Ømm	Connection	Nominal Cracking Pressure	Media Pressure	Media Temperature	Material of Construction	Features
SCS - 04	15	1/2	0.1 BAR	13 BAR	-20°C	Body: Stainless Steel 316	Economical
SCS - 05	20	3/4		13 BAR	180°C	Seat: NBR	Horizontal Mounting Media: Air/Water/ Steam
SCS - 06	25	1					
SCS - 07	32	1-1/4					
SCS - 08	40	1-1/2					
SCS - 09	50	2					

SCB Brass Check Valve available 1/2"-2" BSP

AIR / WATER / STEAM




Piston Check • Forged Steel • Class 800 • NPT

Model	Nominal Bore Ømm	Connection	Nominal Cracking Pressure	Media Pressure	Media Temperature	Material of Construction	Features
PCF8 - 04	15	1/2	0.1 BAR Depending on Valve Size	13.62 Mpa @ -29 to 35 deg C	454 deg C @ 5.5 Mpa	Body: Forged Steel	ASTM A105
PCF8 - 05	20	3/4				Seat: Cr13	API 602 design
PCF8 - 06	25	1				Gasket: Flexible Graphite/304	ASME B1.20.1 ends
PCF8 - 07	32	1-1/4					API 598 Test
PCF8 - 08	40	1-1/2					Class 800
PCF8 - 09	50	2				Coating: Black Steel	Media: Air/Fluid/Steam

Larger Sizes Available

STEAM / FLUID / PETROCHEMICAL Swing Check • Carbon Steel • ANSI 150 • Full Bore • ANSI 300



Model	Nominal Bore Ømm	Connection	Nominal Cracking Pressure	Media Pressure	Media Temperature	Material of Construction	Features
SCFW - 50	50	ANSI 150	0.1 BAR Depending on Valve Size	1964 Kpa @ -29 to 35 deg C	260 deg C @ 1171 Kpa	Body: Cast Steel	ASTM A216-WCB
SCFW - 80	80					Disc: Cast Steel	ASME B16.34 design
SCFW - 100	100					Coating: Silver Primer	ASME B16.10
SCFW - 125	125						ASME B16.5 ends
SCFW - 150	150						API 598 test
SCFW - 200	200					Gasket: Graphite/304	Full Bore
SCFW - 250	250						Media: Air/Fluid/Steam
SCFW - 300	300						

* AVAILABLE ANSI 300

AIR / FLUID / STEAM



In-Line Check Valve • SS316 • 2 Piece

Model	Nominal Bore Ømm	Connection	Nominal Cracking Pressure	Media Pressure	Media Temperature	Material of Construction	Features
ICS - 04	15	1/2	0.1 BAR Depending on Valve Size	54 BAR	-20°C	Body: CF8M/SS316	Design to ANSI B16.34
ICS - 05	20	3/4		54 BAR	180°C	Seat: SS316 Gasket: PTFE	Test API 1598
ICS - 06	25	1					Media: Fluids
ICS - 07	32	1-1/4					
ICS - 08	40	1-1/2					
ICS - 09	50	2					

AIR / FLUID / STEAM



In-Line Check Valve • SS316 • 3 Piece

Model	Nominal Bore Ømm	Connection	Nominal Cracking Pressure	Media Pressure	Media Temperature	Material of Construction	Features
ICS3 - 04	15	1/2	0.1 BAR Depending on Valve Size	54 BAR	-20°C	Body: CF8M/SS316	Design to ANSI B16.34
ICS3 - 05	20	3/4		54 BAR	180°C	Seat: SS316 Gasket: PTFE	Test API 1598
ICS3 - 06	25	1					Media: Fluids/Steam
ICS3 - 07	32	1-1/4					
ICS3 - 08	40	1-1/2					
ICS3 - 09	50	2					

Check Valve

AIR / WATER / STEAM



Series PCS
Piston Check
SS316

Model	Bore Ømm Nominal Orifice	Connection	Nominal Cracking Pressure	Media Pressure	Media Temperature	Material of Construction	Features
Piston Check · SS316							PCS
PCS - 04	1/2	BSP	0.3 BAR	800 PSI 54 BAR	-10°C 180°C	316 St/St PTFE Seat	One Way Flow
PCS - 05	3/4						Can be mounted in any attitude
PCS - 06	1						
PCS - 07	1-1/4						
PCS - 08	1-1/2						
PCS - 09	2						

FLUID / PETROCHEMICAL Swing Check · SS316 Body - Wafer



Series SCVS

Check Valve
SS316 Wafer
Viton Seat

AL Swing Check • SS316 Body - Wafer							SCVS	
SCVS - 50	50	32	WAFFER	0.1 BAR Depending on Valve Size	16 BAR	-20°C	Body: CF8M Disc: CF8M Pins: SS316 Seat: Viton (FKM)	Wafer Design
SCVS - 65	65	40			Fits in horizontal pipe.			
SCVS - 80	80	54			Reduced Flow			
SCVS - 100	100	70						
SCVS - 125	125	92						
SCVS - 150	150	114						
SCVS - 200	200	154						
SCVS - 250	250	200						
SCVS - 300	300	230				Suits ANSI 150 & DIN Flange only		

FLUID / STEAM




Series SDC

Single Disc
Metal Seat 316SS

Disc Check • SS316 Body • Wafer • Metal Seat							SDC
SDC - 15	15	WAFER	0.1 BAR Depending on Valve Size	40 BAR	-20°C	Body: CF8M	Wafer Design
SDC - 20	20			Disc: CF8M	High Temp		
SDC - 25	25			Spring: SS316	High Pressure		
SDC - 32	32			Metal to Metal Seat	Metal to Metal Seat		
SDC - 40	40				Reduced Flow		
SDC - 50	50			Metal to Metal Seat	Media: Fluid/Steam		
SDC - 65	65						
SDC - 80	80						
SDC - 100	100						
SDC - 125	125						
SDC - 150	150	DIN 3202-K4					
SDC - 200	200	Face to Face					

FLUID / PETROCHEMICAL Duo Check · SS316 Body · Wafer



Series DCVS

Duo Check
FKM Seat/316SS

AL Duo Check • SS316 Body • Wafer							DCVS	
DCVS - 50	50	WAFER	0.1 BAR Depending on Valve Size	40 BAR	-20°C	Body: CF8M	CF8M	
DCVS - 65	65			40 BAR	100°C	Disc: CF8M	ENS 584 design	
DCVS - 80	80					Pins: SS316	DIN 3202-K3	
DCVS - 100	100					Seat: FKM (Viton)	Face to Face	
DCVS - 125	125						ANSI 150 / PN16	
DCVS - 150	150						Media: Fluid/ Petrochemical	
DCVS - 200	200							
DCVS - 250	250							
DCVS - 300	300							

STEAM / FLUID / PETROCHEMICAL Swing Check · SS316 Body · ANSI 150



Series SCFS

Swing
Check
316SS

CHEMICAL Swing Check • SS316 Body • ANSI 150							SCFS
SCFS - 050	50	ANSI 150	0.1 BAR Depending on Valve Size	20 BAR	0°C	Body: CF8M	CF8M
SCFS - 080	80					Disc: CF8M	API 598 design
SCFS - 100	100					Pins: SS316	ASME B16.10
SCFS - 125	125					Gasket: Flexible Graphite/316	ASME B16.5 ends
SCFS - 150	150						API 598 test
SCFS - 200	200						Media: Fluid/Steam
SCFS - 250	250						
SCFS - 300	300					20 BAR	

AIR / WATER



Series DCVC

Check Valve
Cast Iron Wafer
DUO Check SS Disc

Duo Check • Cast Iron Body & Wafer							DCVC		
DCVC - 50	50	43	WAFER	0.1 BAR Depending on Valve Size	16 BAR	-10°C	Body: Cast Iron Disc: CF8M Seat: EPDM Coating: FBE	Wafer Design	
DCVC - 65	65	60							Twin Disc to give greater opening
DCVC - 80	80	66							
DCVC - 100	100	90							
DCVC - 125	125	116							
DCVC - 150	150	144							
DCVC - 200	200	198							
DCVC - 250	250	233							
DCVC - 300	300	283							
DCVC - 400	400	381							
DCVC - 450	450	419					ASTM A126 Body ASTM A370 Disc API 598 Test AS 2128 TE } Wafer ANSI 150		
DCVC - 500	500	467							
DCVC - 600	600	572			16 BAR	80°C NBR			

AIR / WATER / STEAM



Series BCV

Ball Check Valve
Ductile Iron

Ball Check • Ductile Iron Body • Table E							BCV
BCV - 50	50	TABLE E	0.3 - 16 BAR	16 BAR	10°C	Body: Ductile Iron	Self Cleaning
BCV - 65	65		0.3 - 16 BAR	16 BAR	80°C	Ball: Steel & NBR Outer	Flanged
BCV - 80	80						ASTM A536 Body NBR Coated Steel Ball
BCV - 100	100						
BCV - 125	125						
BCV - 150	150						
BCV - 200	200						
BCV - 250	250						
BCV - 300	300						
BCV - 400	400						
BCV - 500	500						
						Gasket: NBR	
						Fastening: SS304	Table E
						Coating: FBE	

Check Valve

AIR / WATER



Model	Nominal Bore ømm	Connection	Nominal Cracking Pressure - Water	Maximum Back Pressure - Water	Media Temperature	Material of Construction	Features		
Flex Check • Ductile Iron Body • Table E					FCVC		FCVC		
FCVC - 050	50	TABLE E	0.1 BAR Depending on Valve Size	16 BAR	-20°C	Body: Ductile Iron	Table E		
FCVC - 065	65								
FCVC - 080	80								
FCVC - 100	100								
FCVC - 125	125								
FCVC - 150	150								
FCVC - 200	200								
FCVC - 250	250								
FCVC - 300	300								
FCVC - 350	350								
FCVC - 400	400					16 BAR	80°C	Coating: FBE	ASTM A536 Body EPDM Seat API 598 Test

WATER / EFFLUENT




Duck Bill Valve • Reinforced Rubber • External Flanged							DBFS		
DBFS - 100	100	Flange type (table) must be specified at time of ordering	From 50mm Head depending on size	Up to 2m depending on size	0°C	Outer: Fabric Braided Neoprene	Low Head Loss		
100mm to 2000mm					Backing Ring: SS316	Reliable Backflow Prevention			
					Sizes Customised to Customer Requirements	Corrosion Resistant			
DBFS - 2000	2000				60°C		UV Stable		

WATER / EFFLUENT



Duck Bill Valve • Reinforced Rubber • Slip-On							DBSS		
DBSS - 100	100	Pipe outside Diameter (O.D.) must be specified at time of ordering	From 50mm Head depending on size	Up to 2m depending on size	0°C	Outer: Fabric Braided Neoprene	Low Head Loss		
100mm to 2000mm					Clamping Rings: SS316	Reliable Backflow Prevention			
					Sizes Customised to Customer Requirements	Corrosion Resistant			
						UV Stable			
DBSS - 2000	2000						60°C		Optional flat side valve for low pipes

WATER / EFFLUENT



Duck Bill Valve • Reinforced Rubber • Insertable Flanged + Insertable Clamp							DBIF + DBI		
DBIF - 100	100	Flange type (table) must be specified at time of ordering	From 50mm Head depending on size	Up to 2m depending on size	0°C	Outer: Fabric Braided Neoprene	Low Head Loss		
100mm to 1800mm					Sizes Customised to Customer Requirements	Reliable Backflow Prevention			
					Optional: DBI Insertable Clamp	Corrosion Resistant			
					DBIF - 1800	1800	60°C		

Used for flood mitigation and backflow prevention of contaminated fluids

Strainer

AIR / FLUID / AQUACULTURE Y Strainer • PVC



Model	Nominal Bore mm	Connection	Mesh	Media Pressure	Media Temperature	Material of Construction	Features
Y Strainer • PVC							YSP
YSP - 04	15	SOLVENT WELD SCHEDULE 80	20	10 BAR	0°C	UPVC Body	Solvent Weld
YSP - 05	20					Seats: EPDM	Schedule 80
YSP - 06	25						
YSP - 07	32						
YSP - 08	40						
YSP - 09	50		30			Mesh: Nylon	
YSP - 10	65						
YSP - 11	80						
YSP - 12	100				60°C		

AIR / FLUID



Y Strainer - Brass • BSP							YSB
YSB - 04	15	1/2	18	16 BAR	-20°C	Body: Brass	Economical Strainer
YSB - 05	20	3/4				Screen: SS304	
YSB - 06	25	1					
YSB - 07	32	1-1/4					
YSB - 08	40	1-1/2					
YSB - 09	50	2					
YSB - 11	75	3	18	16 BAR	150°C		

Strainer

AIR / FLUID / STEAM



Model	Nominal Bore ømm	Connection	Mesh	Media Pressure	Media Temperature	Material of Construction	Features
Y Strainer - SS316 · BSP							YSS
YSS - 04	15	1/2	18	800 PSI	-20°C	Body: CF8M	Removes Coarse Particles
YSS - 05	20	3/4	18	800 PSI	-20°C	Mesh: SS316	CF8M Body
YSS - 06	25	1	18	800 PSI	-20°C	Gasket: PTFE	SS316 Mesh
YSS - 07	32	1-1/4	18	800 PSI	-20°C		
YSS - 08	40	1-1/2	18	800 PSI	-20°C		
YSS - 09	50	2	18	800 PSI	-20°C		
YSS - 11	80	3	18	800 PSI	-20°C		
YSS - 12	100	4	18	54 BAR	200°C		

AIR / FLUID / STEAM



Y Strainer • 316SS • ANSI 150						YSSF	
YSSF - 25	25	ANSI150	14	1964Kpa @ -29 to 35 deg C	260 deg C @ 1171 Kpa	Body: CF8M / SS316 Screen: SS316 Gasket: Flexible Graphite/ SS304	ASTM A351-CF8M ASTM B16.34 design ASME B16.5 ends API 598 test
YSSF - 32	32		14				
YSSF - 40	45		14				
YSSF - 50	50		14				
YSSF - 65	65		14				
YSSF - 80	80		14				
YSSF - 100	100		10				
YSSF - 125	125		10				
YSSF - 150	150		10				
YSSF - 200	200		10				
Also available up to 600mm							

AIR / FLUID



Y Strainer · Ductile Iron · Table E							YSCF
YSCF - 50	50	Table E	10	16 BAR	-20°C	Body: Cast Iron	High Flow Economical
YSCF - 65	63		10	16 BAR	-20°C	Screen: SS304	ASTM536 Body
YSCF - 80	80		7	16 BAR	-20°C	FBE Coating	ASTMA370 Screen
YSCF - 100	100		7	16 BAR	-20°C		EPDM Gasket
YSCF - 125	125		7	16 BAR	-20°C		API 598 Test
YSCF - 150	150		4	16 BAR	-20°C		
YSCF - 200	200		4	16 BAR	-20°C		
YSCF - 250	250		4	16 BAR	-20°C		
YSCF - 300	300		4	16 BAR	-20°C		
YSCF - 350	350		4	16 BAR	-20°C		
YSCF - 400	400		4	16 BAR	-20°C		
YSCF - 500	500		4	16 BAR	-20°C		
YSCF - 600	600		4	16 BAR	90°C		

AIR / FLUID



Basket Strainer · Ductile Iron · Table E							BSC
BSC - 50	50	Table E	10	16 BAR	-20°C	Body: Cast Iron	High Flow Economical
BSC - 65	65		10	16 BAR	-20°C	Screen: SS304	
BSC - 80	80		10	16 BAR	-20°C	FBE Coating	
BSC - 100	100		10	16 BAR	-20°C		
BSC - 125	125		7	16 BAR	-20°C		
BSC - 150	150		7	16 BAR	-20°C		
BSC - 200	200		4	16 BAR	-20°C		
BSC - 250	250		4	16 BAR	-20°C		
BSC - 300	300		4	16 BAR	-20°C		
BSC - 400	400		4	16 BAR	-20°C		
BSC - 500	500		4	16 BAR	-20°C		
BSC - 600	600		4	16 BAR	90°C		

AIR / FLUID / STEAM



Y Strainer • Carbon Steel • ANSI 150 • ANSI 300							YSWF	
YSWF - 50	50	ANSI150	40	1964Kpa @ -29 to 35 deg C	260 deg C @ 1171 Kpa	Body: Cast Steel	ASTM A234-WPB	
YSWF - 65	65					ASTM A105		
YSWF - 80	80					ASTM B16.34		
YSWF - 100	100					design		
YSWF - 125	125					ASME B16.10		
YSWF - 150	150					ASME B16.5 ends		
YSWF - 200	200					API 598 test		
YSWF - 250	250							
YSWF - 300	300					40		
Also available up to 600mm • Optional YSWF3 ANSI 300 50-3000 50-100 Ex Stock, Balance Indent.								

AIR / FLUID / STEAM



Basket Strainer • Carbon Steel • ANSI 150							BSW
BSW - 50	50	ANSI 150 RF	40	1964Kpa @ -29 to 35 deg C	260 deg C @ 1171 Kpa	Body: Carbon Steel	ASTM A234-WPB
BSW - 65	65		40			Screen: SS304 #40	ASTM A105
BSW - 80	80		40			Gasket: Flexible Graphite/ SS304	ASTM B16.34 design
BSW - 100	100		40			Coating: Silver Primer	ASME B16.10
BSW - 125	125		40				ASME B16.5 ends
BSW - 150	150		40				API 598 test
BSW - 200	200		40				
BSW - 250	250		40				
BSW - 300	300		40				
Also available up to 600mm							

**Pressure Reducing Valves
Bellows Sealed Globe Valve**

**Pressure
Reducing**

Model	Port Size	Connection	Description	Pressure	Temp	Features
-------	-----------	------------	-------------	----------	------	----------

Ductile Iron Piston Operated Pressure Reducing Valve • Steam

GP-1010



Series GP

GP-1010-04 GP-1010-05 GP-1010-06 GP-1010-07 GP-1010-08 GP-1010-09	1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	BSPT BSPT	Ductile Iron Pressure Reducing Valve Ductile Iron Pressure Reducing Valve	0.5~9 Bar 0.5~9 Bar	0°C 220°C	- Ductile Iron Body - BSPT Connection - Pilot Operated Piston Type - Max 20:1 Pressure Reduction Ratio
--	--	-------------------	---	-----------------------------	-------------------	--

Ductile Iron Diaphragm Operated Pressure Reducing Valve • Steam

GP-2000



Series GP

GP-2000*-04 GP-2000*-05 GP-2000*-06 GP-2000*-07 GP-2000*-08 GP-2000*-09	1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	BSPT BSPT	Ductile Iron Diaphragm Operated Pressure Reducing Valve Ductile Iron Diaphragm Operated Pressure Reducing Valve * Multiple Pressure Ranges Available A, B, C. A = 0.2-1.5 Bar, B = 1-14 Bar, C = 13-17 Bar	0.2 Bar 17 Bar	0°C 220°C	- Ductile Iron Body - BSPT Connection - Pilot Operated Diaphragm Type - Max 20:1 Pressure Reduction Ratio - Optional Pressure Ranges
--	--	-------------------	--	------------------------	-------------------	--

Ductile Iron Flanged Diaphragm Operated Pressure Reducing Valve • Steam

GP-2000F



Series GP

GP-2000F*-050 GP-2000F*-065 GP-2000F*-080 GP-2000F*-100 GP-2000F*-125 GP-2000F*-150 GP-2000F*-200	50mm 65mm 80mm 100mm 125mm 150mm 200mm	ANSI 150 Flanged 	Ductile Iron Diaphragm Operated Pressure Reducing Valve Ductile Iron Diaphragm Operated Pressure Reducing Valve * Multiple Pressure Ranges Available A, B, C. A = 0.2-1.5 Bar, B = 1-14 Bar, C = 13-17 Bar	0.2 Bar 17 Bar	0°C 220°C	- Ductile Iron Body - BSPT Connection - Pilot Operated Diaphragm Type - Max 20:1 Pressure Reduction Ratio - Optional Pressure Ranges
---	--	-------------------------	--	------------------------	-------------------	--

Alternate Flanges Available

Bronze Pressure Reducing Valve • Steam

GD-30



Series GD

GD-30*-04 GD-30*-05 GD-30*-06	1/2" 3/4" 1"	BSPT BSPT	Bronze Pressure Reducing Valve Bronze Pressure Reducing Valve * Multiple Pressure Ranges Available A, B, C. A = 0.2-1.5 Bar, B = 1-14 Bar, C = 13-17 Bar	0.2 Bar 17 Bar	0°C 210°C	- Bronze Body - Direct Acting Type - BSPT Connection - Max 10:1 Pressure Reduction Ratio - Optional Pressure Ranges
GD-3055*-04 GD-3055*-05 GD-3055*-06	1/2" 3/4" 1"	BSPT BSPT	SS316 Options in stock	0.2 Bar 17 Bar	0°C 210°C	

Bronze Pressure Reducing Valve • Hot & Cold Water

GD-24



Series GD

GD-24-04 GD-24-05 GD-24-06 GD-24-07 GD-24-08 GD-24-09	1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	BSPT BSPT	Bronze Pressure Reducing Valve Bronze Pressure Reducing Valve	0.5 Bar 5 Bar	0°C 080°C	- Bronze Body - Direct Acting Type - BSPT Connection - For 0°C to 80°C Water Applications
--	--	-------------------	---	-----------------------	-------------------	---

Bellow Sealed Globe Valve • Hot & Cold Water • Steam

BSV-2EN



Series BSV-2EN

BSV-2EN-015 BSV-2EN-020 BSV-2EN-025 BSV-2EN-032 BSV-2EN-040 BSV-2EN-050 BSV-2EN-065 BSV-2EN-080 BSV-2EN-100 BSV-2EN-125 BSV-2EN-150	15mm 20mm 25mm 32mm 40mm 50mm 65mm 80mm 100mm 125mm 150mm	Flanged DIN 	Ductile Iron Flanged Bellows Seated Globe Valve Ductile Iron Flanged Bellows Seated Globe Valve	16 Bar 16 Bar	0°C 300°C	- Ductile Iron Body - PN16 Flanged Ends - Stainless Steel Internals - Non Rising Hand Wheel - Zero leakage by two-stage sealing - Extremely low torque and Maintenance free
---	---	-----------------	---	-----------------------	-------------------	---

Steam Traps

Steam Traps

Model	Port Size	Connection	Description	Pressure	Temp	Features
-------	-----------	------------	-------------	----------	------	----------

Inverted Bucket Traps - Ductile Iron / Screwed BSPT • Condensate

TB-20

TB-20-04 TB-20-05 TB-20-06	1/2" 3/4" 1"	BSPT BSPT	Ductile Iron Inverted Bucket Steam Trap Ductile Iron Inverted Bucket Steam Trap * Multiple Pressure Ranges Available A, B, C, D. A = 0.1-3 Bar, B = 2-6 Bar, C = 3-10 Bar, D = 6-16 Bar	0.1 Bar 16 Bar	0°C 220°C	- Ductile Iron Body - Inverted Bucket Type Trap - BSPT Connection - Integral Strainer - Stainless Steel Internal Parts
----------------------------------	--------------------	-------------------	---	------------------------	-------------------	--

Float SteamTraps - Ductile Iron / Screwed BSPT • Condensate

TSF-8-21

TSF-8-21-04 TSF-8-21-05	1/2" 3/4"	BSPT BSPT	Ductile Iron Float Steam Trap Ductile Iron Float Steam Trap	0.1~21 Bar 0.1~21 Bar	0°C to 220°C	- Ductile Iron Body - Float Type Trap - BSPT Connection - Various Installation Angles Achievable - Incorporated Thermostatic Air Vent
----------------------------	--------------	-------------------	---	-------------------------------	----------------------	---

Float SteamTraps - Ductile Iron / Screwed BSPT • Condensate

TSF-11-21

TSF-11-21-06 TSF-11-21-07 TSF-11-21-08 TSF-11-21-09	1" 1-1/4" 1-1/2" 2"	BSPT BSPT	Ductile Iron Float Steam Trap Ductile Iron Float Steam Trap	0.1~21 Bar 0.1~21 Bar	0°C 220°C	- Ductile Iron Body - Float Type Trap - BSPT Connection - Various Installation Angles Achievable - Incorporated Thermostatic Air Vent
--	------------------------------	-------------------	---	-------------------------------	-------------------	---

Thermodynamic Steam Trap - Ductile Iron / Screwed BSPT • Condensate

TD-10NA

TD-10NA-04 TD-10NA-05 TD-10NA-06	1/2" 3/4" 1"	BSPT BSPT	Ductile Iron Thermodynamic Steam Trap Ductile Iron Thermodynamic Steam Trap	0.35~20 Bar 0.35~20 Bar	0°C 220°C	- Ductile Iron Body - Thermodynamic Disk Type Trap - BSPT Connection - Bi-Metal Ring & Integral Strainer
--	--------------------	-------------------	---	---------------------------------	-------------------	---

Thermodynamic Steam Trap - Stainless Steel / Screwed BSPT • Condensate

TSD

TSD-42-04 TSD-42-05 TSD-42-06	1/2" 3/4" 1"	BSPT BSPT	Stainless Steel Thermodynamic Steam Trap Stainless Steel Thermodynamic Steam Trap	0.35~42 Bar 0.35~42 Bar	0°C 425°C	- SCS2A Body - Thermodynamic Disk Type Trap - BSPT Connection - Bi-Metal Ring & Integral Strainer
-------------------------------------	--------------------	-------------------	---	---------------------------------	-------------------	--

- Additional Products:**
- TSF-12 High Capacity. 1 1/2", 2" BSPT. Multiple Pressure Ranges. 200°C. Horizontal Flow Installation.
 - TSF-13 Extra High Capacity. 1 1/2", 2" BSPT. ANSI 150, ANSI 300, PN16, PN25. 220°C. Multiple Pressure Ranges Available. Horizontal Flow Installation.
 - TFA-2000 Pump Assist Trap 1"
 - PF-2000 Pressure Powered Pump 1"
 - PF-7000 Pressure Powered Pump 1" - 1 1/2"x1 1/2" - 2"x2" - 3"x2"

Ancillary

Model	Port Size	Connection	Description	Pressure	Temp	Features
-------	-----------	------------	-------------	----------	------	----------

Bronze Temperature Regulator-Screwed BSPT • Hot Water & Steam

OB-30



Series OB

OB-30-04 OB-30-05 OB-30-06	1/2" 3/4" BSPT 1" BSPT	BSPT BSPT	Bronze Temperature Regulator Bronze Temperature Regulator	10 Bar Steam 17 Bar Water	Max. Temp. 185°C	- Bronze Body - External Pressurised Bellows - BSPT Connection - Direct Acting
----------------------------------	------------------------------	-------------------	---	--------------------------------------	------------------------	---

Temp Sensors-2mtr Capillary Length • Hot Water & Steam

OB-30



Series OB

OB-30-Temp 1 OB-30-Temp 2 OB-30-Temp 3 OB-30-Temp 4 OB-30-Temp 5			Sensor for OB-30 Sensor for OB-30	Max. Bulb Pressure 10 Bar ↓	0~35°C 25~70°C 40~100°C 60~130°C 150°C	- Copper (Nickel Plated Chrome) - 2m Capillary Length - Max Bulb Pressure of 10 Bar
OB-30-TW			Thermowell for OB-30 Temperature Probe			

Drain Separator Ductile Iron / Screwed BSPT • Condensate

DS-1



Series DS

DS-1-06 DS-1-07 DS-1-08 DS-1-09	1" 1-1/4" 1-1/2" 2"	BSPT BSPT	Ductile Iron Drain Separator Ductile Iron Drain Separator	20 Bar 20 Bar	0°C 220°C	- Ductile Iron - BSPT Connection - 0°C to 220°C Temperature Range - 0 to 20 Bar (Steam), 0 to 10 Bar (Air)
--	------------------------------	-------------------	---	-----------------------	-------------------	---

Drain Separator Ductile Iron / Flange • Condensate

DS-2



Series DS

DS-2-50 DS-2-65 DS-2-80 DS-2-100	50mm 65mm 80mm 100mm	DIN PN16 Flange ↓	Ductile Iron Drain Separator Ductile Iron Drain Separator	20 Bar 20 Bar	0°C 220°C	- Ductile Iron - Flange Connection - 0°C to 220°C Temperature Range - 0 to 20 Bar (Steam), 0 to 10 Bar (Air)
---	-------------------------------	------------------------------	---	-----------------------	-------------------	---

Sight Glass Flap type-Ductile Iron-Screwed BSPT • Condensate

SF-1S



Series SF

SF-1S-04 SF-1S-05 SF-1S-06 SF-1S-07 SF-1S-08 SF-1S-09	1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	BSPT BSPT	Ductile Iron Flap Type Sight Glass Ductile Iron Flap Type Sight Glass	10 Bar 10 Bar	0°C 150°C	- Ductile Iron - Flap Type Sight Glass - 0 to 10 Bar Pressure Range - 0°C to 150°C Temperature Range - Maximum Thermo/Shock 100°C
--	--	-------------------	---	-----------------------	-------------------	---

Ductile Iron Air Vent

TA-3



Series TA

TA-3-04 TA-3-05 TA-3-06	1/2" 3/4" 1"	BSPT BSPT	Ductile Iron Air Vent Valve Ductile Iron Air Vent Valve	0.1~10 Bar 0.1~10 Bar	0°C 90°C	- Ductile Iron - Large Capacity & Compact Design - Tight Seal & Easy Maintenance
-------------------------------	--------------------	-------------------	---	-------------------------------	------------------	--

Steam Trap Checker

STC-1



Series STC

STC-1			Digital Steam Trap Checker	- Speedy Diagnosis with multiple operating modes and functions including Automatic Diagnosis - 0.5 to 80 Bar Working Pressure and 0 to 300°C Surface Temperature Range - Large Backlit LCD Screen for easy reading along with LED for diagnosis results		
-------	--	--	----------------------------	---	--	--

Pressure Relief

Model	Inlet Connection BSP	Outlet Connection BSP	Description	Pressure	Temp	Features
-------	----------------------	-----------------------	-------------	----------	------	----------

Bronze Pressure Relief • Closed Cap • SS316 Trim • *

BPRC

BPRC- 04 BPRC- 05 BPRC- 06 BPRC- 07 BPRC- 08 BPRC- 09	1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	Bronze Body / SS316 Internals RTFE Seat * See below for pressure range options All valves preset at 10 Bar Not for safety relief.	1.0 Bar 20 Bar	-40°C 180°C	Closed Cap. Adjustable. Oil, Air, Water • NOT for Steam
--	--	--	---	---------------------------	------------------------	--

Bronze Pressure Relief • Lever • SS316 Trim • *

BPRL

BPRL- 04 BPRL- 05 BPRL- 06 BPRL- 07 BPRL- 08 BPRL- 09	1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	Bronze Body / SS316 Internals RTFE Seat * See below for pressure range options All valves preset at 10 Bar Not for safety relief.	1.0 Bar 20 Bar	-40°C 180°C	Open Cap. Lever Override. Adjustable. Oil, Air, Water • NOT for Steam
--	--	--	---	---------------------------	------------------------	---

* Setting Ranges (Spring Sets):
for above Series BPRC & BPRL

1/2" BSP	1-3 Bar, 3-5 Bar, 5-15 Bar (std), 7-23 Bar
3/4" BSP	2-5 Bar, 5-16 Bar (std), 7-22 Bar
1" BSP	2-5 Bar, 4-15 Bar (std), 14-24 Bar
1 1/4" BSP	1-3 Bar, 3-13 Bar (std), 12-20 Bar
1 1/2" BSP	1-4 Bar, 3-11 Bar (std), 9-22 Bar
2" BSP	1-8 Bar, 4-12 Bar (std), 12-23 Bar

Stainless Steel Pressure Relief • Closed Cap • SS316 Trim • *

FGX

FGX- 04 FGX- 05 FGX- 06 FGX- 07 FGX- 08 FGX- 09	1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	1" 1" 1" 2" 2" 2"	SS316 Body / SS316 Trim RTFE Seat Setting range: 1-5 Bar, 4-12 Bar (std), 12-20 Bar All valves preset at 10 Bar Not for safety relief.	1.0 Bar 20 Bar	-40°C 180°C	Closed Cap. Adjustable. Oil, Air, Water, Steam • NOT for Steam
--	--	----------------------------------	---	---------------------------	------------------------	--

Stainless Steel Pressure Relief • Lever • SS316 Trim • *

FGXL

FGXL- 04 FGXL- 05 FGXL- 06 FGXL- 07 FGXL- 08 FGXL- 09	1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	1" 1" 1" 2" 2" 2"	SS316 Body / SS316 Trim RTFE Seat Setting range: 1-5 Bar, 4-12 Bar (std), 12-20 Bar All valves preset at 10 Bar Not for safety relief.	1.0 Bar 20 Bar	-40°C 180°C	Open Cap. Lever Override. Adjustable. Oil, Air, Water • NOT for Steam
--	--	----------------------------------	---	---------------------------	------------------------	---

Vacuum Breaker Breather

Model	Port Size BSP	Description	Pressure	Temp	Features
-------	---------------	-------------	----------	------	----------

Stainless Steel Vacuum Breaker • SS316 • *

VBS

VBS - 04	1/2"	SS316 Body. FKM Seat / Seal Install vertically with connection down.	0.1-16 Bar	-20°C to 180°C	Permits air to enter the system with the pressure drop avoiding a vacuum internally. • NOT for Steam
----------	------	---	------------	----------------	---

Stainless Steel Air Vent • SS316 • *

AVS

AVS - 04 AVS - 05 AVS - 06	1/2" 3/4" 1"	SS316 Body. FKM Seat / Seal	0.1 16 Bar	-20°C 180°C	Float valve allows trapped air to vent. • NOT for Steam
----------------------------------	--------------------	-----------------------------	--------------------	---------------------	--

* Relief Valves not certified for installation on Steam Boilers or Pressure Vessels.



Steam Boiler

Model	Sizes	Description	Features
-------	-------	-------------	----------

Water Flange Level Gauges for Boilers

BGM



BGM

BGM - Level Gauge Flanged	20mm Flanged. Table H or Undrilled Other Flange Tables as requested	Glass Special Lengths Ex Stock.	AS1271-1997 Section 5. Left or Right Hand in one assembly. Self Closing Safety Ball and Isolating Valves Standard. Gauge Guards available AB11 Gauge Cones
---------------------------	--	---------------------------------	---

Water Level Gauges • High Pressure


LEVCO, REFLEV



LEVCO
REFLEV

Level Gauges	25mm ANSI 150, ANSI 300 Table H & Undrilled 16mm End Tube	Gauge Mounts Reflex and Transparent Level Gauges. Glass Sight Gauges. Mica Protection	Left Hand or Right Hand
--------------	---	--	-------------------------


Jointing & Gasket Materials



GASKETS

Gasket Sheetting Cut Gaskets	Various Grades & Flange Sizes.	Expanded PTFE. Tanged Graphite. Boiler Door Gaskets.	Large Range Available. Gaskets cut to size
---------------------------------	-----------------------------------	--	---

Graphite Gland Packing • PTFE & Graphite



PTFE Packing Graphite Packing	Pure PTFE Filament with PTFE Dispersion. PTFE Yarns with Encapsulated Graphite. Packing Removal Tools. PTFE Joint Sealant	8m Rolls 1m Handy Packs 3-25mm Square
----------------------------------	--	---

Lagging Tapes & Rope

TAPE



TAPE

Fibreglass Woven Tape.	Various Sizes	25mm – 100mm Width	30m Lengths
Fibreglass Ladder Tape	Various Sizes	25mm – 75mm Width	30m Lengths
Fibreglass Lagging Rope	Various Sizes	12mm – 50mm	Various Lengths

- Gauge Mount Spares - Glass Tube, Cones, Spindles.
- Gauge Guards

Nitto Type Couplers - Stainless Steel SS304 - 15Bar Working Pressure

PM Male Adaptor (SS304)

	1/4 BSPM	S - 20PM
	3/8 BSPM	S - 30PM
	1/2 BSPM	S - 40PM

PF Female Adaptor (SS304)

	1/4 BSPF	S - 20PF
	3/8 BSPF	S - 30PF
	1/2 BSPF	S - 40PF

PH Hose Barb (SS304)

	8mm I.D. Hose	S - 20PH
	10mm I.D. Hose	S - 30PH
	12mm I.D. Hose	S - 40PH

SM Male Coupler (SS304)

	1/4 BSPM	S - 20SM
	3/8 BSPM	S - 30SM
	1/2 BSPM	S - 40SM

SF Female Coupler (SS304)

	1/4 BSPF	S - 20SF
	3/8 BSPF	S - 30SF
	1/2 BSPF	S - 40SF

SH Hose Barb Coupler (SS304)

	8mm I.D. Hose	S - 20SH
	10mm I.D. Hose	S - 30SH
	12mm I.D. Hose	S - 40SH

Switch

PRESSURE SWITCH



Model	Description	Connection	Function
IP65			
PSM2R14AP PSM10R14APS PSM50R14S PSM100R14S	Brass Brass Brass Brass	0.2-2 Bar 1-10 Bar 10-50 Bar 10-100 Bar	Max 300 Bar Over Pressure
PSP150R14S PSP300R14S	SS316 SS316	30-150 Bar 50-300 Bar	
VSM1R14 VSM2R14	Brass Brass	100-500 mBar (VAC) 500-900 mBar (VAC)	
PSMPSP	DIN Plug	4 PIN Connector Plug	ISO Square Plug
			1/4" BSP (Parallel) with O'Ring Seal
			S.P.D.T. (NC or NO) 6Amp (res) 2 Amp (Inductive) 240V AC Max IP65 30% Full Scale Hysteresis Membrane - NBR - Standard Viton Silicone EPDM Stainless Steel

Plug

CONNECTOR PLUG



Square 28x28mm DIN 43650A • IP65

Model	Description	Gromet (ID mm)	Cable Gland	Voltage Range	Pin Details
DPSL - 6 - H - PG11 DPSL - 6 - L - PG11	LED Illuminated LED Illuminated	6 6	PG11 PG11	70 ~ 250v AC/DC 10AMP 10 ~ 50v AC/DC 10AMP	2 Pin + Earth 18mm Pin Spacing
DPSM - 6 - H - PG11 DPSM - 6 - L - PG11	Surge Suppresion Surge Suppresion	6 6	PG11 PG11	61 ~ 240v AC/DC 10AMP 0 ~ 60v AC/DC 10AMP	
DPSR - 6 - H - PG11 DPSR - 6 - L - PG11	Rectifier Plug Rectifier Plug	6 6	PG11 PG11	110/240v AC ~ 110/240v DC 1.5AMP 12/24v AC ~ 12/24v DC 1.5AMP	
DPSB - 6 - 2E - PG11 DPSB - 6 - 3E - PG11	Plain Black Plain Black	6 6	PG11 PG11	0 ~ 415v AC/DC 10AMP 0 ~ 415v AC/DC 10AMP	2 Pin + Earth 3 Pin + Earth

POWER SAVER



Square 28x28mm DIN 43650A • IP65

Power Saving up to 70% – Lower Coil Temperature					
DPPS - 6 - 1 - PG11 DPPS - 6 - 8 - PG11	Power Saving - Lower Temp Power Saving - Lower Temp	6 6	PG11 PG11	240v AC 0.4 AMP 24v DC 1.5AMP	2 Pin + Earth 2 Pin + Earth
Great for applications where a coil is energised for long periods of time and temperature / enclosure becomes an issue.					

CONNECTOR PLUG



Rectangle 20x28mm DIN 43650B • IP65

Model	Description	Gromet (ID mm)	Cable Gland	Voltage Range	Pin Details
DPRL - 6 - H - PG9 DPRL - 6 - L - PG9	LED Illuminated LED Illuminated	6 6	PG9 PG9	70 ~ 250v AC/DC 10AMP 10 ~ 50v AC/DC 10AMP	2 Pin + Earth 2 Pin + Earth 9.4mm Pin Spacing
DPRB - 6 - PG9	Plain Black	6	PG9	10 ~ 250v AC/DC 10AMP	2 Pin + Earth 11mm Pin Spacing

CONNECTOR PLUG



Mini Plug 15x15mm DIN 43650C • IP65

Model	Description	Gromet (ID mm)	Cable Gland	Voltage Range	Pin Details
DPML - 4 - H - PG7 DPML - 4 - L - PG7	LED Illuminated LED Illuminated	4 4	PG7 PG7	70 ~ 250v AC/DC 6AMP 10 ~ 50v AC/DC 6AMP	2 Pin + Earth 9.4mm Pin Spacing

CONNECTOR PLUG



A-B Adapter DIN 43650A to DIN 43650B • IP65

Model	Description	Pin Details
A-B ADAPT	Converts Rectangular DIN 43650B to Square DIN 43650A Used in Conjunction with Solenoid Valve Timers (refers to Series EM/TEC Data Sheet & page 45) 10AMP	2 Pin + Earth

Timer

TIMERS



EMD

Digital. Programmable 0.1 Sec - 99 Hours • IP65

EMD

Model	Description	Connection	CYCLE TIMER	
			ON	OFF
			0.1 Sec - 99 Hrs	0.1 Sec - 99 Hrs
EMD - 12A	DIGITAL TIME 110-220vAC	Square Plug IP65	Single Shot ON 0.1 Sec - 99 Hrs	
EMD - 12B	DIGITAL TIME 10-48V AC/DC	Square Plug IP65	Single Shot OFF 0.1 Sec - 99 Hrs	
			Max Current 1 Amp	

TIMERS



Series TEC - EM

Analog. External Knob Adjustment • IP65

TEC

Model	Description	Connection	ON	OFF
			0.5 - 10 Sec	0.5 - 45 min
Blow Down Cycle Timer TEC - 22A	Cycle Timer 24 - 240V AC/DC	Square Plug IP65	Max Current 1 Amp	

Timer Drain

TIMER / DRAIN VALVE



Series CRD

Air Air -
Condensate
Removal

CRD - c/w Integral Y Strainer and Ball Valve • IP65

CRD

Model	Pressure Range	Description	Connection	Function
CRD - 4 - 3.5 - *VY	16 BAR	Value & Timer combination for condensate removal from air systems. Integral Isolating Ball Valve and Y Strainer	1/2" BSP Voltages:- 240vAC (Standard) 24vAC 110vAC 24vDC IP65	Body: Brass Seats: Viton Operator: Brass & Stainless Steel Air (Compressed Air Condensate) Manual Test Cycle. LED Indicator. Direct Acting For 12vDC use EMD-12A
Optional Flex & 3 pin plug 240VDC. 1.5m		0.5 - 10 SECS ON 1 - 45 MINS OFF ADJUSTABLE		
Contact Factory for 12VDC Supply Option				

TIMER / DRAIN VALVE



Series CRD

CRD - c/w Separate Y Strainer and Ball Valve • IP65

CRD

Model	Pressure Range	Description	Connection	Function
CRD - 4 - 4.5 - * VY CRD - 4 - 2.8 - * VY CRD - 4 - 1.9 - * V	16 BAR 40 BAR 80 BAR	Value & Timer combination for condensate removal from air systems. Seperate Isolation Ball Valve and Strainer	1/2" BSP 1/2" BSP 1/2" BSP Voltages:- 240vAC (Standard) 24vAC 110vAC 24vDC IP65	Body: Brass Seats: Viton Operator: Brass & Stainless Steel Air (Compressed Air Condensate) Manual Test Cycle. LED Indicator. Direct Acting For 12vDC use EMD-12A
Optional Flex & 3 pin plug 240VDC. 1.5m		0.5 - 10 SECS ON 1 - 45 MINS OFF ADJUSTABLE		
Contact Factory for 12VDC Supply Option				

Gauges

DIAL GAUGE

Series GAU



63mm

DIAL GAUGE

Series GAU



100mm

DIAL GAUGE

Series GAU



100mm

DIAL GAUGE

Series GAU












150mm

DIAL GAUGE



Bottom Entry	Rear Entry	Features
63mm SS304 Case 1/4" BSPT • Brass Internals • Liquid Filled		
GAU63		SS304 Case Brass Internals Liquid Filled Dual Scale Kpa/PSI Brass Connection 3/8 BSP C/W Panel Mount Bracket (Rear Entry)
Bottom Entry (Kpa) GAU63B ~ 100V (-100 Kpa / 30"Hg) GAU63B ~ 100 (100 Kpa / 15 psi) GAU63B ~ 100C16 (-100 Kpa to 1600 Kpa) GAU63B ~ 200 (200 Kpa / 30 psi) GAU63B ~ 400 (400 Kpa / 60 psi) GAU63B ~ 600 (600 Kpa / 90 psi) GAU63B ~ 800 (800 Kpa / 110 psi) GAU63B ~ 1000 (1000 Kpa / 140 psi) GAU63B ~ 1600 (1600 Kpa / 230 psi) GAU63B ~ 2500 (2500 Kpa / 360 psi) GAU63B ~ 4000 (4000 Kpa / 580 psi) GAU63B ~ 250B (250 BAR / 3600 psi) Hydraulic Connection 1/4" BSPP c/w Snubber GAU63B ~ 400B (400 BAR / 5800 psi) Hydraulic Connection 1/4" BSPP c/w Snubber	Rear Entry (Kpa) c/w Panel Mounting Clamp GAU63R ~ 100V (-100 Kpa / 30"Hg) GAU63R ~ 100 (100 Kpa / 15 psi) GAU63R ~ 100C16 (-100 Kpa to 1600 Kpa) GAU63R ~ 200 (200 Kpa / 30 psi) GAU63R ~ 400 (400 Kpa / 60 psi) GAU63R ~ 600 (600 Kpa / 90 psi) GAU63R ~ 800 (800 Kpa / 110 psi) GAU63R ~ 1000 (1000 Kpa / 140 psi) GAU63R ~ 1600 (1600 Kpa / 230 psi) GAU63R ~ 2500 (2500 Kpa / 360 psi) GAU63R ~ 4000 (4000 Kpa / 580 psi) GAU63R ~ 250B (250 BAR / 3600 psi) Hydraulic Connection 1/4" BSPP c/w Snubber GAU63R ~ 400B (400 BAR / 5800 psi) Hydraulic Connection 1/4" BSPP c/w Snubber	
Options: Gauge Guard • Heat Shield • Gauge Cock • Higher Pressure Gauges Available		Accuracy +- 1.6% full scale Working Range:- Steady 3/4 full scale Temperature Ambient/Media Fluctuating 2/3 full scale -20deg.C + 60deg.C Short time full Scale
100mm SS304 Case 3/8" BSPT • Brass Internals • Liquid Filled		
GAU100		SS304 Case Brass Internals Liquid Filled Dual Scale Kpa/PSI Brass Connection 3/8 BSP C/W Panel Mount Bracket (Rear Entry)
Bottom Entry (Kpa) GAU100B - 100V (-100 Kpa/30"Hg) GAU100B - 100C (-100 Kpa to 1600 Kpa) GAU100B ~ 200 (200 Kpa / 30 psi) GAU100B ~ 400 (400 Kpa / 60 psi) GAU100B ~ 600 (600 Kpa / 90 psi) GAU100B ~ 800 (800 Kpa / 110 psi) GAU100B ~ 1000 (1000 Kpa / 140 psi) GAU100B ~ 1600 (1600 Kpa / 230 psi) GAU100B ~ 2500 (2500 Kpa / 360 psi) GAU100B ~ 4000 (4000 Kpa / 580 psi)		
Options: Gauge Guard • Heat Shield • Gauge Cock • Higher Pressure Gauges Available		Accuracy +- 1.6% full scale Working Range:- Steady 3/4 full scale Temperature Ambient/Media Fluctuating 2/3 full scale -20deg.C + 60deg.C Short time full Scale
100mm SS316 Case 3/8" BSPT • Stainless Steel Internals • Liquid Filled		
GAU100		SS316 Case Stainless Steel Internals SS316 Connection 3/8 BSP Dual Scale Kpa/PSI Liquid Filled Optional: Mounting Flange Face
Bottom Entry (Kpa) GAU100BS ~ 1000 (1000 Kpa / 140 psi) GAU100BS ~ 1600 (1600 Kpa / 230 psi) GAU100BS ~ 2500 (2500 Kpa / 360 psi)	Rear Entry (Kpa) c/w Panel Mounting Clamp GAU100RS ~ 1000 (1000 Kpa / 140 psi) GAU100RS ~ 1600 (1600 Kpa / 230 psi)	
Other pressure ranges available Options: Gauge Guard • Heat Shield • Gauge Cock		Accuracy +- 1.0% full scale Working Range:- Steady 3/4 full scale Temperature Ambient/Media Fluctuating 2/3 full scale -20deg.C + 60deg.C Short time full Scale
150mm SS316 Case 1/2" NPT • Stainless Steel Internals • Liquid Filled		
GAU150		SS316 Case Stainless Steel Internals SS316 Connection 1/2 NPT Dual Scale Kpa/PSI Liquid Filled • C/W Mounting Flange • Bottom Entry
GAU150BS ~ 1000 (1000 Kpa / 140 psi) Bottom Entry c/w Back Mounting Flange GAU150BS ~ 2500 (2500 Kpa / 360 psi) Bottom Entry c/w Back Mounting Flange		
Other pressure ranges available Options: Gauge Guard • Heat Shield • Gauge Cock		Accuracy +- 1.0% full scale Working Range:- Steady 3/4 full scale Temperature Ambient/Media Fluctuating 2/3 full scale -20deg.C + 60deg.C Short time full Scale
40mm SS316 Case 1/8" BSP • Brass Internals		
GAU40R		
GAU40R ~ 1000 (1000 Kpa / 140 psi)		




Other Instrumentation Products (Indent Only) Include: • Digital Pressure Gauges • Digital Temperature Gauges • Digital Pressure Transmitter / Transducer • Flow Meters • Gauge Diaphragm Seals • Gauge Scrubbers • PGT Pigtail Siphon.

Air Service	Symbol	Model	Port Size BSP	Pressure Range	Function	Model Website
FILTER REGULATOR LUBRICATORS (FRL) (5 Micron Filter)						
		FRL-02 FRL-03 FRL-04 FRL-05 FRL-06	1/4 3/8 1/2 3/4 1	0.5 ~ 8 Bar 0.5 ~ 8 Bar 0.5 ~ 8 Bar 0.5 ~ 8 Bar 0.5 ~ 8 Bar	FRL with auto drain, gauge & mtg bracket FRL with auto drain, gauge & mtg bracket FRL with auto drain, gauge & mtg bracket FRL with auto drain, gauge & mtg bracket FRL with auto drain, gauge & mtg bracket	FRL
REGULATORS						
		REG-02 REG-03 REG-04 REG-05 REG-06 REG-08 REG-09	1/4 3/8 1/2 3/4 1 1 1/2 2	0.5 ~ 8 BAR 0.5 ~ 8 BAR 0.5 ~ 8 BAR 0.5 ~ 8 BAR 0.5 ~ 8 BAR 0.5 ~ 16 BAR 0.5 ~ 16 BAR	Regulator with mounting bracket & gauge Regulator with mounting bracket & gauge Regulator with mounting bracket & gauge Regulator with mounting bracket & gauge Regulator with mounting bracket & gauge Regulator with gauge Regulator with gauge	REG
		HPR-02 HPR-03 HPR-04 HPR-05 HPR-06	1/4 3/8 1/2 3/4 1	5 ~ 35 BAR 5 ~ 35 BAR 5 ~ 35 BAR 5 ~ 35 BAR 5 ~ 35 BAR	High Pressure Regulator High Pressure Regulator High Pressure Regulator High Pressure Regulator High Pressure Regulator	HPR
FILTERS						
		FIL-02 FIL-03 FIL-04 FIL-05 FIL-06 FIL-08 FIL-09	1/4 3/8 1/2 3/4 1 1 1/2 2	0 ~ 8 BAR 0 ~ 8 BAR 0 ~ 8 BAR 0 ~ 8 BAR 0 ~ 8 BAR 0 ~ 8 BAR 0 ~ 8 BAR	Filter (5 micron) with auto drain & mtg bracket Filter (5 micron) with auto drain & mtg bracket Filter (5 micron) with auto drain & mtg bracket Filter (5 micron) with auto drain & mtg bracket Filter (5 micron) with auto drain & mtg bracket Filter (50 micron) Filter (50 micron)	FIL
		HPF-02 HPF-04 HPF-05 HPF-06	1/4 1/2 3/4 1	0 ~ 36 BAR 0 ~ 36 BAR 0 ~ 35 BAR 0 ~ 35 BAR	High Pressure Filter High Pressure Filter High Pressure Filter High Pressure Filter	HPF
FILTER REGULATORS (5 Micron filter)						
		FRE-02 FRE-03 FRE-04 FRE-05 FRE-06	1/4 3/8 1/2 3/4 1	0.5 ~ 8 BAR 0.5 ~ 8 BAR 0.5 ~ 8 BAR 0.5 ~ 8 BAR 0.5 ~ 8 BAR	Filter Reg with auto drain, mtg bracket & gauge Filter Reg with auto drain, mtg bracket & gauge Filter Reg with auto drain, mtg bracket & gauge Filter Reg with auto drain, mtg bracket & gauge Filter Reg with auto drain, mtg bracket & gauge	FRE
LUBRICATOR						
		LUB-02 LUB-03 LUB-04 LUB-05 LUB-06 LUB-08 LUB-09	1/4 3/8 1/2 3/4 1 1 1/2 2	0.5 ~ 8 BAR 0.5 ~ 8 BAR 0.5 ~ 8 BAR 0.5 ~ 8 BAR 0.5 ~ 8 BAR 0 ~ 8 BAR 0 ~ 8 BAR	Lubricator Lubricator Lubricator Lubricator Lubricator Lubricator Lubricator	LUB
AUTO DRAIN						
		AUD-04	1/2	1.5 ~ 8 BAR	Auto Drain - Float Type	AUD
		ADV-04	1/2	1.5 ~ 16 BAR	Auto Drain - Ball Type - Heavy Duty	ADV





FOR FULL RANGE VISIT OUR WEBSITE WWW.VALVESONLINE.COM.AU

Air Pilot	Symbol	Model	Port Size BSP	Pressure Range	Function	Model Website
-----------	--------	-------	---------------	----------------	----------	---------------

5/2 - 5 PORTS 2 POSITIONS

		APS52-01	1/8	1.5 ~ 8 BAR	5/2 Pilot Spring	APS52
		APP52-01	1/8	1.5 ~ 8 BAR	5/2 Pilot Pilot	APP52
		APS52-02	1/4	1.5 ~ 8 BAR	5/2 Pilot Spring	APS52
		APP52-02	1/4	1.5 ~ 8 BAR	5/2 Pilot Pilot	APP52
		APS52-03	3/8	1.5 ~ 8 BAR	5/2 Pilot Spring	APS52
		APP52-03	3/8	1.5 ~ 8 BAR	5/2 Pilot Pilot	APP52
		APS52-04	1/2	1.5 ~ 8 BAR	5/2 Pilot Spring	APS52
		APP52-04	1/2	1.5 ~ 8 BAR	5/2 Pilot Pilot	APP52



5/3 - 5 PORTS 3 POSITIONS (closed centre)

		APP53-01	1/8	3 ~ 8 BAR	5/3 Pilot Pilot Closed Centre	APP53
		APP53-02	1/4	3 ~ 8 BAR	5/3 Pilot Pilot Closed Centre	APP53
		APP53-03	3/8	3 ~ 8 BAR	5/3 Pilot Pilot Closed Centre	APP53
		APP53-04	1/2	3 ~ 8 BAR	5/3 Pilot Pilot Closed Centre	APP53






FOR FULL RANGE VISIT OUR WEBSITE WWW.VALVESONLINE.COM.AU

Air Manual	Symbol	Model	Port Size BSP	Model Website	Function	Model Website
------------	--------	-------	---------------	---------------	----------	---------------






3/2 - 3 PORTS 2 POSTIONS 1/8" BSP

		TOG32-M5	M5	0 ~ 8 Bar	3/2 way Brass Toggle	TOG32
		TOG32-01	1/8	0 ~ 8 Bar	3/2 way Toggle	TOG32
		PLU32-01	1/8	0 ~ 8 Bar	3/2 way Plunger Spring Return	PLU32
		RLS32-01	1/8	0 ~ 8 Bar	3/2 way Roller Lever Spring Return	RLS32
		FBS32-01-*	1/8	0 ~ 8 Bar	3/2 way Flush Button Spring Return	FBS32
		RBS32-01-*	1/8	0 ~ 8 Bar	3/2 way Raised Button Spring Return	RBS32
		PBS32-01-*	1/8	0 ~ 8 Bar	3/2 way Palm Button Spring Return	PBS32
		PBL32-01	1/8	0 ~ 8 Bar	3/2 way Palm Button Latching Emergency Stop Valve	PBL32
		ROS32-01-*	1/8	0 ~ 8 Bar	3/2 way Rotary Switch	ROS32
		ROL32-01	1/8	0 ~ 8 Bar	3/2 way Rotary Lever	ROL32








3/2 - 3 PORTS 2 POSTIONS 1/4" BSP

		PLU32-02	1/4	0 ~ 8 Bar	3/2 way Plunger Spring Return	PLU32
		RLS32-02	1/4	0 ~ 8 Bar	3/2 way Roller Lever Spring Return	RLS32
		FBS32-02-*	1/4	0 ~ 8 Bar	3/2 way Flush Button Spring Return	FBS32
		RBS32-02-*	1/4	0 ~ 8 Bar	3/2 way Raised Button Spring Return	RBS32
		PBS32-02-*	1/4	0 ~ 8 Bar	3/2 way Palm Button Spring Return	PBS32
		PBL32-02	1/4	0 ~ 8 Bar	3/2 way Palm Button Latching Emergency Stop Valve	PBL32
		ROS32-02-*	1/4	0 ~ 8 Bar	3/2 way Rotary Switch	ROS32
		ROL32-02	1/4	0 ~ 8 Bar	3/2 way Rotary Lever	ROL32

FOR FULL RANGE VISIT OUR WEBSITE WWW.VALVESONLINE.COM.AU

Air Manual	Symbol	Model	Port Size BSP	Pressure Range	Function	Model Website
5/2 - 5 PORTS 2 POSITIONS 1/4", 3/8", 1/2" BSP						
		TOG52-M5	M5	0 ~ 8 Bar	5/2 Toggle	TOG52
		TOG52-01	1/8	0 ~ 8 Bar	5/2 Toggle	TOG52
		PUP52-01	1/8	0 ~ 8 Bar	5/2 Push Pull	PUP52
		PLU52-02	1/4	0 ~ 8 Bar	5/2 way Plunger Spring Return	PLU52
		RLS52-02	1/4	0 ~ 8 Bar	5/2 way Roller Lever Spring Return	RLS52
		FBS52-02-*	1/4	0 ~ 8 Bar	5/2 way Flush Button Spring Return	FBS52
		RBS52-02-*	1/4	0 ~ 8 Bar	5/2 way Raised Button Spring Return	RBS52
		PBS52-02-*	1/4	0 ~ 8 Bar	5/2 way Palm Button Spring Return	PBS52
		PBL52-02	1/4	0 ~ 8 Bar	5/2 way Palm Button Latching Emergency Stop Valve	PLB52
		ROS52-02-*	1/4	0 ~ 8 Bar	5/2 way Rotary Switch	ROS52
		ROL52-02	1/4	0 ~ 8 Bar	5/2 way Rotary Lever	ROL52
		LEL52-02 LEL52-03 LEL52-04	1/4 3/8 1/2	0 ~ 8 Bar 0 ~ 8 Bar 0 ~ 8 Bar	5/2 way Lever Lever	LEL52
		LEL53-02 LEL53-03 LEL53-04	1/4 3/8 1/2	0 ~ 8 Bar 0 ~ 8 Bar 0 ~ 8 Bar	5/3 way Lever Lever - Closed Centre	LEL53
		LES52-02	1/4	0 ~ 8 Bar	5/2 way Lever Spring	LES52
		PUP52-02	1/4	0 ~ 8 Bar	5/2 Push Pull	PUP52
		FSG52-02	1/4	0 ~ 8 Bar	5/2 way Foot Spring with Guard	FSG52
4 WAY 3 POSITION 1/4, 3/8, 1/2" BSP						
		ROT43-02 ROT43-03 ROT43-04	1/4 3/8 1/2	0 ~ 8 Bar 0 ~ 8 Bar 0 ~ 8 Bar	4 way 3 position ceramic seat Rotary Lever	ROT43

FOR FULL RANGE VISIT OUR WEBSITE WWW.VALVESONLINE.COM.AU

Ancillary	Symbol	Model	Port Size BSP	Pressure Range	Function	Model Website
CHECK VALVE 1/8 – 1” BSP						
		ACV-01	1/8"	0.5 ~ 12 Bar	In-Line Air Check Valve	ACV
		ACV-02	1/4"	0.5 ~ 12 Bar		
		ACV-03	3/8"	0.5 ~ 12 Bar		
		ACV-04	1/2"	0.5 ~ 12 Bar		
		ACV-05	3/4"	0.5 ~ 12 Bar		
		ACV-06	1"	0.5 ~ 12 Bar		
PILOT CHECK VALVE 1/8” BSP						
		APC-01	1/8"	0.5 ~ 8 Bar	In-Line Air Check Valve – Pilot Operated	APC
SHUTTLE VALVE 1/8 – 1” BSP						
		ASV-01	1/8"	0.5 ~ 8 Bar	Shuttle Valve Either one signal or the other to a common outlet	ASV
		ASV-02	1/4"	0.5 ~ 8 Bar		
		ASV-03	3/8"	0.5 ~ 8 Bar		
		ASV-04	1/2"	0.5 ~ 8 Bar		
		ASV-05	3/4"	0.5 ~ 8 Bar		
		ASV-06	1"	0.5 ~ 8 Bar		
QUICK EXHAUST VALVE 1/8 – 1” BSP						
		AQE-01	1/8"	0.5 ~ 8 Bar	Quick Exhaust of air signal when flow is reversed	AQE
		AQE-02	1/4"	0.5 ~ 8 Bar		
		AQE-03	3/8"	0.5 ~ 8 Bar		
		AQE-04	1/2"	0.5 ~ 8 Bar		
		AQE-05	3/4"	0.5 ~ 8 Bar		
		AQE-06	1"	0.5 ~ 8 Bar		
HAND SLIDE VALVE 1/8 – 1/2” BSP (Brass/Aluminium)						
		AHS-01	1/8"	0 ~ 10 Bar	3/2 Way Valve to close off supply and pump downstream to atmosphere	AHS
		AHS-02	1/4"	0 ~ 10 Bar		
		AHS-03	3/8"	0 ~ 10 Bar		
		AHS-04	1/2"	0 ~ 10 Bar		
PRECISION SPEED CONTROLLERS 1/8 – 1/2” BSP						
		APS-01	1/8"	0 ~ 10 Bar	In-Line Precision Speed Controller for air actuators	APS
		APS-02	1/4"	0 ~ 10 Bar		
		APS-03	3/8"	0 ~ 10 Bar		
		APS-04	1/2"	0 ~ 10 Bar		
PNEUMATIC VIBRATOR						
	Rotary Steel Ball	APV-02	1/4"	1 ~ 8 Bar	Air Vibrator for small parts	APV
VACUUM GENERATOR						
	Venturi	VAC-01 VAC-02 VAC-03	1/8" 1/4" 3/8"	0.1 ~ 16 Bar	Vacuum Generator using compressed air supply	VAC

FOR FULL RANGE VISIT OUR WEBSITE WWW.VALVESONLINE.COM.AU

Silencer	Model	Description
----------	-------	-------------

Exhaust Silencer/Regulator - Brass

BES

	BES-01	G1/8" Brass Exhaust Reg/Silencer
	BES-02	G1/4" Brass Exhaust Reg/Silencer
	BES-03	G3/8" Brass Exhaust Reg/Silencer
	BES-04	G1/2" Brass Exhaust Reg/Silencer
	BES-05	G3/4" Brass Exhaust Reg/Silencer
	BES-06	G1" Brass Exhaust Reg/Silencer

Silencer - Brass

BSL

	BSL-M5	M5 Brass Silencer
	BSL-01	G1/8" Brass Silencer
	BSL-02	G1/4" Brass Silencer
	BSL-03	G3/8" Brass Silencer
	BSL-04	G1/2" Brass Silencer
	BSL-05	G3/4" Brass Silencer
	BSL-06	G1" Brass Silencer
	BSL-07	G1-1/4" Brass Silencer
	BSL-08	G1-1/2" Brass Silencer
BSL-09	G2" Brass Silencer	

Silencer Mini - Brass

BSM

	BSM-01	G1/8" Brass Mini Silencer
	BSM-02	G1/4" Brass Mini Silencer
	BSM-03	G3/8" Brass Mini Silencer
	BSM-04	G1/2" Brass Mini Silencer
	BSM-05	G3/4" Brass Mini Silencer
	BSM-06	G1" Brass Mini Silencer

Silencer	Model	Description
----------	-------	-------------

Exhaust Silencer/Regulator - Stainless Steel

SES

	SES-01	G1/8" S.S Exhaust Reg/Silencer
	SES-02	G1/4" S.S Exhaust Reg/Silencer
	SES-03	G3/8" S.S Exhaust Reg/Silencer
	SES-04	G1/2" S.S Exhaust Reg/Silencer
	SES-05	G3/4" S.S Exhaust Reg/Silencer
	SES-06	G1" S.S Exhaust Reg/Silencer

Silencer - Stainless Steel

SSL

	SSL-M5	M5 S.S Silencer
	SSL-01	G1/8" S.S Silencer
	SSL-02	G1/4" S.S Silencer
	SSL-03	G3/8" S.S Silencer
	SSL-04	G1/2" S.S Silencer
	SSL-05	G3/4" S.S Silencer
	SSL-06	G1" S.S Silencer

Silencer Mini - Stainless Steel

SSM

	SSM-M5	M5 S.S Mini Silencer
	SSM-01	G1/8" S.S Mini Silencer
	SSM-02	G1/4" S.S Mini Silencer
	SSM-03	G3/8" S.S Mini Silencer
	SSM-04	G1/2" S.S Mini Silencer
	SSM-05	G3/4" S.S Mini Silencer
	SSM-06	G1" S.S Mini Silencer

Nylon Tubing to suit Push-Fit fittings

Nylon Tube	Item	Description	Full Coil Options				
			5m Coil	10m Coil	20m Coil	100m Coil	200m Coil
	NYL04-*	4mm O.D Nylon Tube (200m roll)	✓	✓	✓	✓	✓
	NYL06-*	6mm O.D Nylon Tube (200m roll)	✓	✓	✓	✓	✓
	NYL08-*	8mm O.D Nylon Tube (100m roll)	✓	✓	✓	✓	—
	NYL10-*	10mm O.D Nylon Tube (100m roll)	✓	✓	✓	✓	—
	NYL12-*	12mm O.D Nylon Tube (100m roll)	✓	✓	✓	✓	—
	NYL16-*	16mm O.D Nylon Tube (100m roll)	—	—	50m Coil ✓	✓	—
	NYL14-*	1/4" O.D Nylon Tube (200m roll)	✓	✓	✓	—	✓
	NYL1516-*	5/16" O.D Nylon Tube (100m roll)	✓	✓	✓	✓	—
	NYL138-*	3/8" O.D Nylon Tube (100m roll)	✓	✓	✓	✓	—
	NYL112-*	1/2" O.D Nylon Tube (100m roll)	✓	✓	✓	✓	—

Metric Tubing

Item	NYL04	NYL06	NYL08	NYL10	NYL12	NYL16	- Working Pressure 20 BAR @ 20°C. - UV Stabilised Black Tubing - PA6 Nylon
O.D. (mm)	ø 4.0	ø 6.0	ø 8.0	ø 10.0	ø 12.0	ø 16.0	
I.D. (mm)	ø 2.5	ø 4.0	ø 6.0	ø 7.5	ø 9.0	ø 12.0	

Imperial Tubing

Item	—	NYL114	NYL1516	NYL138	NYL112		- Working Pressure 20 BAR @ 20°C. - UV Stabilised Black Tubing - PA6 Nylon
O.D. (mm)	—	ø 1/4" 6.35mm	ø 5/16" 7.94mm	ø 3/8" 9.52mm	ø 1/2" 12.7mm		
I.D. (mm)	—	ø 4.2	ø 6.0	ø 6.35	ø 9.6		

- Swivel Joints
- Nickel Plated Brass Body with PTFE Coated Male Thread
- UV Resistant Plastic Body, Stainless Steel Gripper and NBR O-ring

Push Fit	Model	Description
----------	-------	-------------

Male Straight Connector (O.D. Tube to Male BSP Thread) YPC

	YPC04-M5	4mm x M5 BSPT Male Straight Connector
	YPC04-01	4mm x 1/8" BSPT Male Straight Connector
	YPC04-02	4mm x 1/4" BSPT Male Straight Connector
	YPC06-M5	6mm x M5 Male Straight Connector
	YPC06-01	6mm x 1/8" BSPT Male Straight Connector
	YPC06-02	6mm x 1/4" BSPT Male Straight Connector
	YPC06-03	6mm x 3/8" BSPT Male Straight Connector
	YPC06-04	6mm x 1/2" BSPT Male Straight Connector
	YPC08-01	8mm x 1/8" BSPT Male Straight Connector
	YPC08-02	8mm x 1/4" BSPT Male Straight Connector
	YPC08-03	8mm x 3/8" BSPT Male Straight Connector
	YPC08-04	8mm x 1/2" BSPT Male Straight Connector
	YPC10-01	10mm x 1/8" BSPT Male Straight Connector
	YPC10-02	10mm x 1/4" BSPT Male Straight Connector
	YPC10-03	10mm x 3/8" BSPT Male Straight Connector
	YPC10-04	10mm x 1/2" BSPT Male Straight Connector
	YPC12-02	12mm x 1/4" BSPT Male Straight Connector
	YPC12-03	12mm x 3/8" BSPT Male Straight Connector
	YPC12-04	12mm x 1/2" BSPT Male Straight Connector
	YPC16-04	16mm x 1/2" BSPT Male Straight Connector

Female Straight Connector (O.D. Tube to Female BSP Thread) YPCF

	YPCF04-M5	4mm x M5 BSPP Fem St. Connector
	YPCF04-01	4mm x 1/8" BSPP Fem St. Connector
	YPCF04-02	4mm x 1/4" BSPP Fem St. Connector
	YPCF06-M5	6mm x M5 BSPP Fem St. Connector
	YPCF06-01	6mm x 1/8" BSPP Fem St. Connector
	YPCF06-02	6mm x 1/4" BSPP Fem St. Connector
	YPCF06-03	6mm x 3/8" BSPP Fem St. Connector
	YPCF06-04	6mm x 1/2" BSPP Fem St. Connector
	YPCF08-01	8mm x 1/8" BSPP Fem St. Connector
	YPCF08-02	8mm x 1/4" BSPP Fem St. Connector
	YPCF08-03	8mm x 3/8" BSPP Fem St. Connector
	YPCF08-04	8mm x 1/2" BSPP Fem St. Connector
	YPCF10-01	10mm x 1/8" BSPP Fem St. Connector
	YPCF10-02	10mm x 1/4" BSPP Fem St. Connector
	YPCF10-03	10mm x 3/8" BSPP Fem St. Connector
	YPCF10-04	10mm x 1/2" BSPP Fem St. Connector
	YPCF12-02	12mm x 1/4" BSPP Fem St. Connector
	YPCF12-03	12mm x 3/8" BSPP Fem St. Connector
	YPCF12-04	12mm x 1/2" BSPP Fem St. Connector

Female Swivel Elbow (O.D. Tube to Female BSP Thread) YPLF

	YPLF04-M5	4mm x M5 BSPP Fem. Swivel Elbow
	YPLF04-01	4mm x 1/8" BSPP Fem. Swivel Elbow
	YPLF04-02	4mm x 1/4" BSPP Fem. Swivel Elbow
	YPLF06-M5	6mm x M5 BSPP Fem. Swivel Elbow
	YPLF06-01	6mm x 1/8" BSPP Fem. Swivel Elbow
	YPLF06-02	6mm x 1/4" BSPP Fem. Swivel Elbow
	YPLF06-03	6mm x 3/8" BSPP Fem. Swivel Elbow
	YPLF06-04	6mm x 1/2" BSPP Fem. Swivel Elbow
	YPLF08-01	8mm x 1/8" BSPP Fem. Swivel Elbow
	YPLF08-02	8mm x 1/4" BSPP Fem. Swivel Elbow
	YPLF08-03	8mm x 3/8" BSPP Fem. Swivel Elbow
	YPLF08-04	8mm x 1/2" BSPP Fem. Swivel Elbow
	YPLF10-01	10mm x 1/8" BSPP Fem. Swivel Elbow
	YPLF10-02	10mm x 1/4" BSPP Fem. Swivel Elbow
	YPLF10-03	10mm x 3/8" BSPP Fem. Swivel Elbow
	YPLF10-04	10mm x 1/2" BSPP Fem. Swivel Elbow
	YPLF12-02	12mm x 1/4" BSPP Fem. Swivel Elbow
	YPLF12-03	12mm x 3/8" BSPP Fem. Swivel Elbow
	YPLF12-04	12mm x 1/2" BSPP Fem. Swivel Elbow

On/Off Valve c/w Push Fit Ends YBV

	YBV04	4mm On/Off Valve
	YBV06	6mm On/Off Valve
	YBV08	8mm On/Off Valve
	YBV10	10mm On/Off Valve
	YBV12	12mm On/Off Valve

Metric Push Fits - Plastic

- Suitable for Air to 10 Bar. Metric and Imperial Tube Fittings
- Straight Fittings with Internal Allen Key Drive for Installation in Narrow Positions

Push Fit	Model	Description
----------	-------	-------------

Male Swivel Elbow (O.D. Tube to Male BSP Thread) YPL

	YPL04-M5	4mm x M5 BSPT Swivel Elbow
	YPL04-01	4mm x 1/8" BSPT Swivel Elbow
	YPL04-02	4mm x 1/4" BSPT Swivel Elbow
	YPL04-03	4mm x 3/8" BSPT Swivel Elbow
	YPL06-M5	6mm x M5 BSPT Swivel Elbow
	YPL06-01	6mm x 1/8" BSPT Swivel Elbow
	YPL06-02	6mm x 1/4" BSPT Swivel Elbow
	YPL06-03	6mm x 3/8" BSPT Swivel Elbow
	YPL06-04	6mm x 1/2" BSPT Swivel Elbow
	YPL08-01	8mm x 1/8" BSPT Swivel Elbow
	YPL08-02	8mm x 1/4" BSPT Swivel Elbow
	YPL08-03	8mm x 3/8" BSPT Swivel Elbow
	YPL08-04	8mm x 1/2" BSPT Swivel Elbow
	YPL10-01	10mm x 1/8" BSPT Swivel Elbow
	YPL10-02	10mm x 1/4" BSPT Swivel Elbow
	YPL10-03	10mm x 3/8" BSPT Swivel Elbow
	YPL10-04	10mm x 1/2" BSPT Swivel Elbow
	YPL12-02	12mm x 1/4" BSPT Swivel Elbow
	YPL12-03	12mm x 3/8" BSPT Swivel Elbow
	YPL12-04	12mm x 1/2" BSPT Swivel Elbow
	YPL16-04	16mm x 1/2" BSPT Swivel Elbow

Extension Swivel Elbow (O.D. Tube to Male BSP Thread) YPLL

	YPLL04-M5	4mm x M5 BSPT Ext. Swivel Elbow
	YPLL04-01	4mm x 1/8" BSPT Ext. Swivel Elbow
	YPLL04-02	4mm x 1/4" BSPT Ext. Swivel Elbow
	YPLL06-M5	6mm x M5 BSPT Ext. Swivel Elbow
	YPLL06-01	6mm x 1/8" BSPT Ext. Swivel Elbow
	YPLL06-02	6mm x 1/4" BSPT Ext. Swivel Elbow
	YPLL06-03	6mm x 3/8" BSPT Ext. Swivel Elbow
	YPLL06-04	6mm x 1/2" BSPT Ext. Swivel Elbow
	YPLL08-01	8mm x 1/8" BSPT Ext. Swivel Elbow
	YPLL08-02	8mm x 1/4" BSPT Ext. Swivel Elbow
	YPLL08-03	8mm x 3/8" BSPT Ext. Swivel Elbow
	YPLL08-04	8mm x 1/2" BSPT Ext. Swivel Elbow
	YPLL10-01	10mm x 1/8" BSPT Ext. Swivel Elbow
	YPLL10-02	10mm x 1/4" BSPT Ext. Swivel Elbow
	YPLL10-03	10mm x 3/8" BSPT Ext. Swivel Elbow
	YPLL10-04	10mm x 1/2" BSPT Ext. Swivel Elbow
	YPLL12-02	12mm x 1/4" BSPT Ext. Swivel Elbow
	YPLL12-03	12mm x 3/8" BSPT Ext. Swivel Elbow
	YPLL12-04	12mm x 1/2" BSPT Ext. Swivel Elbow

Elbow Joiner (O.D. Tube to O.D. Tube) YPV

	YPV04	4mm Elbow Joiner
	YPV06	6mm Elbow Joiner
	YPV08	8mm Elbow Joiner
	YPV10	10mm Elbow Joiner
	YPV12	12mm Elbow Joiner
	YPV16	16mm Elbow Joiner

Straight Joiner (O.D. Tube to O.D. Tube) YPU

	YPU04	4mm Straight Joiner
	YPU06	6mm Straight Joiner
	YPU08	8mm Straight Joiner
	YPU10	10mm Straight Joiner
	YPU12	12mm Straight Joiner
	YPU16	16mm Straight Joiner

Tee Joiner (O.D. Tube to O.D. Tube) YPE

	YPE04	4mm Tee Joiner
	YPE06	6mm Tee Joiner
	YPE08	8mm Tee Joiner
	YPE10	10mm Tee Joiner
	YPE12	12mm Tee Joiner
	YPE16	16mm Tee Joiner

Push Fit

Model

Description

- Swivel Joints
- Nickel Plated Brass Body with PTFE Coated Male Thread
- UV Resistant Plastic Body, Stainless Steel Gripper and NBR O-ring

Male Run Tee (O.D. Tube to Male BSP Thread)

YPB

	YPB04-M5	4mm x M5" BSPT Male Run Tee
	YPB04-01	4mm x 1/8" BSPT Male Run Tee
	YPB04-02	4mm x 1/4" BSPT Male Run Tee
	YPB06-M5	6mm x M5" BSPT Male Run Tee
	YPB06-01	6mm x 1/8" BSPT Male Run Tee
	YPB06-02	6mm x 1/4" BSPT Male Run Tee
	YPB06-03	6mm x 3/8" BSPT Male Run Tee
	YPB06-04	6mm x 1/2" BSPT Male Run Tee
	YPB08-01	8mm x 1/8" BSPT Male Run Tee
	YPB08-02	8mm x 1/4" BSPT Male Run Tee
	YPB08-03	8mm x 3/8" BSPT Male Run Tee
	YPB08-04	8mm x 1/2" BSPT Male Run Tee
	YPB10-01	10mm x 1/8" BSPT Male Run Tee
	YPB10-02	10mm x 1/4" BSPT Male Run Tee
	YPB10-03	10mm x 3/8" BSPT Male Run Tee
	YPB10-04	10mm x 1/2" BSPT Male Run Tee
	YPB12-02	12mm x 1/4" BSPT Male Run Tee
	YPB12-03	12mm x 3/8" BSPT Male Run Tee
	YPB12-04	12mm x 1/2" BSPT Male Run Tee

Male Branch Y (O.D. Tube to Male BSP Thread)

YPX

	YPX04-M5	4mm x M5 BSPT Male Branch Y
	YPX04-01	4mm x 1/8" BSPT Male Branch Y
	YPX04-02	4mm x 1/4" BSPT Male Branch Y
	YPX06-M5	6mm x M5 BSPT Male Branch Y
	YPX06-01	6mm x 1/8" BSPT Male Branch Y
	YPX06-02	6mm x 1/4" BSPT Male Branch Y
	YPX06-03	6mm x 3/8" BSPT Male Branch Y
	YPX06-04	6mm x 1/2" BSPT Male Branch Y
	YPX08-01	8mm x 1/8" BSPT Male Branch Y
	YPX08-02	8mm x 1/4" BSPT Male Branch Y
	YPX08-03	8mm x 3/8" BSPT Male Branch Y
	YPX08-04	8mm x 1/2" BSPT Male Branch Y
	YPX10-01	10mm x 1/8" BSPT Male Branch Y
	YPX10-02	10mm x 1/4" BSPT Male Branch Y
	YPX10-03	10mm x 3/8" BSPT Male Branch Y
	YPX10-04	10mm x 1/2" BSPT Male Branch Y
	YPX12-02	12mm x 1/4" BSPT Male Branch Y
	YPX12-03	12mm x 3/8" BSPT Male Branch Y
	YPX12-04	12mm x 1/2" BSPT Male Branch Y

Elbow Speed Control (O.D. Tube to Male BSP Thread)

YSC

	YSC04-M5	4mm x M5 BSPT Tube Speed Control
	YSC04-01	4mm x 1/8" BSPT Tube Speed Control
	YSC04-02	4mm x 1/4" BSPT Tube Speed Control
	YSC06-M5	6mm x M5 BSPT Tube Speed Control
	YSC06-01	6mm x 1/8" BSPT Tube Speed Control
	YSC06-02	6mm x 1/4" BSPT Tube Speed Control
	YSC06-03	6mm x 3/8" BSPT Tube Speed Control
	YSC06-04	6mm x 1/2" BSPT Tube Speed Control
	YSC08-01	8mm x 1/8" BSPT Tube Speed Control
	YSC08-02	8mm x 1/4" BSPT Tube Speed Control
	YSC08-03	8mm x 3/8" BSPT Tube Speed Control
	YSC08-04	8mm x 1/2" BSPT Tube Speed Control
	YSC10-01	10mm x 1/8" BSPT Tube Speed Control
	YSC10-02	10mm x 1/4" BSPT Tube Speed Control
	YSC10-03	10mm x 3/8" BSPT Tube Speed Control
	YSC10-04	10mm x 1/2" BSPT Tube Speed Control
	YSC12-02	12mm x 1/4" BSPT Tube Speed Control
	YSC12-03	12mm x 3/8" BSPT Tube Speed Control
	YSC12-04	12mm x 1/2" BSPT Tube Speed Control

Push Fit

Model

Description

- Suitable for Air to 10 Bar. Metric and Imperial Tube Fittings
- Straight Fittings with Internal Allen Key Drive for Installation in Narrow Positions

Male Branch Tee (O.D. Tube to Male BSP Thread)

YPD

	YPD04-M5	4mm x M5 BSPT Male Branch Tee
	YPD04-01	4mm x 1/8" BSPT Male Branch Tee
	YPD04-02	4mm x 1/4" BSPT Male Branch Tee
	YPD06-M5	6mm x M5 BSPT Male Branch Tee
	YPD06-01	6mm x 1/8" BSPT Male Branch Tee
	YPD06-02	6mm x 1/4" BSPT Male Branch Tee
	YPD06-03	6mm x 3/8" BSPT Male Branch Tee
	YPD06-04	6mm x 1/2" BSPT Male Branch Tee
	YPD08-01	8mm x 1/8" BSPT Male Branch Tee
	YPD08-02	8mm x 1/4" BSPT Male Branch Tee
	YPD08-03	8mm x 3/8" BSPT Male Branch Tee
	YPD08-04	8mm x 1/2" BSPT Male Branch Tee
	YPD10-01	10mm x 1/8" BSPT Male Branch Tee
	YPD10-02	10mm x 1/4" BSPT Male Branch Tee
	YPD10-03	10mm x 3/8" BSPT Male Branch Tee
	YPD10-04	10mm x 1/2" BSPT Male Branch Tee
	YPD12-02	12mm x 1/4" BSPT Male Branch Tee
	YPD12-03	12mm x 3/8" BSPT Male Branch Tee
	YPD12-04	12mm x 1/2" BSPT Male Branch Tee

Universal Female Elbow (O.D. Tube to Male BSP Thread)

YPHF

	YPHF04-M5	4mm x M5 BSPP Univ. Female Elbow
	YPHF04-01	4mm x 1/8" BSPP Univ. Female Elbow
	YPHF04-02	4mm x 1/4" BSPP Univ. Female Elbow
	YPHF06-M5	6mm x M5 BSPP Univ. Female Elbow
	YPHF06-01	6mm x 1/8" BSPP Univ. Female Elbow
	YPHF06-02	6mm x 1/4" BSPP Univ. Female Elbow
	YPHF06-03	6mm x 3/8" BSPP Univ. Female Elbow
	YPHF06-04	6mm x 1/2" BSPP Univ. Female Elbow
	YPHF08-01	8mm x 1/8" BSPP Univ. Female Elbow
	YPHF08-02	8mm x 1/4" BSPP Univ. Female Elbow
	YPHF08-03	8mm x 3/8" BSPP Univ. Female Elbow
	YPHF08-04	8mm x 1/2" BSPP Univ. Female Elbow
	YPHF10-01	10mm x 1/8" BSPP Univ. Female Elbow
	YPHF10-02	10mm x 1/4" BSPP Univ. Female Elbow
	YPHF10-03	10mm x 3/8" BSPP Univ. Female Elbow
	YPHF10-04	10mm x 1/2" BSPP Univ. Female Elbow
	YPHF12-02	12mm x 1/4" BSPP Univ. Female Elbow
	YPHF12-03	12mm x 3/8" BSPP Univ. Female Elbow
	YPHF12-04	12mm x 1/2" BSPP Univ. Female Elbow

Hex Head Male Elbow (O.D. Tube to Male BSP Thread)

YPH

	YPH04-M5	4mm x M5 BSPT Hex Head Male Elbow
	YPH04-01	4mm x 1/8" BSPT Hex Head Male Elbow
	YPH04-02	4mm x 1/4" BSPT Hex Head Male Elbow
	YPH06-M5	6mm x M5 BSPT Hex Head Male Elbow
	YPH06-01	6mm x 1/8" BSPT Hex Head Male Elbow
	YPH06-02	6mm x 1/4" BSPT Hex Head Male Elbow
	YPH06-03	6mm x 3/8" BSPT Hex Head Male Elbow
	YPH06-04	6mm x 1/2" BSPT Hex Head Male Elbow
	YPH08-01	8mm x 1/8" BSPT Hex Head Male Elbow
	YPH08-02	8mm x 1/4" BSPT Hex Head Male Elbow
	YPH08-03	8mm x 3/8" BSPT Hex Head Male Elbow
	YPH08-04	8mm x 1/2" BSPT Hex Head Male Elbow
	YPH10-01	10mm x 1/8" BSPT Hex Head Male Elbow
	YPH10-02	10mm x 1/4" BSPT Hex Head Male Elbow
	YPH10-03	10mm x 3/8" BSPT Hex Head Male Elbow
	YPH10-04	10mm x 1/2" BSPT Hex Head Male Elbow
	YPH12-02	12mm x 1/4" BSPT Hex Head Male Elbow
	YPH12-03	12mm x 3/8" BSPT Hex Head Male Elbow
	YPH12-04	12mm x 1/2" BSPT Hex Head Male Elbow

Push Fit	Model	Description
----------	-------	-------------

Push Fit	Model	Description
----------	-------	-------------

Metric Push Fits - Plastic

Bulkhead Union (O.D. Tube to O.D. Tube)

YPM

	YPM04	4mm Bulkhead Union
	YPM06	6mm Bulkhead Union
	YPM08	8mm Bulkhead Union
	YPM10	10mm Bulkhead Union
	YPM12	12mm Bulkhead Union

Y Joiner (O.D. Tube to O.D. Tube)

YPY

	YPY04	4mm Y Joiner
	YPY06	6mm Y Joiner
	YPY08	8mm Y Joiner
	YPY10	10mm Y Joiner
	YPY12	12mm Y Joiner
	YPY16	16mm Y Joiner

Cross Joiner (O.D. Tube to O.D. Tube)

YPZ

	YPZA04	4mm Cross Joiner
	YPZA06	6mm Cross Joiner
	YPZA08	8mm Cross Joiner
	YPZA10	10mm Cross Joiner
	YPZA12	12mm Cross Joiner

Triple Joiner (O.D. Tube to O.D. Tube)

YPK

	YPK04	4mm Triple Joiner
	YPK06	6mm Triple Joiner
	YPK08	8mm Triple Joiner
	YPK10	10mm Triple Joiner
	YPK12	12mm Triple Joiner

Triple Male Elbow (O.D. Tube to Male BSP Thread)

YPKB

	YPKB04-01	4mm x 1/8" BSPT Triple Male Elbow
	YPKB04-02	4mm x 1/4" BSPT Triple Male Elbow
	YPKB06-01	6mm x 1/8" BSPT Triple Male Elbow
	YPKB06-02	6mm x 1/4" BSPT Triple Male Elbow
	YPKB06-03	6mm x 3/8" BSPT Triple Male Elbow
	YPKB08-01	8mm x 1/8" BSPT Triple Male Elbow
	YPKB08-02	8mm x 1/4" BSPT Triple Male Elbow
	YPKB08-03	8mm x 3/8" BSPT Triple Male Elbow

Plug In Elbow (O.D. Tube to Male Tube)

YPLGJ

	YPLGJ06-04	6mm to 4mm Plug in Elbow
	YPLGJ08-04	8mm to 4mm Plug in Elbow
	YPLGJ08-06	8mm to 6mm Plug in Elbow
	YPLGJ10-6	10mm to 6mm Plug in Elbow
	YPLGJ10-8	10mm to 8mm Plug in Elbow
	YPLGJ12-10	12mm to 10mm Plug in Elbow
	YPLGJ12-8	12mm to 8mm Plug in Elbow

Plug In Tee (O.D. Tube to Male Tube)

YPEGJ

	YPEGJ06-04	6mm to 4mm Plug in Tee
	YPEGJ08-04	8mm to 4mm Plug in Tee
	YPEGJ08-06	8mm to 6mm Plug in Tee
	YPEGJ10-6	10mm to 6mm Plug in Tee
	YPEGJ10-8	10mm to 8mm Plug in Tee
	YPEGJ12-10	12mm to 10mm Plug in Tee
	YPEGJ12-8	12mm to 8mm Plug in Tee

Plug In Reducer (O.D. Tube to Male Tube)

YPGJ

	YPGJ06-04	6mm to 4mm Plug in Reducer
	YPGJ08-04	8mm to 4mm Plug in Reducer
	YPGJ08-06	8mm to 6mm Plug in Reducer
	YPGJ10-06	10mm to 6mm Plug in Reducer
	YPGJ10-08	10mm to 8mm Plug in Reducer
	YPGJ12-06	12mm to 6mm Plug in Reducer
	YPGJ12-08	12mm to 8mm Plug in Reducer
	YPGJ12-10	12mm to 10mm Plug in Reducer

Plug (Male Tube)

YPP

	YPP04	4mm Plug
	YPP06	6mm Plug
	YPP08	8mm Plug
	YPP10	10mm Plug
	YPP12	12mm Plug

Imperial Push Fits - Plastic

Male Straight Connector (O.D. Tube to Male BSP Thread)

IPC

	IPC14-01	1/4" Tube x 1/8" BSPT Male Straight Connector
	IPC14-02	1/4" Tube x 1/4" BSPT Male Straight Connector
	IPC14-03	1/4" Tube x 3/8" BSPT Male Straight Connector
	IPC14-04	1/4" Tube x 1/2" BSPT Male Straight Connector
	IPC516-01	5/16" Tube x 1/8" BSPT Male Straight Connector
	IPC516-02	5/16" Tube x 1/4" BSPT Male Straight Connector
	IPC516-03	5/16" Tube x 3/8" BSPT Male Straight Connector
	IPC516-04	5/16" Tube x 1/2" BSPT Male Straight Connector
	IPC38-01	3/8" Tube x 1/8" BSPT Male Straight Connector
	IPC38-02	3/8" Tube x 1/4" BSPT Male Straight Connector
	IPC38-03	3/8" Tube x 3/8" BSPT Male Straight Connector
	IPC38-04	3/8" Tube x 1/2" BSPT Male Straight Connector
	IPC12-02	1/2" Tube x 1/4" BSPT Male Straight Connector
	IPC12-03	1/2" Tube x 3/8" BSPT Male Straight Connector
	IPC12-04	1/2" Tube x 1/2" BSPT Male Straight Connector

Tee Joiner (O.D. Tube to O.D. Tube)

IPE

	IPE14	1/4" Tee Joiner
	IPE516	5/16" Tee Joiner
	IPE38	3/8" Tee Joiner
	IPE12	1/2" Tee Joiner

Swivel Elbow (O.D. Tube to Male BSP Thread)

IPL

	IPL14-01	1/4" Tube x 1/8" BSPT Swivel Elbow
	IPL14-02	1/4" Tube x 1/4" BSPT Swivel Elbow
	IPL14-03	1/4" Tube x 3/8" BSPT Swivel Elbow
	IPL14-04	1/4" Tube x 1/2" BSPT Swivel Elbow
	IPL516-01	5/16" Tube x 1/8" BSPT Swivel Elbow
	IPL516-02	5/16" Tube x 1/4" BSPT Swivel Elbow
	IPL516-03	5/16" Tube x 3/8" BSPT Swivel Elbow
	IPL516-04	5/16" Tube x 1/2" BSPT Swivel Elbow
	IPL38-01	3/8" Tube x 1/8" BSPT Swivel Elbow
	IPL38-02	3/8" Tube x 1/4" BSPT Swivel Elbow
	IPL38-03	3/8" Tube x 3/8" BSPT Swivel Elbow
	IPL38-04	3/8" Tube x 1/2" BSPT Swivel Elbow
	IPL12-02	1/2" Tube x 1/4" BSPT Swivel Elbow
	IPL12-03	1/2" Tube x 3/8" BSPT Swivel Elbow
	IPL12-04	1/2" Tube x 1/2" BSPT Swivel Elbow

Straight Joiner (O.D. Tube to O.D. Tube)

IPU

	IPU14	1/4" Tube St. Joiner
	IPU516	5/16" Tube St. Joiner
	IPU38	3/8" Tube St. Joiner
	IPU12	1/2" Tube St. Joiner

Imperial Push Fits - Plastic

Push Fit	Model	Description
----------	-------	-------------

Y Joiner (O.D. Tube to O.D. Tube) IPY

IPY

	IPY14	1/4" Y Joiner
	IPY516	5/16" Y Joiner
	IPY38	3/8" Y Joiner
	IPY12	1/2" Y Joiner

Elbow Joiner (O.D. Tube to O.D. Tube)

IPV

	IPV14	1/4" Elbow Joiner
	IPV516	5/16" Elbow Joiner
	IPV38	3/8" Elbow Joiner
	IPV12	1/2" Elbow Joiner

Female Swivel Elbow (O.D. Tube to Female BSP Thread)

IPLF

	IPLF14-01	1/4" x 1/8" BSPT Female Swivel Elbow
	IPLF14-02	1/4" x 1/4" BSPT Female Swivel Elbow
	IPLF14-03	1/4" x 3/8" BSPT Female Swivel Elbow
	IPLF14-04	1/4" x 1/2" BSPT Female Swivel Elbow
	IPLF516-01	5/16" x 1/8" BSPT Female Swivel Elbow
	IPLF516-02	5/16" x 1/2" BSPT Female Swivel Elbow
	IPLF516-03	5/16" x 3/8" BSPT Female Swivel Elbow
	IPLF516-04	5/16" x 1/2" BSPT Female Swivel Elbow
	IPLF38-01	3/8" x 1/8" BSPT Female Swivel Elbow
	IPLF38-02	3/8" x 1/4" BSPT Female Swivel Elbow
	IPLF38-03	3/8" x 3/8" BSPT Female Swivel Elbow
	IPLF38-04	3/8" x 1/2" BSPT Female Swivel Elbow
	IPLF12-02	1/2" x 1/4" BSPT Female Swivel Elbow
	IPLF12-03	1/2" x 3/8" BSPT Female Swivel Elbow
	IPLF12-04	1/2" x 1/2" BSPT Female Swivel Elbow

Elbow Speed Control (O.D. Tube to Male BSP Thread)

ISC

	ISC14-01	1/4" x 1/8" BSPT Tube Speed Control
	ISC14-02	1/4" x 1/4" BSPT Tube Speed Control
	ISC516-01	5/16" x 1/8" BSPT Tube Speed Control
	ISC516-02	5/16" x 1/4" BSPT Tube Speed Control
	ISC516-03	5/16" x 3/8" BSPT Tube Speed Control
	ISC38-03	3/8" x 3/8" BSPT Tube Speed Control
	ISC38-04	3/8" x 1/2" BSPT Tube Speed Control
	ISC12-03	1/2" x 3/8" BSPT Tube Speed Control
	ISC12-04	1/2" x 1/2" BSPT Tube Speed Control

Union Tube Joiner (Imperial to Metric)

YPI

	YPI06-14	6mm Tube to 1/4" Tube
	YPI10-38	10mm Tube to 3/8" Tube
	YPI12-12	12mm Tube to 1/2" Tube

Push Fit	Model	Description
----------	-------	-------------

Male Run Tee (O.D. Tube to Male BSP Thread)

IPB

	IPB14-01	1/4" x 1/8" BSPT Male Run Tee
	IPB14-02	1/4" x 1/4" BSPT Male Run Tee
	IPB14-03	1/4" x 3/8" BSPT Male Run Tee
	IPB14-04	1/4" x 1/2" BSPT Male Run Tee
	IPB516-01	5/16" x 1/8" BSPT Male Run Tee
	IPB516-02	5/16" x 1/4" BSPT Male Run Tee
	IPB516-03	5/16" x 3/8" BSPT Male Run Tee
	IPB516-04	5/16" x 1/2" BSPT Male Run Tee
	IPB38-01	3/8" x 1/8" BSPT Male Run Tee
	IPB38-02	3/8" x 1/4" BSPT Male Run Tee
	IPB38-03	3/8" x 3/8" BSPT Male Run Tee
	IPB38-04	3/8" x 1/2" BSPT Male Run Tee
	IPB12-02	1/2" x 1/4" BSPT Male Run Tee
	IPB12-03	1/2" x 3/8" BSPT Male Run Tee
	IPB12-04	1/2" x 1/2" BSPT Male Run Tee

Female Straight Connector (O.D. Tube to Female BSP Thread) IPCF

	IPCF14-01	1/4" x 1/8" BSPT Female Straight Connector
	IPCF14-02	1/4" x 1/4" BSPT Female Straight Connector
	IPCF14-03	1/4" x 3/8" BSPT Female Straight Connector
	IPCF14-04	1/4" x 1/2" BSPT Female Straight Connector
	IPCF516-01	5/16" x 1/8" BSPT Female Straight Connector
	IPCF516-02	5/16" x 1/4" BSPT Female Straight Connector
	IPCF516-03	5/16" x 3/8" BSPT Female Straight Connector
	IPCF516-04	5/16" x 1/2" BSPT Female Straight Connector
	IPCF38-01	3/8" x 1/8" BSPT Female Straight Connector
	IPCF38-02	3/8" x 1/4" BSPT Female Straight Connector
	IPCF38-03	3/8" x 3/8" BSPT Female Straight Connector
	IPCF38-04	3/8" x 1/2" BSPT Female Straight Connector
	IPCF12-02	1/2" x 1/4" BSPT Female Straight Connector
	IPCF12-03	1/2" x 3/8" BSPT Female Straight Connector
	IPCF12-04	1/2" x 1/2" BSPT Female Straight Connector

Bulkhead Union (O.D. Tube to O.D. Tube)

IPM

	IPM14	1/4" Bulkhead Union
	IPM516	5/16" Bulkhead Union
	IPM38	3/8" Bulkhead Union
	IPM12	1/2" Bulkhead Union

Plug In Reducer (O.D. Tube to Male Tube)

IPGJ

	IPGJ516-14	5/16" to 1/4" Plug in Reducer
	IPGJ38-14	3/8" to 1/4" Plug in Reducer
	IPGJ38-516	3/8" to 5/16" Plug in Reducer
	IPGJ12-14	1/2" to 1/4" Plug in Reducer
	IPGJ12-516	1/2" to 5/16" Plug in Reducer
	IPGJ12-38	1/2" to 3/8" Plug in Reducer

Plug (Male Tube)

IPP

	IPP14	1/4" Plug
	IPP516	5/16" Plug
	IPP38	3/8" Plug
	IPP12	1/2" Plug

On/Off Valve c/w Push Fit Ends

IBV

	IBV14	1/4" On/Off Valve
	IBV516	5/16" On/Off Valve
	IBV38	3/8" On/Off Valve
	IBV12	1/2" On/Off Valve

Stainless Steel SS316 Push Fit Tube Connectors – Metric & Imperial

- Swivel Joints
- Stainless Steel Body & Internals
- Viton (FKM) O-Ring

- Ideal for food, pharmaceutical, marine environment, chemical
- 20 BAR Working Pressure Ambient
- Optional Imperial and other sizes including 14mm OD Tube (Indent Only)

Push Fit	Model	Tube Metric	Model	Tube Imperial
Male Straight Connector	SPC		ISPC	
 O.D. Tube to Male BSPT SS316	SPC04-M5	4mm x M5 BSPT	—	—
	SPC04-01	4mm x 1/8" BSPT	—	—
	SPC04-02	4mm x 1/4" BSPT	—	—
	SPC06-M5	6mm x M5	ISPC14-M5	1/4" x M5 BSPT
	SPC06-01	6mm x 1/8" BSPT	ISPC14-01	1/4" x 1/8" BSPT
	SPC06-02	6mm x 1/4" BSPT	ISPC14-02	1/4" x 1/4" BSPT
	SPC06-03	6mm x 3/8" BSPT	ISPC14-03	1/4" x 3/8" BSPT
	SPC08-01	8mm x 1/8" BSPT	ISPC516-01	5/16" x 1/8" BSPT
	SPC08-02	8mm x 1/4" BSPT	ISPC516-02	5/16" x 1/4" BSPT
	SPC08-03	8mm x 3/8" BSPT	ISPC516-03	5/16" x 3/8" BSPT
	SPC10-02	10mm x 1/4" BSPT	ISPC38-02	3/8" x 1/4" BSPT
	SPC10-03	10mm x 3/8" BSPT	ISPC38-03	3/8" x 3/8" BSPT
	SPC10-04	10mm x 1/2" BSPT	ISPC38-04	3/8" x 1/2" BSPT
	SPC12-02	12mm x 1/4" BSPT	ISPC12-02	1/2" x 1/4" BSPT
	SPC12-03	12mm x 3/8" BSPT	ISPC12-03	1/2" x 3/8" BSPT
	SPC12-04	12mm x 1/2" BSPT	ISPC12-04	1/2" x 1/2" BSPT
	SPC14-04	14mm x 1/2" BSPT	—	—
	SPC16-04	16mm x 1/2" BSPT	—	—
	SPC16-05	16mm x 3/4" BSPT	—	—
Female Straight Connector	SPCF		ISPCF	
 O.D. Tube to Female BSPF SS316	SPCF04-01	4mm x 1/8" BSPF	—	—
	SPCF04-02	4mm x 1/4" BSPF	—	—
	SPCF06-01	6mm x 1/8" BSPF	ISPCF14-01	1/4" x 1/8" BSPF
	SPCF06-02	6mm x 1/4" BSPF	ISPCF14-02	1/4" x 1/4" BSPF
	SPCF06-03	6mm x 3/8" BSPF	ISPCF14-03	1/4" x 3/8" BSPF
	SPCF08-01	8mm x 1/8" BSPF	ISPCF516-01	5/16" x 1/8" BSPF
	SPCF08-02	8mm x 1/4" BSPF	ISPCF516-02	5/16" x 1/4" BSPF
	SPCF08-03	8mm x 3/8" BSPF	ISPCF516-03	5/16" x 3/8" BSPF
	SPCF08-04	8mm x 1/2" BSPF	ISPCF38-04	3/8" x 1/2" BSPF
	SPCF10-02	10mm x 1/4" BSPF	ISPCF38-02	3/8" x 1/4" BSPF
	SPCF10-03	10mm x 3/8" BSPF	ISPCF38-03	3/8" x 3/8" BSPF
	SPCF10-04	10mm x 1/2" BSPF	ISPCF38-04	3/8" x 1/2" BSPF
	SPCF12-02	12mm x 1/4" BSPF	ISPCF12-02	1/2" x 1/4" BSPF
	SPCF12-03	12mm x 3/8" BSPF	ISPCF12-03	1/2" x 3/8" BSPF
	SPCF12-04	12mm x 1/2" BSPF	ISPCF12-04	1/2" x 1/2" BSPF
Male Run Tee	SPB		ISPB	
 O.D. Tube to Male BSPT SS316	SPB04-01	4mm x 1/8" BSPT	—	—
	SPB04-02	4mm x 1/4" BSPT	—	—
	SPB06-01	6mm x 1/8" BSPT	ISPB14-01	1/4" x 1/8" BSPT
	SPB06-02	6mm x 1/4" BSPT	ISPB14-02	1/4" x 1/4" BSPT
	SPB08-01	8mm x 1/8" BSPT	ISPB516-01	5/16" x 1/8" BSPT
	SPB08-02	8mm x 1/4" BSPT	ISPB516-02	5/16" x 1/4" BSPT
	SPB08-03	8mm x 3/8" BSPT	ISPB516-03	5/16" x 3/8" BSPT
	SPB10-02	10mm x 1/4" BSPT	ISPB38-02	3/8" x 1/4" BSPT
	SPB10-03	10mm x 3/8" BSPT	ISPB38-03	3/8" x 3/8" BSPT
	SPB12-03	12mm x 3/8" BSPT	ISPB12-03	1/2" x 3/8" BSPT
	SPB12-04	12mm x 1/2" BSPT	ISPB12-04	1/2" x 1/2" BSPT
	SPB14-04	14mm x 1/2" BSPT	—	—
	SPB16-04	16mm x 1/2" BSPT	—	—
	SPB16-05	16mm x 3/4" BSPT	—	—
Tee Joiner	SPE		ISPE	
 O.D. to O.D. Tube SS316	SPE04	4mm	ISPE14	1/4"
	SPE06	6mm	ISPE16	5/16"
	SPE08	8mm	ISPE38	3/8"
	SPE10	10mm	ISPE12	1/2"
	SPE12	12mm	—	—
	SPE14	14mm	—	—
	SPE16	16mm	—	—
Elbow Joiner	SPV		ISPV	
 O.D. to O.D. Tube SS316	SPV04	4mm	ISPV14	1/4"
	SPV06	6mm	ISPV16	5/16"
	SPV08	8mm	ISPV38	3/8"
	SPV10	10mm	ISPV12	1/2"
	SPV12	12mm	—	—
	SPV14	14mm	—	—
	SPV16	16mm	—	—

Push Fit	Model	Tube Metric	Model	Tube Imperial
Male Swivel Elbow	SPL		ISPL	
 O.D. Tube to Male BSPT SS316	SPL04-M5	4mm x M5 BSPT	—	—
	SPL04-01	4mm x 1/8" BSPT	—	—
	SPL04-02	4mm x 1/4" BSPT	—	—
	SPL06-M5	6mm x M5 BSPT	ISPL14-M5	1/4" x M5 BSPT
	SPL06-01	6mm x 1/8" BSPT	ISPL14-01	1/4" x 1/8" BSPT
	SPL06-02	6mm x 1/4" BSPT	ISPL14-02	1/4" x 1/4" BSPT
	SPL06-03	6mm x 3/8" BSPT	ISPL14-03	1/4" x 3/8" BSPT
	SPL08-01	8mm x 1/8" BSPT	ISPL516-01	5/16" x 1/8" BSPT
	SPL08-02	8mm x 1/4" BSPT	ISPL516-02	5/16" x 1/4" BSPT
	SPL08-03	8mm x 3/8" BSPT	ISPL516-03	5/16" x 3/8" BSPT
	SPL10-02	10mm x 1/4" BSPT	ISPL38-02	3/8" x 1/4" BSPT
	SPL10-03	10mm x 3/8" BSPT	ISPL38-03	3/8" x 3/8" BSPT
	SPL10-04	10mm x 1/2" BSPT	ISPL38-04	3/8" x 1/2" BSPT
	SPL12-02	12mm x 1/4" BSPT	ISPL12-02	1/2" x 1/4" BSPT
	SPL12-03	12mm x 3/8" BSPT	ISPL12-03	1/2" x 3/8" BSPT
	SPL12-04	12mm x 1/2" BSPT	ISPL12-04	1/2" x 1/2" BSPT
	SPL14-04	14mm x 1/2" BSPT	—	—
	SPL16-04	16mm x 1/2" BSPT	—	—
	SPL16-05	16mm x 3/4" BSPT	—	—
Female Swivel Elbow	SPLF		ISPLF	
 O.D. Tube to Female BSPF SS316	SPLF04-01	4mm x 1/8" BSPF	—	—
	SPLF04-02	4mm x 1/4" BSPF	—	—
	SPLF06-01	6mm x 1/8" BSPF	ISPLF14-01	1/4" x 1/8" BSPF
	SPLF06-02	6mm x 1/4" BSPF	ISPLF14-02	1/4" x 1/4" BSPF
	SPLF06-03	6mm x 3/8" BSPF	ISPLF14-03	1/4" x 3/8" BSPF
	SPLF08-01	8mm x 1/8" BSPF	ISPLF516-01	5/16" x 1/8" BSPF
	SPLF08-02	8mm x 1/4" BSPF	ISPLF516-02	5/16" x 1/4" BSPF
	SPLF08-03	8mm x 3/8" BSPF	ISPLF516-03	5/16" x 3/8" BSPF
	SPLF08-04	8mm x 1/2" BSPF	ISPLF516-04	5/16" x 3/8" BSPF
	SPLF10-02	10mm x 1/4" BSPF	ISPLF38-02	3/8" x 1/4" BSPF
	SPLF10-03	10mm x 3/8" BSPF	ISPLF38-03	3/8" x 3/8" BSPF
	SPLF10-04	10mm x 1/2" BSPF	ISPLF38-04	3/8" x 1/2" BSPF
	SPLF12-02	12mm x 1/4" BSPF	ISPLF12-02	1/2" x 1/4" BSPF
	SPLF12-03	12mm x 3/8" BSPF	ISPLF12-03	1/2" x 3/8" BSPF
	SPLF12-04	12mm x 1/2" BSPF	ISPLF12-04	1/2" x 1/2" BSPF
Male Branch Tee	SPD		ISPD	
 O.D. Tube to Male BSPT SS316	SPD04-01	4mm x 1/8" BSPT	—	—
	SPD04-02	4mm x 1/4" BSPT	—	—
	SPD06-01	6mm x 1/8" BSPT	ISPD14-01	1/4" x 1/8" BSPT
	SPD06-02	6mm x 1/4" BSPT	ISPD14-02	1/4" x 1/4" BSPT
	SPD08-01	8mm x 1/8" BSPT	ISPD516-01	5/16" x 1/8" BSPT
	SPD08-02	8mm x 1/4" BSPT	ISPD516-02	5/16" x 1/4" BSPT
	SPD10-02	10mm x 1/4" BSPT	ISPD38-02	3/8" x 1/4" BSPT
	SPD10-03	10mm x 3/8" BSPT	ISPD38-03	3/8" x 3/8" BSPT
	SPD12-03	12mm x 3/8" BSPT	ISPD12-03	1/2" x 3/8" BSPT
	SPD12-04	12mm x 1/2" BSPT	ISPD12-04	1/2" x 1/2" BSPT
	SPD14-04	14mm x 1/2" BSPT	—	—
	SPD16-04	16mm x 1/2" BSPT	—	—
	SPD16-05	16mm x 3/4" BSPT	—	—
Straight Joiner	SPS		ISPS	
 O.D. to O.D. Tube SS316	SPS04	4mm	ISPS14	1/4"
	SPS06	6mm	ISPS16	5/16"
	SPS08	8mm	ISPS38	3/8"
	SPS10	10mm	ISPS12	1/2"
	SPS12	12mm	—	—
	SPS14	14mm	—	—
	SPS16	16mm	—	—
Bulkhead Union	SPM		ISPM	
 O.D. to O.D. Tube SS316	SPM04	4mm	ISPM14	1/4"
	SPM06	6mm	ISPM16	5/16"
	SPM08	8mm	ISPM38	3/8"
	SPM10	10mm	ISPM12	1/2"
	SPM12	12mm	—	—
	SPM14	14mm	—	—
	SPM16	16mm	—	—

Stainless Steel SS316 Push Fit Tube Connectors – Metric & Imperial

Push Fit	Model	Tube Metric
Elbow Speed Control	SSC	
O.D. Tube to BSP Thread	SSC04-01 SSC04-02 SSC06-01 SSC06-02 SSC08-01 SSC08-02 SSC10-02 SSC10-03 SSC12-03 SSC12-04	4mm x 1/8" BSPT 4mm x 1/4" BSPT 6mm x 1/8" BSPT 6mm x 1/4" BSPT 8mm x 1/8" BSPT 8mm x 1/4" BSPT 10mm x 1/4" BSPT 10mm x 3/8" BSPT 12mm x 3/8" BSPT 12mm x 1/2" BSPT



SS316

Push Fit	Model	Tube Metric	Model	Tube Imperial
Plug In Reducer	SPGJ			
O.D. Tube to Male Tube	SPGJ06-04 SPGJ08-04 SPGJ08-06 SPGJ10-06 SPGJ10-08 SPGJ12-06 SPGJ12-08 SPGJ12-10	6mm to 4mm 8mm to 4mm 8mm to 6mm 10mm to 6mm 10mm to 8mm 12mm to 6mm 12mm to 8mm 12mm to 10mm		
Plug (Male Tube)	SPP		ISPP	
O.D. Plug	SPP04 SPP06 SPP08 SPP10 SPP12	4mm Plug 6mm Plug 8mm Plug 10mm Plug 12mm Plug	ISPP14 ISPP516 ISPP38 ISPP12	1/4" Plug 5/16" Plug 3/8" Plug 1/2" Plug



SS316



Screwed Fittings – Stainless Steel SS316 – BSP & NPT

- 316 Stainless Steel
- Acid cleaned for swarf and contaminants

- 150lb pressure rating (200 psi @ 20°C working pressure)
- All threads are qualified

Fittings	Model	BSP	Model	NPT
Nipple Hex	SF27		NSF27	
	SF2701 SF2702 SF2703 SF2704 SF2705 SF2706 SF2707 SF2708 SF2709 SF2710 SF2711 SF2712	1/8" BSPT 1/4" BSPT 3/8" BSPT 1/2" BSPT 3/4" BSPT 1" BSPT 1 1/4" BSPT 1 1/2" BSPT 2" BSPT 2 1/2" BSPT 3" BSPT 4" BSPT	NSF2701 NSF2702 NSF2703 NSF2704 NSF2705 NSF2706 NSF2707 NSF2708 NSF2709 NSF2710 NSF2711 NSF2712	1/8" NPT 1/4" NPT 3/8" NPT 1/2" NPT 3/4" NPT 1" NPT 1 1/4" NPT 1 1/2" NPT 2" NPT 2 1/2" NPT 3" NPT 4" NPT
Socket	SF26		NSF26	
	SF2601 SF2602 SF2603 SF2604 SF2605 SF2606 SF2607 SF2608 SF2609 SF2610 SF2611 SF2612	1/8" BSPP 1/4" BSPP 3/8" BSPP 1/2" BSPP 3/4" BSPP 1" BSPP 1 1/4" BSPP 1 1/2" BSPP 2" BSPP 2 1/2" BSPP 3" BSPP 4" BSPP	NSF2601 NSF2602 NSF2603 NSF2604 NSF2605 NSF2606 NSF2607 NSF2608 NSF2609 NSF2610 NSF2611 NSF2612	1/8" NPS 1/4" NPS 3/8" NPS 1/2" NPS 3/4" NPS 1" NPS 1 1/4" NPS 1 1/2" NPS 2" NPS 2 1/2" NPS 3" NPS 4" NPS
Male Barrel Unions.	SF80		NSF80	
Connical Seat	SF8004 SF8005 SF8006 SF8007 SF8008 SF8009 SF8010 SF8011 SF8012	1/2" BSP 3/4" BSP 1" BSP 1 1/4" BSP 1 1/2" BSP 2" BSP 2 1/2" BSP 3" BSP 4" BSP	NSF8004 NSF8005 NSF8006 NSF8007 NSF8008 NSF8009 NSF8010 NSF8011 NSF8012	1/2" NPS 3/4" NPS 1" NPS 1 1/4" NPS 1 1/2" NPS 2" NPS 2 1/2" NPS 3" NPS 4" NPS

Fittings	Model	BSP	Model	NPT
Elbow Male to Female	SF25		NSF25	
	SF2501 SF2502 SF2503 SF2504 SF2505 SF2506 SF2507 SF2508 SF2509 SF2510 SF2511 SF2512	1/8" BSP 1/4" BSP 3/8" BSP 1/2" BSP 3/4" BSP 1" BSP 1 1/4" BSP 1 1/2" BSP 2" BSP 2 1/2" BSP 3" BSP 4" BSP	NSF2501 NSF2502 NSF2503 NSF2504 NSF2505 NSF2506 NSF2507 NSF2508 NSF2509 NSF2510 NSF2511 NSF2512	1/8" NPT 1/4" NPT 3/8" NPT 1/2" NPT 3/4" NPT 1" NPT 1 1/4" NPT 1 1/2" NPT 2" NPT 2 1/2" NPT 3" NPT 4" NPT
Tee Female	SF35		NSF35	
	SF3501 SF3502 SF3503 SF3504 SF3505 SF3506 SF3507 SF3508 SF3509 SF3510 SF3511 SF3512	1/8" BSP 1/4" BSP 3/8" BSP 1/2" BSP 3/4" BSP 1" BSP 1 1/4" BSP 1 1/2" BSP 2" BSP 2 1/2" BSP 3" BSP 4" BSP	NSF3501 NSF3502 NSF3503 NSF3504 NSF3505 NSF3506 NSF3507 NSF3508 NSF3509 NSF3510 NSF3511 NSF3512	1/8" NPS 1/4" NPS 3/8" NPS 1/2" NPS 3/4" NPS 1" NPS 1 1/4" NPS 1 1/2" NPS 2" NPS 2 1/2" NPS 3" NPS 4" NPS

Screwed Fittings – Stainless Steel SS316 – BSP & NPT

- 316 Stainless Steel
- Acid cleaned for swarf and contaminants

- 150lb pressure rating (200 psi @ 20°C working pressure)
- All threads are qualified

Fittings	Model BSP	Description	Model NPT	Description
Elbow Female to Female	SF34		NSF34	
	SF3401 SF3402 SF3403 SF3404 SF3405 SF3406 SF3407 SF3408 SF3409 SF3410 SF3411 SF3412	1/8" BSPP 1/4" BSPP 3/8" BSPP 1/2" BSPP 3/4" BSPP 1" BSPP 1 1/4" BSPP 1 1/2" BSPP 2" BSPP 2 1/2" BSPP 3" BSPP 4" BSPP	NSF3401 NSF3402 NSF3403 NSF3404 NSF3405 NSF3406 NSF3407 NSF3408 NSF3409 NSF3410 NSF3411 NSF3412	1/8" NPS 1/4" NPS 3/8" NPS 1/2" NPS 3/4" NPS 1" NPS 1 1/4" NPS 1 1/2" NPS 2" NPS 2 1/2" NPS 3" NPS 4" NPS
Reducing Bush	SF24		NSF24	
	SF240201 SF240301 SF240302 SF240402 SF240403 SF240502 SF240503 SF240504 SF240604 SF240605 SF240706 SF240806 SF240807 SF240906 SF240907 SF240908 SF241008 SF241109 SF241110 SF241211	1/4" x 1/8" BSP 3/8" x 1/8" BSP 3/8" x 1/4" BSP 1/2" x 1/4" BSP 1/2" x 3/8" BSP 3/4" x 1/4" BSP 3/4" x 3/8" BSP 3/4" x 1/2" BSP 1" x 1/2" BSP 1" x 3/4" BSP 1 1/4" x 1" BSP 1 1/2" x 1" BSP 1 1/2" x 1 1/4" BSP 2" x 1" BSP 2" x 1 1/4" BSP 2" x 1 1/2" BSP 2 1/2" x 2" BSP 3" x 2" BSP 3" x 2 1/2" BSP 4" x 3" BSP	NSF240201 NSF240301 NSF240302 NSF240402 NSF240403 NSF240502 NSF240503 NSF240504 NSF240604 NSF240605 NSF240706 NSF240806 NSF240807 NSF240906 NSF240907 NSF240908 NSF241008 NSF241109 NSF241110 NSF241211	1/4" x 1/8" NPT 3/8" x 1/8" NPT 3/8" x 1/4" NPT 1/2" x 1/4" NPT 1/2" x 3/8" NPT 3/4" x 1/4" NPT 3/4" x 3/8" NPT 3/4" x 1/2" NPT 1" x 1/2" NPT 1" x 3/4" NPT 1 1/4" x 1" NPT 1 1/2" x 1" NPT 1 1/2" x 1 1/4" NPT 2" x 1" NPT 2" x 1 1/4" NPT 2" x 1 1/2" NPT 2 1/2" x 2" NPT 3" x 2" NPT 3" x 2 1/2" NPT 4" x 3" NPT
Reducing Bush	SF73		NSF73	
	SF730201 SF730301 SF730302 SF730402 SF730403 SF730504 SF730604 SF730605 SF730706 SF730806 SF730807 SF730906 SF730907 SF730908 SF731009 SF731109 SF731110 SF731209 SF731210 SF731211	1/4" x 1/8" BSP 3/8" x 1/8" BSP 3/8" x 1/4" BSP 1/2" x 1/4" BSP 1/2" x 3/8" BSP 3/4" x 1/2" BSP 1" x 1/2" BSP 1" x 3/4" BSP 1 1/4" x 1" BSP 1 1/2" x 1" BSP 1 1/2" x 1 1/4" BSP 2" x 1" BSP 2" x 1 1/4" BSP 2" x 1 1/2" BSP 2 1/2" x 2" BSP 3" x 2" BSP 3" x 2 1/2" BSP 4" x 2" BSP 4" x 2 1/2" BSP 4" x 3" BSP	NSF730201 NSF730301 NSF730302 NSF730402 NSF730403 NSF730504 NSF730604 NSF730605 NSF730706 NSF730806 NSF730807 NSF730906 NSF730907 NSF730908 NSF731009 NSF731109 NSF731110 NSF731209 NSF731210 NSF731211	1/4" x 1/8" NPT 3/8" x 1/8" NPT 3/8" x 1/4" NPT 1/2" x 1/4" NPT 1/2" x 3/8" NPT 3/4" x 1/2" NPT 1" x 1/2" NPT 1" x 3/4" NPT 1 1/4" x 1" NPT 1 1/2" x 1" NPT 1 1/2" x 1 1/4" NPT 2" x 1" NPT 2" x 1 1/4" NPT 2" x 1 1/2" NPT 2 1/2" x 2" NPT 3" x 2" NPT 3" x 2 1/2" NPT 4" x 2" NPT 4" x 2 1/2" NPT 4" x 3" NPT
Adaptor	GAUA	BSP Female to NPT Male		
	GAUA-02-02N GAUA-03-03N GAUA-04-04N GAUA-05-05N GAUA-06-06N GAUA-07-07N GAUA-08-08N GAUA-09-09N	1/4" BSP Female x 1/4" NPT Male Adapter 3/8" BSP Female x 3/8" NPT Male Adapter 1/2" BSP Female x 1/2" NPT Male Adapter 3/4" BSP Female x 3/4" NPT Male Adapter 1" BSP Female x 1" NPT Male Adapter 1 1/4" BSP Female x 1 1/4" NPT Male Adapter 1 1/2" BSP Female x 1 1/2" NPT Male Adapter 2" BSP Female x 2" NPT Male Adapter		

Fittings	Model BSP	Description	Model NPT	Description
Plug Hex	SF64		NSF64	
	SF6401 SF6402 SF6403 SF6404 SF6405 SF6406 SF6407 SF6408 SF6409 SF6410 SF6411 SF6412	1/8" BSP 1/4" BSP 3/8" BSP 1/2" BSP 3/4" BSP 1" BSP 1 1/4" BSP 1 1/2" BSP 2" BSP 2 1/2" BSP 3" BSP 4" BSP	NSF6401 NSF6402 NSF6403 NSF6404 NSF6405 NSF6406 NSF6407 NSF6408 NSF6409 NSF6410 NSF6411 NSF6412	1/8" NPT 1/4" NPT 3/8" NPT 1/2" NPT 3/4" NPT 1" NPT 1 1/4" NPT 1 1/2" NPT 2" NPT 2 1/2" NPT 3" NPT 4" NPT
Hose Tail	SF30		ISF30	
	SF300102 SF300202 SF300302 SF300102.5 SF300202.5 SF300302.5 SF300203 SF300303 SF300403 SF300204 SF300304 SF300404 SF300504 SF300405 SF300505 SF300606 SF300707 SF300808 SF300909	1/8" BSP x 1/4" Tail 1/4" BSP x 1/4" Tail 3/8" BSP x 1/4" Tail 1/8" BSP x 5/16" Tail 1/4" BSP x 5/16" Tail 3/8" BSP x 5/16" Tail 1/4" BSP x 3/8" Tail 3/8" BSP x 3/8" Tail 1/2" BSP x 3/8" Tail 1/4" BSP x 1/2" Tail 3/8" BSP x 1/2" Tail 1/2" BSP x 1/2" Tail 3/4" BSP x 1/2" Tail 1/2" BSP x 3/4" Tail 3/4" BSP x 3/4" Tail 1" BSP x 1" Tail 1 1/4" BSP x 1 1/4" Tail 1 1/2" BSP x 1 1/2" Tail 2" BSP x 2" Tail	ISF300102 ISF300202 ISF300302 ISF300102.5 ISF300202.5 ISF300302.5 ISF300203 ISF300303 ISF300403 ISF300204 ISF300304 ISF300404 ISF300504 ISF300405 ISF300505 ISF300606 ISF300707 ISF300808 ISF300909	1/8" NPT x 1/4" Tail 1/4" NPT x 1/4" Tail 3/8" NPT x 1/4" Tail 1/8" NPT x 5/16" Tail 1/4" NPT x 5/16" Tail 3/8" NPT x 5/16" Tail 1/4" NPT x 3/8" Tail 3/8" NPT x 3/8" Tail 1/2" NPT x 3/8" Tail 1/4" NPT x 1/2" Tail 3/8" NPT x 1/2" Tail 1/2" NPT x 1/2" Tail 3/4" NPT x 1/2" Tail 1/2" NPT x 3/4" Tail 3/4" NPT x 3/4" Tail 1" NPT x 1" Tail 1 1/4" NPT x 1 1/4" Tail 1 1/2" NPT x 1 1/2" Tail 2" NPT x 2" Tail
Barrel Nipple	SF28		ISF28	
	SF2801 SF2802 SF2803 SF2804 SF2805 SF2806 SF2807 SF2808 SF2809	1/8" BSP Barrel Nipple 1/4" BSP Barrel Nipple 3/8" BSP Barrel Nipple 1/2" BSP Barrel Nipple 3/4" BSP Barrel Nipple 1" BSP Barrel Nipple 1"-1/4" BSP Barrel Nipple 1"-1/2" BSP Barrel Nipple 2" BSP Barrel Nipple	ISF2801 ISF2802 ISF2803 ISF2804 ISF2805 ISF2806 ISF2807 ISF2808 ISF2809	1/8" NPT Barrel Nipple 1/4" NPT Barrel Nipple 3/8" NPT Barrel Nipple 1/2" NPT Barrel Nipple 3/4" NPT Barrel Nipple 1" NPT Barrel Nipple 1"-1/4" NPT Barrel Nipple 1"-1/2" NPT Barrel Nipple 2" NPT Barrel Nipple
Adaptor	SF72	BSP Female to BSP Male		
	SF720201 SF720302	1/4" BSP Female x 1/8" BSP Male Adapter 3/8" BSP Female x 1/4" BSP Male Adapter		
Adaptor	NPBP	NPT Female to BSP Male		
	NPBP-02-02N NPBP-03-03N NPBP-04-04N NPBP-05-05N NPBP-06-06N NPBP-07-07N NPBP-08-08N NPBP-09-09N	1/4" NPT Female x 1/4" BSP Male Adapter 3/8" NPT Female x 3/8" BSP Male Adapter 1/2" NPT Female x 1/2" BSP Male Adapter 3/4" NPT Female x 3/4" BSP Male Adapter 1" NPT Female x 1" BSP Male Adapter 1 1/4" NPT Female x 1 1/4" BSP Male Adapter 1 1/2" NPT Female x 1 1/2" BSP Male Adapter 2" NPT Female x 2" BSP Male Adapter		



Same Day Despatch

Huge stock holdings with great service

Biggest range of Solenoid Valves

Ball Valves for every application

Butterfly Valves in Stock



Solenoid Valves

Large range of solenoid valves including direct acting, differential, high pressure, high temperature, explosion proof along with the various body material options available. Applications include solenoid valves for water, steam, chemicals, high pressure and vacuum.



Ball Valves

Ball valve range includes 316 stainless steel, nickel plated brass, UPVC, 2 way, 3 way, threaded, flanged and fire safe. All ball valves are available with pneumatic, electric and manual operation.



Butterfly Valves

Comprehensive range of Butterfly Valves for general industrial, mining and agricultural applications. Sizes from 50mm to 2400mm in wafer, lugged and flanged. All are available with manual, electric or pneumatic actuation (double acting or spring return).



Knife Gate Valves

Knife gate Valves in manual and double acting pneumatic actuation. Body materials Ductile Iron and 316 Stainless Steel with resilient (soft) and metal seat options. Applications include mining, mineral processing, power industries, slurries, sewerage and water treatment.



Check Valves

Check Valves in both Cast Iron and 316 Stainless Steel. Models include swing, piston, ball, pilot and duck bill. Applications include mining, mineral processing, power industries, sewerage, tidal and water treatment.



Other Valves

Also stock angle seat valves, needle valves, pinch valves, gate valves and globe valves for all industry applications.

YOSHITAKE

Steam products for energy saving and efficiency.

NPV VALVES

www.npvvalves.com.au

Severe duty and high pressure valves.
Valve safety lockouts.
Heavy duty valve handles.



Hawleys

- Engineering Solutions -

www.hawleys.com.au

Steam boiler level gauges.
Bronze steam valves.
Stainless steel steam valves.
Gaskets for steam and fluid applications.
Spare: Packings and boiler gauge glass.



PROCESS SYSTEMS PTY LTD

ABN 15 010 932 386

Phone 1300 887 880
Email: sales@processsystems.com.au
Website: www.valvesonline.com.au
Central Warehouse & Sales Office
Unit 4, 308 New Cleveland Rd, Tingalpa QLD 4173

WARNING

These products are intended for use in industrial applications only. Do not use these products where pressures and temperatures can exceed those listed under 'Technical Data' and in our individual 'Series' data sheets. Before using these products with fluids other than those specified, for non-industrial applications, life-support systems, or other applications not within published specifications, consult Process Systems Pty Ltd. Through misuse, age, or malfunction, components used in industrial valve applications can fail in various modes. The system designer is warned to consider the failure modes of all component parts used in industrial valve applications and to provide adequate safeguards to prevent personal injury or damage to equipment in the event of such failure. System designers must provide a warning to the user in the system instructional manual if protection against a failure mode cannot be adequately provided. System designers and end users are cautioned to review specific warnings or specifications found in instruction sheets or labels packed or attached and shipped with the products. Our policy is one of continuous research and development. We therefore reserve the right to amend without notice the specifications given in this document or our individual 'Series' data sheets.

WARRANTY INFORMATION

All valve series and other products manufactured or distributed by Process Systems Pty Ltd. are warranted by Process Systems to be free of defects in material and workmanship for a period of 1 year from the date of purchase or as the manufacturer warrants. Process Systems obligation under this warranty is limited to repair or replacement of the defective product or refund of the purchase price paid solely at the discretion of Process Systems and provided such defective product is returned to Process Systems freight prepaid and upon examination by Process Systems such product is found defective. This warranty shall be void in the event that the product has been subject to misuse, misapplication, improper maintenance, modification or tampering. This warranty is expressed in lieu of all other warranties, expressed or implied from Process Systems Pty Ltd. representatives or employees. Process Systems reserves the right to change Valve and Brochure specifications without notice.